

★ Cooling (50Hz 230V)

Outdoor unit	Combination of indoor unit	Capacity of each indoor unit								
		Each capacity (kW)		Total capacity (kW)		Total input (W)		Total current (A)		Power factor (%)
		A room	B room	Rating	(min ~ max)	Rating	(min ~ max)	Rating	(min ~ max)	Rating
2MKS50G2V1B	2.0	2.00	-	2.00	1.53 ~ 2.60	470	330 ~ 690	2.2	1.6 ~ 3.3	91
	2.5	2.50	-	2.50	1.53 ~ 3.10	660	330 ~ 920	3.2	1.6 ~ 4.4	91
	3.5	3.50	-	3.50	1.53 ~ 4.00	1090	330 ~ 1420	5.2	1.6 ~ 6.8	91
	5.0	5.00	-	5.00	1.57 ~ 5.10	2060	330 ~ 2170	9.8	1.6 ~ 10.4	91
	2.0+2.0	2.00	2.00	4.00	1.81 ~ 4.90	1050	330 ~ 1530	5.0	1.6 ~ 7.3	91
	2.0+2.5	2.00	2.50	4.50	1.81 ~ 5.00	1290	330 ~ 1600	6.2	1.6 ~ 7.6	91
	2.0+3.5	1.82	3.18	5.00	1.81 ~ 5.30	1560	330 ~ 1760	7.5	1.6 ~ 8.4	91
	2.0+5.0	1.43	3.57	5.00	1.81 ~ 5.40	1470	330 ~ 1720	7.0	1.6 ~ 8.2	91
	2.5+2.5	2.50	2.50	5.00	1.81 ~ 5.20	1560	330 ~ 1710	7.5	1.6 ~ 8.2	91
	2.5+3.5	2.08	2.92	5.00	1.81 ~ 5.30	1530	330 ~ 1760	7.3	1.6 ~ 8.4	91
	2.5+5.0	1.67	3.33	5.00	1.81 ~ 5.40	1470	330 ~ 1730	7.0	1.6 ~ 8.3	91
	3.5+3.5	2.50	2.50	5.00	1.81 ~ 5.30	1500	330 ~ 1720	7.2	1.6 ~ 8.2	91
	3.5+5.0	2.06	2.94	5.00	1.81 ~ 5.40	1440	330 ~ 1700	6.9	1.6 ~ 8.1	91

3D057678A

- NOTES
- 1

Cooling capacity is based on 27°C DB/19°C WB (indoor temperature), 35°C DB(outdoor temperature).
- 2

The total ability of a connected indoor unit is up to 8.5kW.
- 3

The above is the value for connecting with the following indoor units, 2.0, 2.5, 3.5, 4.2, 5.0 kW class: wall mounted D(NW-S) series.