4MKS58E (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.0	22.0	2.63	0.54	3.04	0.62	3.17	0.63	3.24	0.64	3.44	0.66	3.57	0.67
	25.0	2.63	0.58	2.96	0.64	3.09	0.65	3.16	0.66	3.36	0.68	3.49	0.69
	32.0	2.63	0.68	2.77	0.70	2.90	0.71	2.97	0.72	3.17	0.73	3.30	0.74
	35.0	2.56	0.71	2.69	0.72	2.82	0.73	**2.89**	**0.74**	3.09	0.76	3.22	0.77
	40.0	2.42	0.76	2.56	0.77	2.69	0.78	2.76	0.79	2.96	0.80	3.09	0.82
	43.0	2.34	0.79	2.47	0.80	2.61	0.81	2.67	0.82	2.87	0.83	3.01	0.84
	46.0	2.26	0.82	2.39	0.83	2.53	0.84	2.59	0.85	2.79	0.86	2.93	0.87
2.5	22.0	2.63	0.54	3.23	0.72	3.43	0.75	3.50	0.76	3.71	0.78	3.86	0.79
	25.0	2.63	0.58	3.19	0.76	3.34	0.78	3.41	0.78	3.63	0.81	3.77	0.82
	32.0	2.63	0.68	2.99	0.83	3.14	0.84	3.21	0.85	3.42	0.87	3.57	0.89
	35.0	2.63	0.79	2.90	0.86	3.05	0.87	**3.12**	**0.88**	3.34	0.90	3.48	0.92
	40.0	2.62	0.90	2.76	0.91	2.90	0.93	2.97	0.93	3.19	0.96	3.33	0.97
	43.0	2.53	0.93	2.67	0.95	2.82	0.96	2.89	0.97	3.10	0.99	3.25	1.00
	46.0	2.44	0.97	2.58	0.98	2.73	1.00	2.80	1.00	3.02	1.03	3.16	1.04
3.5	22.0	3.00	0.66	3.68	0.83	4.42	1.03	4.73	1.11	5.02	1.14	5.22	1.16
	25.0	3.00	0.71	3.68	0.89	4.42	1.10	4.61	1.15	4.90	1.18	5.10	1.20
	32.0	3.00	0.84	3.68	1.06	4.24	1.24	4.34	1.25	4.63	1.28	4.82	1.30
	35.0	3.00	0.90	3.68	1.14	4.12	1.28	**4.22**	**1.29**	4.51	1.32	4.71	1.34
	40.0	3.00	1.03	3.68	1.31	3.93	1.36	4.02	1.37	4.32	1.40	4.51	1.42
	43.0	3.00	1.12	3.61	1.39	3.81	1.41	3.91	1.42	4.20	1.45	4.39	1.47
	46.0	3.00	1.22	3.50	1.44	3.69	1.46	3.79	1.47	4.08	1.50	4.27	1.52
4.2	22.0	3.00	0.66	3.68	0.83	4.42	1.03	4.81	1.20	5.59	1.43	5.81	1.45
	25.0	3.00	0.71	3.68	0.89	4.42	1.10	4.81	1.29	5.46	1.47	5.68	1.50
	32.0	3.00	0.84	3.68	1.06	4.42	1.39	4.81	1.54	5.16	1.59	5.37	1.62
	35.0	3.00	0.90	3.68	1.14	4.42	1.50	**4.70**	**1.61**	5.02	1.65	5.24	1.68
	40.0	3.00	1.03	3.68	1.31	4.37	1.70	4.48	1.71	4.81	1.75	5.02	1.77
	43.0	3.00	1.12	3.68	1.49	4.24	1.76	4.35	1.77	4.67	1.81	4.89	1.84
	46.0	3.00	1.22	3.68	1.64	4.11	1.83	4.22	1.84	4.54	1.88	4.76	1.90
5.0	22.0	3.68	0.92	4.52	1.18	5.43	1.49	5.90	1.68	6.43	1.80	6.68	1.83
	25.0	3.68	0.98	4.52	1.27	5.43	1.61	5.90	1.81	6.28	1.86	6.52	1.89
	32.0	3.68	1.17	4.52	1.51	5.43	1.95	5.55	1.96	5.92	2.01	6.17	2.04
	35.0	3.68	1.26	4.52	1.64	5.28	2.02	**5.40**	**2.03**	5.77	2.08	6.02	2.11
	40.0	3.68	1.45	4.52	1.91	5.02	2.14	5.15	2.16	5.52	2.21	5.77	2.24
	43.0	3.68	1.58	4.52	2.10	4.87	2.22	5.00	2.24	5.37	2.28	5.62	2.32
	46.0	3.68	1.74	4.33	2.07	4.53	2.07	4.63	2.07	4.93	2.07	5.12	2.07
2.0+2.0	22.0	5.26	1.27	6.27	1.60	6.54	1.63	6.68	1.65	7.09	1.69	7.37	1.72
	25.0	5.26	1.37	6.10	1.66	6.38	1.69	6.52	1.70	6.93	1.75	7.20	1.78
	32.0	5.26	1.67	5.71	1.80	5.99	1.83	6.13	1.85	6.54	1.89	6.81	1.92
	35.0	5.26	1.83	5.55	1.87	5.82	1.90	**5.96**	**1.91**	6.37	1.96	6.65	1.99
	40.0	5.00	1.95	5.27	1.98	5.55	2.01	5.68	2.03	6.09	2.08	6.37	2.11
	43.0	4.83	2.03	5.10	2.06	5.38	2.09	5.52	2.10	5.93	2.15	6.20	2.18
	46.0	4.63	2.07	4.86	2.07	5.10	2.07	5.21	2.07	5.55	2.07	5.76	2.07

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059226A