**4MKS58E**

**Cooling [50Hz 230V]**

| Combination (Capacity) | Outdoor air temp. °CDB | Indoor air temp.: °CWB | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | 14°C | | 16°C | | 18°C | | 19°C | | 22°C | | 24°C | |
| | | TC | PI | TC | PI | TC | PI | TC | PI | TC | PI | TC | PI |
| | | kW | kW | kW | kW | kW | kW | kW | kW | kW | kW | kW | kW |
| 2.0+2.0+2.5+3.5 | 22.0 | 7.14 | 1.77 | 7.47 | 1.80 | 7.80 | 1.84 | 7.96 | 1.85 | 8.45 | 1.90 | 8.78 | 1.94 |
| | 25.0 | 6.94 | 1.83 | 7.27 | 1.86 | 7.60 | 1.90 | 7.76 | 1.92 | 8.25 | 1.97 | 8.58 | 2.00 |
| | 32.0 | 6.48 | 1.99 | 6.81 | 2.03 | 7.13 | 2.06 | 7.30 | 2.08 | 7.79 | 2.13 | 8.12 | 2.16 |
| | 35.0 | 6.28 | 2.07 | 6.61 | 2.10 | 6.94 | 2.14 | 7.10 | 2.15 | 7.59 | 2.20 | 7.92 | 2.24 |
| | 40.0 | 5.95 | 2.20 | 6.28 | 2.23 | 6.61 | 2.27 | 6.77 | 2.28 | 7.26 | 2.34 | 7.59 | 2.37 |
| | 43.0 | 5.75 | 2.28 | 6.08 | 2.32 | 6.41 | 2.35 | 6.57 | 2.37 | 7.06 | 2.42 | 7.39 | 2.45 |
| | 46.0 | 5.22 | 2.07 | 5.48 | 2.07 | 5.72 | 2.07 | 5.85 | 2.07 | 6.20 | 2.07 | 6.44 | 2.07 |
| 2.0+2.5+2.5+2.5 | 22.0 | 7.14 | 1.77 | 7.47 | 1.80 | 7.80 | 1.84 | 7.96 | 1.85 | 8.45 | 1.90 | 8.78 | 1.94 |
| | 25.0 | 6.94 | 1.83 | 7.27 | 1.86 | 7.60 | 1.90 | 7.76 | 1.92 | 8.25 | 1.97 | 8.58 | 2.00 |
| | 32.0 | 6.48 | 1.99 | 6.81 | 2.03 | 7.13 | 2.06 | 7.30 | 2.08 | 7.79 | 2.13 | 8.12 | 2.16 |
| | 35.0 | 6.28 | 2.07 | 6.61 | 2.10 | 6.94 | 2.14 | 7.10 | 2.15 | 7.59 | 2.20 | 7.92 | 2.24 |
| | 40.0 | 5.95 | 2.20 | 6.28 | 2.23 | 6.61 | 2.27 | 6.77 | 2.28 | 7.26 | 2.34 | 7.59 | 2.37 |
| | 43.0 | 5.75 | 2.28 | 6.08 | 2.32 | 6.41 | 2.35 | 6.57 | 2.37 | 7.06 | 2.42 | 7.39 | 2.45 |
| | 46.0 | 5.22 | 2.07 | 5.48 | 2.07 | 5.72 | 2.07 | 5.85 | 2.07 | 6.20 | 2.07 | 6.44 | 2.07 |
| 2.5+2.5+2.5+2.5 | 22.0 | 7.14 | 1.77 | 7.47 | 1.80 | 7.80 | 1.84 | 7.96 | 1.85 | 8.45 | 1.90 | 8.78 | 1.94 |
| | 25.0 | 6.94 | 1.83 | 7.27 | 1.86 | 7.60 | 1.90 | 7.76 | 1.92 | 8.25 | 1.97 | 8.58 | 2.00 |
| | 32.0 | 6.48 | 1.99 | 6.81 | 2.03 | 7.13 | 2.06 | 7.30 | 2.08 | 7.79 | 2.13 | 8.12 | 2.16 |
| | 35.0 | 6.28 | 2.07 | 6.61 | 2.10 | 6.94 | 2.14 | 7.10 | 2.15 | 7.59 | 2.20 | 7.92 | 2.24 |
| | 40.0 | 5.95 | 2.20 | 6.28 | 2.23 | 6.61 | 2.27 | 6.77 | 2.28 | 7.26 | 2.34 | 7.59 | 2.37 |
| | 43.0 | 5.75 | 2.28 | 6.08 | 2.32 | 6.41 | 2.35 | 6.57 | 2.37 | 7.06 | 2.42 | 7.39 | 2.45 |
| | 46.0 | 5.22 | 2.07 | 5.48 | 2.07 | 5.72 | 2.07 | 5.85 | 2.07 | 6.20 | 2.07 | 6.44 | 2.07 |

3D052359-6A-B

## SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)

## NOTES

Capacities are based on following conditions
Corresponding refrigerant piping length: 7.5 m
Level difference: 0 m
The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5kW class; wall mounted C series
5.0kW class; wall mounted E series