4MKS58E

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
3.5+5.0	22.0	6.96	1.71	7.28	1.74	7.60	1.78	7.76	1.79	8.24	1.84	8.55	1.88
	25.0	6.77	1.77	7.09	1.80	7.41	1.84	7.56	1.85	8.04	1.90	8.36	1.94
	32.0	6.32	1.93	6.64	1.96	6.95	1.99	7.11	2.01	7.59	2.06	7.91	2.09
	35.0	6.12	2.00	6.44	2.03	6.76	2.07	6.92	2.08	7.40	2.13	7.72	2.17
	40.0	5.80	2.13	6.12	2.16	6.44	2.19	6.60	2.21	7.08	2.26	7.39	2.29
	43.0	5.61	2.21	5.93	2.24	6.25	2.27	6.40	2.29	6.88	2.34	7.20	2.37
	46.0	5.16	2.07	5.42	2.07	5.67	2.07	5.79	2.07	6.15	2.07	6.38	2.07
5.0+5.0	22.0	7.04	1.73	7.36	1.77	7.69	1.80	7.85	1.82	8.33	1.87	8.65	1.90
	25.0	6.85	1.80	7.17	1.83	7.49	1.86	7.65	1.88	8.14	1.93	8.46	1.97
	32.0	6.39	1.95	6.71	1.99	7.03	2.02	7.20	2.04	7.68	2.09	8.00	2.12
	35.0	6.19	2.03	6.52	2.06	6.84	2.10	7.00	2.11	7.48	2.16	7.81	2.20
	40.0	5.87	2.16	6.19	2.19	6.51	2.22	6.67	2.24	7.16	2.29	7.48	2.33
	43.0	5.67	2.24	5.99	2.27	6.32	2.31	6.48	2.32	6.96	2.37	7.28	2.41
	46.0	5.19	2.07	5.44	2.07	5.69	2.07	5.81	2.07	6.17	2.07	6.40	2.07
2.0+2.0+2.0	22.0	7.08	1.78	7.41	1.81	7.73	1.84	7.89	1.86	8.38	1.91	8.70	1.95
	25.0	6.88	1.84	7.21	1.87	7.53	1.91	7.70	1.93	8.18	1.98	8.51	2.01
	32.0	6.43	2.00	6.75	2.04	7.07	2.07	7.24	2.09	7.72	2.14	8.05	2.17
	35.0	6.23	2.08	6.55	2.11	6.88	2.15	7.04	2.16	7.53	2.21	7.85	2.25
	40.0	5.90	2.21	6.23	2.24	6.55	2.28	6.71	2.29	7.20	2.35	7.52	2.38
	43.0	5.70	2.29	6.03	2.33	6.35	2.36	6.52	2.38	7.00	2.43	7.33	2.47
	46.0	5.17	2.07	5.42	2.07	5.67	2.07	5.79	2.07	6.14	2.07	6.37	2.07
2.0+2.0+2.5	22.0	7.08	1.78	7.41	1.81	7.73	1.84	7.89	1.86	8.38	1.91	8.70	1.95
	25.0	6.88	1.84	7.21	1.87	7.53	1.91	7.70	1.93	8.18	1.98	8.51	2.01
	32.0	6.43	2.00	6.75	2.04	7.07	2.07	7.24	2.09	7.72	2.14	8.05	2.17
	35.0	6.23	2.08	6.55	2.11	6.88	2.15	7.04	2.16	7.53	2.21	7.85	2.25
	40.0	5.90	2.21	6.23	2.24	6.55	2.28	6.71	2.29	7.20	2.35	7.52	2.38
	43.0	5.70	2.29	6.03	2.33	6.35	2.36	6.52	2.38	7.00	2.43	7.33	2.47
	46.0	5.17	2.07	5.42	2.07	5.67	2.07	5.79	2.07	6.14	2.07	6.37	2.07
2.0+2.0+3.5	22.0	7.10	1.78	7.43	1.81	7.75	1.84	7.91	1.86	8.40	1.91	8.73	1.95
	25.0	6.90	1.84	7.23	1.87	7.55	1.91	7.72	1.93	8.21	1.98	8.53	2.01
	32.0	6.44	2.00	6.77	2.04	7.09	2.07	7.26	2.09	7.75	2.14	8.07	2.17
	35.0	6.25	2.08	6.57	2.11	6.90	2.15	7.06	2.16	7.55	2.21	7.87	2.25
	40.0	5.92	2.21	6.24	2.24	6.57	2.28	6.73	2.29	7.22	2.35	7.54	2.38
	43.0	5.72	2.29	6.05	2.33	6.37	2.36	6.53	2.38	7.02	2.43	7.35	2.47
	46.0	5.18	2.07	5.44	2.07	5.68	2.07	5.81	2.07	6.16	2.07	6.39	2.07
2.0+2.0+5.0	22.0	7.34	1.80	7.68	1.83	8.02	1.87	8.18	1.89	8.69	1.94	9.02	1.97
	25.0	7.14	1.86	7.48	1.90	7.81	1.93	7.98	1.95	8.48	2.00	8.82	2.04
	32.0	6.66	2.03	7.00	2.06	7.34	2.10	7.50	2.12	8.01	2.17	8.34	2.20
	35.0	6.46	2.10	6.80	2.14	7.13	2.17	7.30	2.19	7.80	2.24	8.14	2.28
	40.0	6.12	2.24	6.46	2.27	6.79	2.31	6.96	2.33	7.46	2.38	7.80	2.41
	43.0	5.92	2.32	6.25	2.36	6.59	2.39	6.76	2.41	7.26	2.46	7.60	2.50
	46.0	5.32	2.07	5.58	2.07	5.83	2.07	5.95	2.07	6.32	2.07	6.55	2.07

3D052359-8A-A

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)

NOTES

Capacities are based on following conditions
Corresponding refrigerant piping length: 7.5 m
Level difference: 0 m
The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5kW class; wall mounted D series
5.0kW class; wall mounted E series