4MKS58E

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.5+2.5	22.0	7.08	1.78	7.41	1.81	7.73	1.84	7.89	1.86	8.38	1.91	8.70	1.95
	25.0	6.88	1.84	7.21	1.87	7.53	1.91	7.70	1.93	8.18	1.98	8.51	2.01
	32.0	6.43	2.00	6.75	2.04	7.07	2.07	7.24	2.09	7.72	2.14	8.05	2.17
	35.0	6.23	2.08	6.55	2.11	6.88	2.15	7.04	2.16	7.53	2.21	7.85	2.25
	40.0	5.90	2.21	6.23	2.24	6.55	2.28	6.71	2.29	7.20	2.35	7.52	2.38
	43.0	5.70	2.29	6.03	2.33	6.35	2.36	6.52	2.38	7.00	2.43	7.33	2.47
	46.0	5.17	2.07	5.42	2.07	5.67	2.07	5.79	2.07	6.14	2.07	6.37	2.07
2.0+2.5+3.5	22.0	7.10	1.78	7.43	1.81	7.75	1.84	7.91	1.86	8.40	1.91	8.73	1.95
	25.0	6.90	1.84	7.23	1.87	7.55	1.91	7.72	1.93	8.21	1.98	8.53	2.01
	32.0	6.44	2.00	6.77	2.04	7.09	2.07	7.26	2.09	7.75	2.14	8.07	2.17
	35.0	6.25	2.08	6.57	2.11	6.90	2.15	7.06	2.16	7.55	2.21	7.87	2.25
	40.0	5.92	2.21	6.24	2.24	6.57	2.28	6.73	2.29	7.22	2.35	7.54	2.38
	43.0	5.72	2.29	6.05	2.33	6.37	2.36	6.53	2.38	7.02	2.43	7.35	2.47
	46.0	5.18	2.07	5.44	2.07	5.68	2.07	5.81	2.07	6.16	2.07	6.39	2.07
2.0+2.5+5.0	22.0	7.34	1.80	7.68	1.83	8.02	1.87	8.18	1.89	8.69	1.94	9.02	1.97
	25.0	7.14	1.86	7.48	1.90	7.81	1.93	7.98	1.95	8.48	2.00	8.82	2.04
	32.0	6.66	2.03	7.00	2.06	7.34	2.10	7.50	2.12	8.01	2.17	8.34	2.20
	35.0	6.46	2.10	6.80	2.14	7.13	2.17	7.30	2.24	7.80	2.24	8.14	2.28
	40.0	6.12	2.24	6.46	2.27	6.79	2.31	6.96	2.33	7.46	2.38	7.80	2.41
	43.0	5.92	2.32	6.25	2.36	6.59	2.39	6.76	2.41	7.26	2.46	7.60	2.50
	46.0	5.28	2.07	5.53	2.07	5.78	2.07	5.90	2.07	6.26	2.07	6.49	2.07
2.0+3.5+3.5	22.0	7.11	1.78	7.44	1.81	7.76	1.84	7.93	1.86	8.41	1.91	8.74	1.95
	25.0	6.91	1.84	7.24	1.87	7.57	1.91	7.73	1.93	8.22	1.98	8.54	2.01
	32.0	6.45	2.00	6.78	2.04	7.10	2.07	7.27	2.09	7.76	2.14	8.08	2.17
	35.0	6.26	2.08	6.58	2.11	6.91	2.15	7.07	2.16	7.56	2.21	7.88	2.25
	40.0	5.93	2.21	6.25	2.24	6.58	2.28	6.74	2.29	7.23	2.35	7.56	2.38
	43.0	5.73	2.29	6.05	2.33	6.38	2.36	6.54	2.38	7.03	2.43	7.36	2.47
	46.0	5.19	2.07	5.44	2.07	5.69	2.07	5.81	2.07	6.17	2.07	6.40	2.07
2.5+2.5+2.5	22.0	7.08	1.78	7.41	1.81	7.73	1.84	7.89	1.86	8.38	1.91	8.70	1.95
	25.0	6.88	1.84	7.21	1.87	7.53	1.91	7.70	1.93	8.18	1.98	8.51	2.01
	32.0	6.43	2.00	6.75	2.04	7.07	2.07	7.24	2.09	7.72	2.14	8.05	2.17
	35.0	6.23	2.08	6.55	2.11	6.88	2.15	7.04	2.16	7.53	2.21	7.85	2.25
	40.0	5.90	2.21	6.23	2.24	6.55	2.28	6.71	2.29	7.20	2.35	7.52	2.38
	43.0	5.70	2.29	6.03	2.33	6.35	2.36	6.52	2.38	7.00	2.43	7.33	2.47
	46.0	5.17	2.07	5.42	2.07	5.67	2.07	5.79	2.07	6.14	2.07	6.37	2.07
2.5+2.5+3.5	22.0	7.10	1.78	7.43	1.81	7.75	1.84	7.91	1.86	8.40	1.91	8.73	1.95
	25.0	6.90	1.84	7.23	1.87	7.55	1.91	7.72	1.93	8.21	1.98	8.53	2.01
	32.0	6.44	2.00	6.77	2.04	7.09	2.07	7.26	2.09	7.75	2.14	8.07	2.17
	35.0	6.25	2.08	6.57	2.11	6.90	2.15	7.06	2.16	7.55	2.21	7.87	2.25
	40.0	5.92	2.21	6.24	2.24	6.57	2.28	6.73	2.29	7.22	2.35	7.54	2.38
	43.0	5.72	2.29	6.05	2.33	6.37	2.36	6.53	2.38	7.02	2.43	7.35	2.47
	46.0	5.18	2.07	5.44	2.07	5.68	2.07	5.81	2.07	6.16	2.07	6.39	2.07

3D052359-8A-B

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)

NOTES

Capacities are based on following conditions
Corresponding refrigerant piping length: 7.5 m
Level difference: 0 m
The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5kW class; wall mounted D series
5.0kW class; wall mounted E series