4MKS58E (★ cooling 50Hz 230V)

Outdoor unit	Combination of indoor unit	Capacity of each indoor unit										
		Each capacity (kW)				Total capacity (kW)		Total input (W)		Total current (A)		Power factor (%)
		A Room	B Room	C Room	D Room	Rating	(Min.~max.)	Rating	(Min.~max.)	Rating	(Min.~max.)	Rating
4MKS58E3V1B	2.0	2.00	---	---	---	2.00	1.76 ~ 2.89	460	350 ~ 740	2.1	1.6 ~ 3.4	96
	2.5	2.50	---	---	---	2.50	1.76 ~ 3.12	620	350 ~ 880	2.8	1.6 ~ 3.9	97
	3.5	3.50	---	---	---	3.50	1.76 ~ 4.22	960	350 ~ 1290	4.3	1.6 ~ 5.7	98
	4.2	4.20	---	---	---	4.20	1.76 ~ 4.70	1380	350 ~ 1610	6.1	1.6 ~ 7.1	98
	5.0	---	---	5.00	---	5.00	1.79 ~ 5.40	1750	350 ~ 2030	7.7	1.5 ~ 8.9	99
	2.0+2.0	2.00	2.00	---	---	4.00	1.88 ~ 5.96	950	350 ~ 1910	4.2	1.5 ~ 8.4	99
	2.0+2.5	2.00	2.50	---	---	4.50	1.88 ~ 6.23	1180	350 ~ 2140	5.2	1.5 ~ 9.4	99
	2.0+3.5	1.86	3.25	---	---	5.11	1.88 ~ 6.24	1520	350 ~ 2140	6.7	1.5 ~ 9.4	99
	2.0+4.2	1.70	3.57	---	---	5.27	1.88 ~ 6.25	1620	350 ~ 2140	7.1	1.5 ~ 9.4	99
	2.0+5.0	1.56	---	3.90	---	5.46	1.88 ~ 6.47	1580	350 ~ 2070	6.9	1.5 ~ 9.1	99
	2.5+2.5	2.50	2.50	---	---	5.00	1.88 ~ 6.23	1450	350 ~ 2140	6.4	1.5 ~ 9.4	99
	2.5+3.5	2.18	3.05	---	---	5.23	1.88 ~ 6.35	1580	350 ~ 2160	6.9	1.5 ~ 9.5	99
	2.5+4.2	2.01	3.39	---	---	5.40	1.88 ~ 6.36	1720	350 ~ 2160	7.6	1.5 ~ 9.5	99
	2.5+5.0	1.86	---	3.71	---	5.57	1.88 ~ 6.47	1640	350 ~ 2070	7.2	1.5 ~ 9.1	99
	3.5+3.5	2.73	2.73	---	---	5.46	1.88 ~ 6.40	1700	350 ~ 2160	7.5	1.5 ~ 9.5	99
	3.5+4.2	2.55	3.05	---	---	5.60	1.88 ~ 6.41	1800	350 ~ 2160	7.9	1.5 ~ 9.5	99
	3.5+5.0	2.39	---	3.41	---	5.80	1.88 ~ 6.49	1810	350 ~ 2090	7.9	1.5 ~ 9.2	99
	4.2+4.2	2.89	2.89	---	---	5.78	1.88 ~ 6.42	1900	350 ~ 2160	8.3	1.5 ~ 9.5	99
	4.2+5.0	2.65	---	3.15	---	5.80	1.88 ~ 6.50	1810	350 ~ 2090	7.9	1.5 ~ 9.2	99
	5.0+5.0	---	---	2.90	2.90	5.80	1.89 ~ 6.64	1780	350 ~ 2110	7.8	1.5 ~ 9.3	99
	2.0+2.0+2.0	1.74	1.74	1.74	---	5.22	1.86 ~ 7.04	1260	350 ~ 2160	5.5	1.5 ~ 9.5	99
	2.0+2.0+2.5	1.64	1.64	2.05	---	5.33	1.86 ~ 7.04	1310	350 ~ 2160	5.8	1.5 ~ 9.5	99
	2.0+2.0+3.5	1.49	1.49	2.60	---	5.58	1.95 ~ 7.06	1410	370 ~ 2160	6.2	1.6 ~ 9.5	99
	2.0+2.0+4.2	1.41	1.41	2.97	---	5.80	1.95 ~ 7.07	1510	370 ~ 2160	6.6	1.6 ~ 9.5	99
	2.0+2.0+5.0	1.29	1.29	3.22	---	5.80	1.84 ~ 7.30	1560	350 ~ 2260	6.9	1.5 ~ 9.9	99
	2.0+2.5+2.5	1.56	1.95	1.95	---	5.46	1.86 ~ 7.04	1380	350 ~ 2160	6.1	1.5 ~ 9.5	99
	2.0+2.5+3.5	1.42	1.78	2.49	---	5.69	1.95 ~ 7.06	1480	370 ~ 2160	6.5	1.6 ~ 9.5	99
	2.0+2.5+4.2	1.33	1.67	2.80	---	5.80	1.95 ~ 7.07	1510	370 ~ 2160	6.6	1.6 ~ 9.5	99
	2.0+2.5+5.0	1.22	1.53	3.05	---	5.80	1.84 ~ 7.30	1560	350 ~ 2260	6.9	1.5 ~ 9.9	99
	2.0+3.5+3.5	1.28	2.26	2.26	---	5.80	1.86 ~ 7.07	1570	350 ~ 2160	6.9	1.5 ~ 9.5	99
	2.0+3.5+4.2	1.20	2.09	2.51	---	5.80	1.85 ~ 7.08	1570	350 ~ 2160	6.9	1.5 ~ 9.5	99
	2.5+2.5+2.5	1.86	1.86	1.86	---	5.58	1.95 ~ 7.04	1410	370 ~ 2160	6.2	1.6 ~ 9.5	99
	2.5+2.5+3.5	1.71	1.71	2.38	---	5.80	1.95 ~ 7.06	1570	370 ~ 2160	6.9	1.6 ~ 9.5	99
	2.5+2.5+4.2	1.58	1.58	2.65	---	5.80	1.95 ~ 7.07	1570	370 ~ 2160	6.9	1.6 ~ 9.5	99
	2.5+2.5+5.0	1.45	1.45	2.90	---	5.80	1.84 ~ 7.30	1540	350 ~ 2260	6.8	1.5 ~ 9.9	99
	2.5+3.5+3.5	1.52	2.14	2.14	---	5.80	1.95 ~ 7.07	1620	380 ~ 2160	7.1	1.7 ~ 9.5	99
	2.0+2.0+2.0+2.0	1.42	1.42	1.42	1.42	5.68	1.96 ~ 7.30	1490	400 ~ 2160	6.5	1.8 ~ 9.5	99
	2.0+2.0+2.0+2.5	1.36	1.36	1.36	1.72	5.80	1.96 ~ 7.30	1520	400 ~ 2160	6.7	1.8 ~ 9.5	99
	2.0+2.0+2.0+3.5	1.22	1.22	1.22	2.14	5.80	1.97 ~ 7.30	1520	400 ~ 2160	6.7	1.8 ~ 9.5	99
	2.0+2.0+2.5+2.5	1.29	1.29	1.61	1.61	5.80	1.96 ~ 7.30	1520	400 ~ 2160	6.7	1.8 ~ 9.5	99
	2.0+2.0+2.5+3.5	1.16	1.16	1.45	2.03	5.80	1.99 ~ 7.30	1520	400 ~ 2160	6.7	1.8 ~ 9.5	99
	2.0+2.5+2.5+2.5	1.21	1.53	1.53	1.53	5.80	1.97 ~ 7.30	1520	400 ~ 2160	6.7	1.8 ~ 9.5	99
	2.5+2.5+2.5+2.5	1.45	1.45	1.45	1.45	5.80	1.99 ~ 7.30	1520	400 ~ 2160	6.7	1.8 ~ 9.5	99

3D059225

NOTES

1 Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).

2 The total ability of connected a indoor unit is up to 10.0kW

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2, 5.0 kW class; wall mounted G series

4 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m