4MKS75F2V1B

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.5+7.1	22.0	8.81	2.39	9.22	2.44	9.62	2.48	9.82	2.51	10.43	2.58	10.83	2.62
	25.0	8.57	2.48	8.97	2.52	9.37	2.57	9.58	2.59	10.18	2.66	10.58	2.71
	32.0	8.00	2.70	8.40	2.74	8.80	2.79	9.00	2.81	9.61	2.88	10.01	2.93
	35.0	7.75	2.80	8.15	2.84	8.56	2.89	**8.76**	**2.91**	9.37	2.98	9.77	3.03
	40.0	7.21	2.81	7.56	2.81	7.90	2.81	8.06	2.81	8.55	2.81	8.87	2.81
	43.0	6.88	2.31	6.66	2.31	6.94	2.31	7.07	2.31	7.47	2.31	7.73	2.31
	46.0	5.37	1.80	5.59	1.80	5.80	1.80	5.91	1.80	6.22	1.80	6.42	1.80
2.0+3.5+3.5	22.0	8.12	2.27	8.49	2.31	8.86	2.36	9.05	2.38	9.60	2.44	9.98	2.49
	25.0	7.89	2.35	8.26	2.39	8.64	2.44	8.82	2.46	9.38	2.53	9.75	2.57
	32.0	7.37	2.56	7.74	2.60	8.11	2.64	8.30	2.67	8.85	2.73	9.22	2.78
	35.0	7.14	2.65	7.51	2.70	7.88	2.74	**8.07**	**2.76**	8.63	2.83	9.00	2.87
	40.0	6.75	2.81	7.09	2.81	7.42	2.81	7.58	2.81	8.05	2.81	8.35	2.81
	43.0	6.01	2.31	6.28	2.31	6.55	2.31	6.68	2.31	7.06	2.31	7.31	2.31
	46.0	5.08	1.80	5.29	1.80	5.50	1.80	5.60	1.80	5.90	1.80	6.09	1.80
2.0+3.5+5.0	22.0	8.64	2.31	9.04	2.35	9.43	2.40	9.63	2.42	10.22	2.49	10.62	2.53
	25.0	8.40	2.39	8.80	2.44	9.19	2.48	9.39	2.50	9.98	2.57	10.38	2.62
	32.0	7.84	2.60	8.24	2.65	8.63	2.69	8.83	2.72	9.42	2.78	9.82	2.83
	35.0	7.60	2.70	8.00	2.75	8.39	2.79	**8.59**	**2.81**	9.18	2.88	9.58	2.93
	40.0	7.15	2.81	7.49	2.81	7.83	2.81	8.00	2.81	8.49	2.81	8.81	2.81
	43.0	6.32	2.31	6.60	2.31	6.88	2.31	7.01	2.31	7.41	2.31	7.67	2.31
	46.0	5.31	1.80	5.53	1.80	5.75	1.80	5.85	1.80	6.16	1.80	6.36	1.80
2.0+3.5+6.0	22.0	8.80	2.39	9.20	2.44	9.61	2.48	9.81	2.51	10.41	2.58	10.82	2.62
	25.0	8.56	2.48	8.96	2.52	9.36	2.57	9.56	2.59	10.17	2.66	10.57	2.71
	32.0	7.99	2.70	8.39	2.74	8.79	2.79	8.99	2.81	9.60	2.88	10.00	2.93
	35.0	7.74	2.80	8.15	2.84	8.55	2.89	**8.75**	**2.91**	9.35	2.98	9.76	3.03
	40.0	7.20	2.81	7.55	2.81	7.89	2.81	8.05	2.81	8.54	2.81	8.86	2.81
	43.0	6.37	2.31	6.66	2.31	6.93	2.31	7.07	2.31	7.47	2.31	7.72	2.31
	46.0	5.37	1.80	5.59	1.80	5.80	1.80	5.90	1.80	6.21	1.80	6.41	1.80
2.0+3.5+7.1	22.0	9.00	2.51	9.42	2.56	9.83	2.61	10.03	2.64	10.65	2.71	11.06	2.76
	25.0	8.75	2.61	9.16	2.65	9.58	2.70	9.78	2.73	10.40	2.80	10.81	2.85
	32.0	8.17	2.83	8.58	2.88	8.99	2.93	9.20	2.96	9.82	3.03	10.23	3.08
	35.0	7.92	2.94	8.33	2.99	8.74	3.04	**8.95**	**3.06**	9.57	3.14	9.98	3.19
	40.0	7.27	2.81	7.61	2.81	7.95	2.81	8.11	2.81	8.60	2.81	8.91	2.81
	43.0	6.45	2.31	6.73	2.31	7.00	2.31	7.14	2.31	7.53	2.31	7.79	2.31
	46.0	5.44	1.80	5.66	1.80	5.87	1.80	5.97	1.80	6.28	1.80	6.48	1.80
2.0+5.0+5.0	22.0	8.90	2.18	9.31	2.22	9.72	2.26	9.92	2.28	10.53	2.35	10.94	2.39
	25.0	8.65	2.26	9.06	2.30	9.47	2.34	9.67	2.36	10.29	2.43	10.69	2.47
	32.0	8.08	2.45	8.49	2.50	8.89	2.54	9.10	2.56	9.71	2.62	10.12	2.67
	35.0	7.83	2.55	8.24	2.59	8.65	2.63	**8.85**	**2.65**	9.46	2.72	9.87	2.76
	40.0	7.42	2.71	7.83	2.75	8.23	2.79	8.43	2.81	8.94	2.81	9.28	2.81
	43.0	6.58	2.31	6.88	2.31	7.17	2.31	7.32	2.31	7.74	2.31	8.01	2.31
	46.0	5.48	1.80	5.72	1.80	5.94	1.80	6.06	1.80	6.38	1.80	6.60	1.80

3D056469

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)

NOTES

1 Capacities are based on following conditions
Corresponding refrigerant piping length : 5m
Level difference : 0m

2 The bold line [ ] is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5 kW class: wall mounted D series
5.0, 6.0, 7.1 kW class: wall mounted F series