4MKS75F2V1B

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.0+6.0	22.0	8.41	2.14	8.79	2.19	9.18	2.23	9.37	2.25	9.95	2.31	10.33	2.35
	25.0	8.18	2.22	8.56	2.26	8.95	2.31	9.14	2.33	9.72	2.39	10.10	2.43
	32.0	7.63	2.42	8.02	2.46	8.40	2.50	8.59	2.52	9.17	2.58	9.56	2.63
	35.0	7.40	2.51	7.78	2.55	8.17	2.59	**8.36**	**2.61**	8.94	2.68	9.32	2.72
	40.0	7.01	2.67	7.39	2.71	7.78	2.75	7.97	2.77	8.51	2.81	8.83	2.81
	43.0	6.28	2.31	6.57	2.31	6.85	2.31	6.99	2.31	7.40	2.31	7.66	2.31
	46.0	5.26	1.80	5.49	1.80	5.70	1.80	5.81	1.80	6.13	1.80	6.33	1.80
2.0+2.0+7.1	22.0	8.75	2.35	9.15	2.40	9.55	2.44	9.75	2.46	10.35	2.53	10.76	2.58
	25.0	8.51	2.43	8.91	2.48	9.31	2.53	9.51	2.55	10.11	2.62	10.51	2.66
	32.0	7.94	2.65	8.34	2.70	8.74	2.74	8.94	2.76	9.54	2.83	9.95	2.88
	35.0	7.70	2.75	8.10	2.79	8.50	2.84	**8.70**	**2.86**	9.30	2.93	9.70	2.98
	40.0	7.20	2.81	7.55	2.81	7.89	2.81	8.05	2.81	8.54	2.81	8.86	2.81
	43.0	6.36	2.31	6.65	2.31	6.92	2.31	7.06	2.31	7.46	2.31	7.72	2.31
	46.0	5.35	1.80	5.57	1.80	5.79	1.80	5.89	1.80	6.20	1.80	6.41	1.80
2.0+2.5+2.5	22.0	7.33	1.81	7.67	1.84	8.00	1.88	8.17	1.90	8.68	1.95	9.01	1.98
	25.0	7.13	1.87	7.47	1.91	7.80	1.94	7.97	1.96	8.47	2.01	8.81	2.05
	32.0	6.65	2.04	6.99	2.07	7.33	2.11	7.49	2.13	8.00	2.18	8.33	2.21
	35.0	6.45	2.11	6.79	2.15	7.12	2.18	**7.29**	**2.20**	7.79	2.26	8.13	2.29
	40.0	6.11	2.25	6.45	2.28	6.78	2.32	6.95	2.34	7.45	2.39	7.79	2.43
	43.0	5.87	2.31	6.16	2.31	6.44	2.31	6.58	2.31	6.99	2.31	7.25	2.31
	46.0	4.91	1.80	5.14	1.80	5.36	1.80	5.46	1.80	5.78	1.80	5.98	1.80
2.0+2.5+3.5	22.0	7.74	2.03	8.09	2.07	8.44	2.11	8.62	2.13	9.15	2.19	9.51	2.23
	25.0	7.52	2.10	7.87	2.14	8.23	2.18	8.41	2.20	8.94	2.26	9.29	2.30
	32.0	7.02	2.29	7.37	2.33	7.73	2.37	7.90	2.39	8.44	2.45	8.79	2.49
	35.0	6.80	2.37	7.16	2.41	7.51	2.45	**7.69**	**2.47**	8.22	2.53	8.58	2.57
	40.0	6.45	2.53	6.80	2.57	7.15	2.60	7.33	2.62	7.86	2.68	8.22	2.72
	43.0	5.92	2.31	6.20	2.31	6.47	2.31	6.60	2.31	7.00	2.31	7.25	2.31
	46.0	4.98	1.80	5.20	1.80	5.41	1.80	5.51	1.80	5.82	1.80	6.02	1.80
2.0+2.5+5.0	22.0	8.26	2.29	8.64	2.34	9.01	2.38	9.20	2.40	9.77	2.47	10.15	2.52
	25.0	8.03	2.38	8.41	2.42	8.79	2.46	8.97	2.49	9.54	2.55	9.92	2.60
	32.0	7.49	2.58	7.87	2.63	8.25	2.67	8.44	2.70	9.01	2.76	9.38	2.81
	35.0	7.26	2.68	7.64	2.73	8.02	2.77	**8.21**	**2.79**	8.78	2.86	9.16	2.90
	40.0	6.85	2.81	7.19	2.81	7.52	2.81	7.68	2.81	8.15	2.81	8.46	2.81
	43.0	6.09	2.31	6.36	2.31	6.63	2.31	6.76	2.31	7.15	2.31	7.40	2.31
	46.0	5.14	1.80	5.35	1.80	5.56	1.80	5.67	1.80	5.97	1.80	6.16	1.80
2.0+2.5+6.0	22.0	8.61	2.27	9.00	2.31	9.40	2.36	9.60	2.38	10.19	2.44	10.58	2.49
	25.0	8.37	2.35	8.77	2.39	9.16	2.44	9.36	2.46	9.95	2.53	10.34	2.57
	32.0	7.81	2.56	8.21	2.60	8.60	2.64	8.80	2.67	9.39	2.73	9.79	2.78
	35.0	7.57	2.65	7.97	2.70	8.36	2.74	**8.56**	**2.76**	9.15	2.83	9.55	2.87
	40.0	7.16	2.81	7.51	2.81	7.86	2.81	8.02	2.81	8.52	2.81	8.84	2.81
	43.0	6.32	2.31	6.61	2.31	6.89	2.31	7.02	2.31	7.42	2.31	7.69	2.31
	46.0	5.31	1.80	5.53	1.80	5.75	1.80	5.85	1.80	6.17	1.80	6.37	1.80

3D056460

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)

NOTES

1 Capacities are based on following conditions
Corresponding refrigerant piping length : 5m
Level difference : 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 5.0 kW class: wall mounted D series
6.0, 7.1 kW class: wall mounted F series