4MKS75F2V1B

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.5+3.5+3.5+3.5	22.0	9.29	2.56	9.72	2.61	10.15	2.66	10.36	2.68	11.00	2.75	11.42	2.80
	25.0	9.04	2.65	9.46	2.70	9.89	2.75	10.10	2.77	10.74	2.85	11.16	2.90
	32.0	8.43	2.88	8.86	2.93	9.29	2.98	9.50	3.01	10.14	3.08	10.56	3.13
	35.0	8.18	2.99	8.60	3.04	9.03	3.09	**9.24**	**3.11**	9.88	3.19	10.30	3.24
	40.0	7.46	2.81	7.81	2.81	8.15	2.81	8.32	2.81	8.81	2.81	9.13	2.81
	43.0	6.60	2.31	6.89	2.31	7.17	2.31	7.30	2.31	7.70	2.31	7.96	2.31
	46.0	5.56	1.80	5.78	1.80	5.99	1.80	6.10	1.80	6.41	1.80	6.61	1.80

3D056473

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)

NOTES

1 Capacities are based on following conditions
Corresponding refrigerant piping length : 5m
Level difference : 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5 kW class: wall mounted D series
5.0, 6.0, 7.1 kW class: wall mounted F series