Cooling [50Hz 230V]

Outdoor unit	Combination of indoor unit	Capacity of each indoor unit										
		Each capacity (kW)				Total capacity (kW)		Total input (W)		Total current (A)		Power factor %
		A Room	B Room	C Room	D Room	Rating	(Min.~max.)	Rating	(Min.~max.)	Rating	(Min.~max.)	Rating
4MKS75F2V1B	2.0+5.0+5.0	1.24	---	3.13	3.13	7.50	2.72 ~ 8.85	1870	430 ~ 2650	8.2	1.9 ~ 11.6	99
	2.0+5.0+6.0	1.15	---	2.89	3.46	7.50	2.85 ~ 9.03	1900	480 ~ 2750	8.3	2.1 ~ 12.1	99
	2.5+2.5+2.5	2.30	2.30	2.30	---	6.90	1.99 ~ 7.49	1980	340 ~ 2330	8.7	1.5 ~ 10.2	99
	2.5+2.5+3.5	2.12	2.12	2.96	---	7.20	1.99 ~ 7.88	2150	350 ~ 2620	9.4	1.5 ~ 11.5	99
	2.5+2.5+5.0	1.88	1.88	3.74	---	7.50	2.34 ~ 8.40	2160	380 ~ 2660	9.5	1.7 ~ 11.7	99
	2.5+2.5+6.0	1.70	1.70	4.10	---	7.50	2.45 ~ 8.62	2050	430 ~ 2810	9.0	1.9 ~ 12.3	99
	2.5+2.5+7.1	1.55	1.55	---	4.40	7.50	2.67 ~ 8.89	2050	470 ~ 3010	9.0	2.1 ~ 13.2	99
	2.5+3.5+3.5	1.98	2.76	2.76	---	7.50	2.31 ~ 8.25	2330	410 ~ 2910	10.2	1.8 ~ 12.8	99
	2.5+3.5+5.0	1.70	2.39	3.41	---	7.50	2.56 ~ 8.66	2140	430 ~ 2860	9.4	1.9 ~ 12.6	99
	2.5+3.5+6.0	1.56	2.19	3.75	---	7.50	2.67 ~ 8.87	2050	470 ~ 3010	9.0	2.1 ~ 13.2	99
	2.5+3.5+7.1	1.43	2.00	---	4.07	7.50	2.78 ~ 9.01	2050	500 ~ 3120	9.0	2.2 ~ 13.7	99
	2.5+5.0+5.0	1.50	---	3.00	3.00	7.50	2.72 ~ 8.95	1890	430 ~ 2650	8.3	1.9 ~ 11.6	99
	2.5+5.0+6.0	1.39	---	2.78	3.33	7.50	2.96 ~ 9.03	1870	500 ~ 2750	8.2	2.2 ~ 12.1	99
	3.5+3.5+3.5	2.50	2.50	2.50	---	7.50	2.41 ~ 8.52	2330	440 ~ 3170	10.2	1.9 ~ 13.9	99
	3.5+3.5+5.0	2.19	2.19	3.12	---	7.50	2.67 ~ 8.88	2120	460 ~ 2960	9.3	2.0 ~ 13.0	99
	3.5+3.5+6.0	2.02	2.02	3.46	---	7.50	2.67 ~ 9.00	2050	460 ~ 3120	9.0	2.0 ~ 13.7	99
	3.5+5.0+5.0	1.94	---	2.78	2.78	7.50	2.84 ~ 9.05	1870	460 ~ 2650	8.2	2.0 ~ 11.6	99
	2.0+2.0+2.0+2.0	1.76	1.76	1.76	1.76	7.04	2.01 ~ 7.83	1770	330 ~ 2140	7.8	1.4 ~ 9.4	99
	2.0+2.0+2.0+2.5	1.69	1.69	1.69	2.13	7.20	2.01 ~ 8.06	1850	330 ~ 2270	8.1	1.4 ~ 10.0	99
	2.0+2.0+2.0+3.5	1.58	1.58	1.58	2.76	7.50	2.36 ~ 8.29	1980	390 ~ 2440	8.7	1.7 ~ 10.7	99
	2.0+2.0+2.0+5.0	1.36	1.36	1.36	3.42	7.50	2.51 ~ 8.80	1790	420 ~ 2500	7.9	1.8 ~ 11.0	99
	2.0+2.0+2.0+6.0	1.25	1.25	1.25	3.75	7.50	2.76 ~ 9.13	1790	480 ~ 2650	7.9	2.1 ~ 11.6	99
	2.0+2.0+2.0+7.1	1.15	1.15	1.15	4.05	7.50	2.88 ~ 9.29	1790	510 ~ 2750	7.9	2.2 ~ 12.1	99
	2.0+2.0+2.5+2.5	1.63	1.63	2.04	2.04	7.34	2.01 ~ 8.14	1890	330 ~ 2340	8.3	1.4 ~ 10.3	99
	2.0+2.0+2.5+3.5	1.50	1.50	1.88	2.62	7.50	2.36 ~ 8.44	1980	390 ~ 2510	8.7	1.7 ~ 11.0	99
	2.0+2.0+2.5+5.0	1.30	1.30	1.64	3.26	7.50	2.51 ~ 8.88	1790	420 ~ 2550	7.9	1.8 ~ 11.2	99
	2.0+2.0+2.5+6.0	1.20	1.20	1.50	3.60	7.50	2.76 ~ 9.13	1790	480 ~ 2650	7.9	2.1 ~ 11.6	99
	2.0+2.0+3.5+3.5	1.36	1.36	2.39	2.39	7.50	2.47 ~ 8.79	1980	420 ~ 2760	8.7	1.8 ~ 12.1	99
	2.0+2.0+3.5+5.0	1.20	1.20	2.10	3.00	7.50	2.76 ~ 9.18	1790	460 ~ 2700	7.9	2.0 ~ 11.9	99
	2.0+2.0+3.5+6.0	1.11	1.11	1.95	3.33	7.50	2.88 ~ 9.29	1790	510 ~ 2800	7.9	2.2 ~ 12.3	99
	2.0+2.5+2.5+2.5	1.59	1.97	1.97	1.97	7.50	2.36 ~ 8.29	1980	390 ~ 2440	8.7	1.7 ~ 10.7	99
	2.0+2.5+2.5+3.5	1.43	1.79	1.79	2.49	7.50	2.47 ~ 8.58	1980	420 ~ 2610	8.7	1.8 ~ 11.5	99
	2.0+2.5+2.5+5.0	1.25	1.56	1.56	3.13	7.50	2.63 ~ 9.03	1790	440 ~ 2600	7.9	1.9 ~ 11.4	99
	2.0+2.5+2.5+6.0	1.15	1.44	1.44	3.47	7.50	2.88 ~ 9.28	1790	510 ~ 2780	7.9	2.2 ~ 12.2	99
	2.0+2.5+3.5+3.5	1.30	1.64	2.28	2.28	7.50	2.47 ~ 8.92	1980	420 ~ 2860	8.7	1.8 ~ 12.6	99
	2.0+2.5+3.5+5.0	1.15	1.44	2.03	2.88	7.50	2.88 ~ 9.32	1790	480 ~ 2800	7.9	2.1 ~ 12.3	99
	2.0+3.5+3.5+3.5	1.20	2.10	2.10	2.10	7.50	2.70 ~ 9.24	1980	460 ~ 3110	8.7	2.0 ~ 13.7	99
	2.5+2.5+2.5+2.5	1.87	1.87	1.87	1.87	7.48	2.36 ~ 8.44	1980	390 ~ 2510	8.7	1.7 ~ 11.0	99
	2.5+2.5+2.5+3.5	1.70	1.70	1.70	2.40	7.50	2.47 ~ 8.79	1980	420 ~ 2760	8.7	1.8 ~ 12.1	99
	2.5+2.5+2.5+5.0	1.50	1.50	1.50	3.00	7.50	2.63 ~ 9.18	1790	440 ~ 2700	7.9	1.9 ~ 11.9	99
	2.5+2.5+2.5+6.0	1.39	1.39	1.39	3.33	7.50	2.88 ~ 9.28	1790	500 ~ 2750	7.9	2.2 ~ 12.1	99
	2.5+2.5+3.5+3.5	1.56	1.56	2.19	2.19	7.50	2.59 ~ 9.05	1980	430 ~ 2960	8.7	1.9 ~ 13.0	99
	2.5+2.5+3.5+5.0	1.39	1.39	1.94	2.78	7.50	2.88 ~ 9.33	1790	480 ~ 2800	7.9	2.1 ~ 12.3	99
	2.5+3.5+3.5+3.5	1.44	2.02	2.02	2.02	7.50	2.59 ~ 9.24	1980	450 ~ 3110	8.7	2.0 ~ 13.7	99

3D056457

NOTES

1 Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).

2 The total ability of connected a indoor unit is up to 13.5 kW

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 5.0 kW class: wall mounted D series
6.0, 7.1 kW class: wall mounted F series

4 Capacities are based on the following conditions:
Corresponding refrigerant piping length : 5m
Level difference : 0m

5 The bold line is indicated the rated combination of indoor unit.