Model		Units				Power supply		Comp.		OFM	
Outdoor	H/P C/D	Hz	Volts	Min.	Max.	MCA	MFA	MSC	RLA	W	FLA
4MKS75F2V1B	C/D	50	230	207	253	16.0	20	8.5	7.46	43	0.33

3D056164

SYMBOLS

MCA : Min. Circuit Amps (A)
MFA : Max. Fuse Amps (See note 6). (A)
MSC : MSC means the max. current during the starting of compressor. (A)
RLA : Rated Load Amps (A)
OFM : Outdoor Fan Motor
FLA : Full Load Amps (A)
W : Fan Motor Rated Output (W)

NOTES

1. RLA is based on the following conditions:
   Cooling
   Indoor temp.: 27°CDB/19.0°CWB
   Outdoor temp. : 35°CDB
2. Voltage range
   Units are suitable for use on electrical systems where voltage supplied to unit terminals is not below or above listed operation range limits
3. Maximum allowable voltage variation between phases is 2%
4. MCA represents maximum input current.
   MFA represents capacity which may accept MCA
5. Select wire size based on the larger value of MCA.
6. MFA is used to select the circuit breaker and the ground fault circuit interrupter (earth leakage circuit breaker)
7. For more details concerning conditional connections, see http://extranet.daikineurope.com, select "E-Data Books". Finally, click on the document title of your choice.