4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
3.5+7.1	22.0	8.29	2.56	8.67	2.61	9.05	2.66	9.24	2.69	9.81	2.76	10.19	2.81
	25.0	8.06	2.66	8.44	2.71	8.82	2.76	9.01	2.78	9.58	2.86	9.96	2.91
	32.0	7.52	2.89	7.90	2.94	8.28	2.99	8.47	3.01	9.04	3.09	9.42	3.14
	35.0	7.29	3.00	7.67	3.05	8.05	3.10	**8.24**	**3.12**	8.81	3.20	9.19	3.25
	40.0	6.72	2.81	7.04	2.81	7.35	2.81	7.51	2.81	7.96	2.81	8.25	2.81
	43.0	6.04	2.31	6.30	2.31	6.55	2.31	6.68	2.31	7.05	2.31	7.29	2.31
	46.0	5.15	1.80	5.35	1.80	5.55	1.80	5.65	1.80	5.93	1.80	6.12	1.80
4.2+4.2	22.0	6.76	2.09	8.01	2.74	8.36	2.79	8.53	2.82	9.06	2.90	9.41	2.95
	25.0	6.76	2.28	7.79	2.84	8.14	2.89	8.32	2.91	8.84	2.99	9.20	3.05
	32.0	6.76	2.85	7.30	3.08	7.65	3.13	7.82	3.16	8.35	3.24	8.70	3.29
	35.0	6.73	3.14	7.08	3.19	7.43	3.25	**7.61**	**3.27**	8.14	3.35	8.49	3.40
	40.0	6.26	2.81	6.55	2.81	6.84	2.81	6.98	2.81	7.40	2.81	7.67	2.81
	43.0	5.71	2.31	5.95	2.31	6.18	2.31	6.30	2.31	6.64	2.31	6.86	2.31
	46.0	4.92	1.80	5.11	1.80	5.29	1.80	5.39	1.80	5.65	1.80	5.82	1.80
4.2+5.0	22.0	7.71	2.40	8.07	2.45	8.42	2.49	8.60	2.52	9.13	2.59	9.48	2.63
	25.0	7.50	2.49	7.85	2.53	8.21	2.58	8.38	2.60	8.91	2.67	9.27	2.72
	32.0	7.00	2.70	7.35	2.75	7.71	2.80	7.88	2.82	8.41	2.89	8.77	2.94
	35.0	6.79	2.81	7.14	2.85	7.49	2.90	**7.67**	**2.92**	8.20	2.99	8.55	3.04
	40.0	6.35	2.81	6.66	2.81	6.96	2.81	7.11	2.81	7.55	2.81	7.84	2.81
	43.0	5.72	2.31	5.97	2.31	6.22	2.31	6.35	2.31	6.71	2.31	6.94	2.31
	46.0	4.89	1.80	5.09	1.80	5.28	1.80	5.38	1.80	5.66	1.80	5.84	1.80
4.2+6.0	22.0	8.02	2.35	8.38	2.40	8.75	2.44	8.93	2.46	9.49	2.53	9.85	2.58
	25.0	7.79	2.43	8.16	2.48	8.53	2.53	8.71	2.55	9.26	2.62	9.63	2.68
	32.0	7.27	2.65	7.64	2.70	8.01	2.74	8.19	2.76	8.74	2.83	9.11	2.88
	35.0	7.05	2.75	7.42	2.79	7.79	2.84	**7.97**	**2.86**	8.52	2.93	8.89	2.98
	40.0	6.61	2.81	6.94	2.81	7.25	2.81	7.41	2.81	7.87	2.81	8.16	2.81
	43.0	5.91	2.31	6.18	2.31	6.44	2.31	6.56	2.31	6.94	2.31	7.18	2.31
	46.0	5.03	1.80	5.23	1.80	5.43	1.80	5.53	1.80	5.82	1.80	6.01	1.80
4.2+7.1	22.0	8.30	2.56	8.68	2.61	9.06	2.66	9.25	2.69	9.82	2.76	10.20	2.81
	25.0	8.07	2.66	8.45	2.71	8.83	2.76	9.02	2.78	9.59	2.86	9.97	2.91
	32.0	7.53	2.89	7.91	2.94	8.29	2.99	8.48	3.01	9.05	3.09	9.43	3.14
	35.0	7.30	3.00	7.68	3.05	8.06	3.10	**8.25**	**3.12**	8.82	3.20	9.20	3.25
	40.0	6.73	2.81	7.05	2.81	7.36	2.81	7.51	2.81	7.97	2.81	8.26	2.81
	43.0	6.04	2.31	6.30	2.31	6.56	2.31	6.68	2.31	7.05	2.31	7.29	2.31
	46.0	5.15	1.80	5.35	1.80	5.55	1.80	5.65	1.80	5.94	1.80	6.12	1.80
5.0+5.0	22.0	8.16	2.65	8.53	2.70	8.91	2.75	9.09	2.78	9.65	2.85	10.03	2.90
	25.0	7.93	2.74	8.30	2.79	8.68	2.84	8.87	2.87	9.43	2.95	9.80	3.00
	32.0	7.40	2.98	7.78	3.03	8.15	3.09	8.34	3.11	8.90	3.19	9.27	3.24
	35.0	7.18	3.09	7.55	3.15	7.92	3.20	**8.11**	**3.22**	8.67	3.30	9.04	3.35
	40.0	6.61	2.81	6.92	2.81	7.23	2.81	7.38	2.81	7.82	2.81	8.10	2.81
	43.0	5.97	2.31	6.22	2.31	6.47	2.31	6.59	2.31	6.95	2.31	7.19	2.31
	46.0	5.11	1.80	5.31	1.80	5.50	1.80	5.59	1.80	5.87	1.80	6.06	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059237A