4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.0+3.5	22.0	7.54	1.91	7.89	1.95	8.24	1.99	8.41	2.01	8.93	2.06	9.27	2.10
	25.0	7.33	1.98	7.68	2.02	8.03	2.06	8.20	2.08	8.72	2.13	9.06	2.17
	32.0	6.85	2.16	7.19	2.20	7.54	2.23	7.71	2.25	8.23	2.31	8.57	2.34
	35.0	6.64	2.24	6.98	2.28	7.33	2.31	**7.50**	**2.33**	8.02	2.39	8.36	2.43
	40.0	6.29	2.38	6.63	2.42	6.98	2.46	7.15	2.48	7.67	2.53	8.01	2.57
	43.0	5.90	2.31	6.18	2.31	6.46	2.31	6.60	2.31	7.00	2.31	7.26	2.31
	46.0	4.95	1.80	5.17	1.80	5.38	1.80	5.49	1.80	5.80	1.80	6.00	1.80
2.0+2.0+4.2	22.0	7.75	2.03	8.10	2.07	8.45	2.11	8.63	2.13	9.16	2.19	9.52	2.23
	25.0	7.53	2.10	7.88	2.14	8.24	2.18	8.42	2.20	8.95	2.26	9.30	2.30
	32.0	7.03	2.29	7.38	2.33	7.74	2.37	7.92	2.39	8.45	2.45	8.80	2.49
	35.0	6.81	2.37	7.17	2.41	7.52	2.45	**7.70**	**2.47**	8.23	2.53	8.59	2.57
	40.0	6.45	2.53	6.81	2.57	7.16	2.60	7.34	2.62	7.87	2.68	8.23	2.72
	43.0	5.92	2.31	6.20	2.31	6.48	2.31	6.61	2.31	7.01	2.31	7.26	2.31
	46.0	4.98	1.80	5.20	1.80	5.41	1.80	5.52	1.80	5.82	1.80	6.02	1.80
2.0+2.0+5.0	22.0	8.08	2.17	8.45	2.21	8.82	2.25	9.00	2.28	9.56	2.34	9.93	2.38
	25.0	7.85	2.25	8.22	2.29	8.59	2.33	8.78	2.35	9.33	2.42	9.70	2.46
	32.0	7.33	2.45	7.70	2.49	8.07	2.53	8.25	2.55	8.81	2.61	9.18	2.66
	35.0	7.11	2.54	7.48	2.58	7.85	2.62	**8.03**	**2.64**	8.58	2.71	8.95	2.75
	40.0	6.73	2.70	7.10	2.74	7.47	2.78	7.66	2.80	8.14	2.81	8.45	2.81
	43.0	6.04	2.31	6.32	2.31	6.59	2.31	6.72	2.31	7.12	2.31	7.37	2.31
	46.0	5.09	1.80	5.31	1.80	5.52	1.80	5.62	1.80	5.93	1.80	6.12	1.80
2.0+2.0+6.0	22.0	8.41	2.14	8.79	2.19	9.18	2.23	9.37	2.25	9.95	2.31	10.33	2.35
	25.0	8.18	2.22	8.56	2.26	8.95	2.31	9.14	2.33	9.72	2.39	10.10	2.43
	32.0	7.63	2.42	8.02	2.46	8.40	2.50	8.59	2.52	9.17	2.58	9.56	2.63
	35.0	7.40	2.51	7.78	2.55	8.17	2.59	**8.36**	**2.61**	8.94	2.68	9.32	2.72
	40.0	7.01	2.67	7.39	2.71	7.78	2.75	7.97	2.77	8.51	2.81	8.83	2.81
	43.0	6.28	2.31	6.57	2.31	6.85	2.31	6.99	2.31	7.40	2.31	7.66	2.31
	46.0	5.26	1.80	5.49	1.80	5.70	1.80	5.81	1.80	6.13	1.80	6.33	1.80
2.0+2.0+7.1	22.0	8.75	2.35	9.15	2.40	9.55	2.44	9.75	2.46	10.35	2.53	10.76	2.58
	25.0	8.51	2.43	8.91	2.48	9.31	2.53	9.51	2.55	10.11	2.62	10.51	2.66
	32.0	7.94	2.65	8.34	2.70	8.74	2.74	8.94	2.76	9.54	2.83	9.95	2.88
	35.0	7.70	2.75	8.10	2.79	8.50	2.84	**8.70**	**2.86**	9.30	2.93	9.70	2.98
	40.0	7.20	2.81	7.55	2.81	7.89	2.81	8.05	2.81	8.54	2.81	8.86	2.81
	43.0	6.36	2.31	6.65	2.31	6.92	2.31	7.06	2.31	7.46	2.31	7.72	2.31
	46.0	5.35	1.80	5.57	1.80	5.79	1.80	5.89	1.80	6.20	1.80	6.41	1.80
2.0+2.5+2.5	22.0	7.33	1.81	7.67	1.84	8.00	1.88	8.17	1.90	8.68	1.95	9.01	1.98
	25.0	7.13	1.87	7.47	1.91	7.80	1.94	7.97	1.96	8.47	2.01	8.81	2.05
	32.0	6.65	2.04	6.99	2.07	7.33	2.11	7.49	2.13	8.00	2.18	8.33	2.21
	35.0	6.45	2.11	6.79	2.15	7.12	2.18	**7.29**	**2.20**	7.79	2.26	8.13	2.29
	40.0	6.11	2.25	6.45	2.28	6.78	2.32	6.95	2.34	7.45	2.39	7.79	2.43
	43.0	5.87	2.31	6.16	2.31	6.44	2.31	6.58	2.31	6.99	2.31	7.25	2.31
	46.0	4.91	1.80	5.14	1.80	5.36	1.80	5.46	1.80	5.78	1.80	5.98	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059238A