4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+3.5+4.2	22.0	8.24	2.35	8.62	2.40	8.99	2.44	9.18	2.46	9.75	2.53	10.12	2.58
	25.0	8.01	2.43	8.39	2.48	8.76	2.53	8.95	2.55	9.52	2.62	9.90	2.66
	32.0	7.48	2.65	7.85	2.70	8.23	2.74	8.42	2.76	8.98	2.83	9.36	2.88
	35.0	7.25	2.75	7.62	2.79	8.00	2.84	**8.19**	**2.86**	8.76	2.93	9.13	2.98
	40.0	6.79	2.81	7.12	2.81	7.44	2.81	7.60	2.81	8.07	2.81	8.37	2.81
	43.0	6.05	2.31	6.32	2.31	6.58	2.31	6.71	2.31	7.10	2.31	7.34	2.31
	46.0	5.12	1.80	5.33	1.80	5.54	1.80	5.64	1.80	5.94	1.80	6.13	1.80
2.0+3.5+5.0	22.0	8.62	2.51	9.02	2.56	9.41	2.61	9.61	2.64	10.20	2.71	10.59	2.76
	25.0	8.38	2.61	8.78	2.65	9.17	2.70	9.37	2.73	9.96	2.80	10.36	2.85
	32.0	7.82	2.83	8.22	2.88	8.61	2.93	8.81	2.96	9.40	3.03	9.80	3.08
	35.0	7.58	2.94	7.98	2.99	8.37	3.04	**8.57**	**3.06**	9.16	3.14	9.56	3.19
	40.0	6.99	2.81	7.32	2.81	7.64	2.81	7.80	2.81	8.27	2.81	8.57	2.81
	43.0	6.23	2.31	6.50	2.31	6.77	2.31	6.90	2.31	7.28	2.31	7.53	2.31
	46.0	5.28	1.80	5.49	1.80	5.70	1.80	5.80	1.80	6.09	1.80	6.29	1.80
2.0+3.5+6.0	22.0	8.80	2.39	9.20	2.44	9.61	2.48	9.81	2.51	10.41	2.58	10.82	2.62
	25.0	8.56	2.48	8.96	2.52	9.36	2.57	9.56	2.59	10.17	2.66	10.57	2.71
	32.0	7.99	2.70	8.39	2.74	8.79	2.79	8.99	2.81	9.60	2.88	10.00	2.93
	35.0	7.74	2.80	8.15	2.84	8.55	2.89	**8.75**	**2.91**	9.35	2.98	9.76	3.03
	40.0	7.20	2.81	7.55	2.81	7.89	2.81	8.05	2.81	8.54	2.81	8.86	2.81
	43.0	6.37	2.31	6.66	2.31	6.93	2.31	7.07	2.31	7.47	2.31	7.72	2.31
	46.0	5.37	1.80	5.59	1.80	5.80	1.80	5.90	1.80	6.21	1.80	6.41	1.80
2.0+3.5+7.1	22.0	9.00	2.51	9.42	2.56	9.83	2.61	10.03	2.64	10.65	2.71	11.06	2.76
	25.0	8.75	2.61	9.16	2.65	9.58	2.70	9.78	2.73	10.40	2.80	10.81	2.85
	32.0	8.17	2.83	8.58	2.88	8.99	2.93	9.20	2.96	9.82	3.03	10.23	3.08
	35.0	7.92	2.94	8.33	2.99	8.74	3.04	**8.95**	**3.06**	9.57	3.14	9.98	3.19
	40.0	7.27	2.81	7.61	2.81	7.95	2.81	8.11	2.81	8.60	2.81	8.91	2.81
	43.0	6.45	2.31	6.73	2.31	7.00	2.31	7.14	2.31	7.53	2.31	7.79	2.31
	46.0	5.44	1.80	5.66	1.80	5.87	1.80	5.97	1.80	6.28	1.80	6.48	1.80
2.0+4.2+4.2	22.0	8.31	2.39	8.69	2.44	9.07	2.48	9.26	2.51	9.83	2.58	10.21	2.62
	25.0	8.08	2.48	8.46	2.52	8.84	2.57	9.03	2.59	9.60	2.66	9.98	2.71
	32.0	7.54	2.70	7.92	2.74	8.30	2.79	8.49	2.81	9.06	2.88	9.44	2.93
	35.0	7.31	2.80	7.69	2.84	8.07	2.89	**8.26**	**2.91**	8.83	2.98	9.21	3.03
	40.0	6.82	2.81	7.15	2.81	7.47	2.81	7.63	2.81	8.10	2.81	8.40	2.81
	43.0	6.08	2.31	6.35	2.31	6.61	2.31	6.74	2.31	7.12	2.31	7.37	2.31
	46.0	5.15	1.80	5.36	1.80	5.57	1.80	5.67	1.80	5.96	1.80	6.15	1.80
2.0+4.2+5.0	22.0	8.62	2.51	9.02	2.56	9.41	2.61	9.61	2.64	10.20	2.71	10.59	2.76
	25.0	8.38	2.61	8.78	2.65	9.17	2.70	9.37	2.73	9.96	2.80	10.36	2.85
	32.0	7.82	2.83	8.22	2.88	8.61	2.93	8.81	2.96	9.40	3.03	9.80	3.08
	35.0	7.58	2.94	7.98	2.99	8.37	3.04	**8.57**	**3.06**	9.16	3.14	9.56	3.19
	40.0	6.99	2.81	7.32	2.81	7.64	2.81	7.80	2.81	8.27	2.81	8.57	2.81
	43.0	6.23	2.31	6.50	2.31	6.77	2.31	6.90	2.31	7.28	2.31	7.53	2.31
	46.0	5.28	1.80	5.49	1.80	5.70	1.80	5.80	1.80	6.09	1.80	6.29	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059239A