4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.5+2.5+4.2	22.0	8.00	2.19	8.36	2.23	8.73	2.27	8.91	2.29	9.46	2.36	9.83	2.40
	25.0	7.77	2.26	8.14	2.31	8.51	2.35	8.69	2.37	9.24	2.43	9.61	2.48
	32.0	7.26	2.46	7.62	2.51	7.99	2.55	8.17	2.57	8.72	2.63	9.09	2.68
	35.0	7.03	2.56	7.40	2.60	7.77	2.64	**7.95**	**2.66**	8.50	2.73	8.87	2.77
	40.0	6.66	2.72	7.03	2.76	7.40	2.80	7.56	2.81	8.04	2.81	8.34	2.81
	43.0	5.98	2.31	6.25	2.31	6.52	2.31	6.65	2.31	7.04	2.31	7.29	2.31
	46.0	5.05	1.80	5.26	1.80	5.47	1.80	5.57	1.80	5.87	1.80	6.07	1.80
2.5+2.5+5.0	22.0	8.44	2.39	8.83	2.44	9.21	2.48	9.41	2.51	9.99	2.58	10.37	2.62
	25.0	8.20	2.48	8.59	2.52	8.98	2.57	9.17	2.59	9.75	2.66	10.14	2.71
	32.0	7.66	2.70	8.04	2.74	8.43	2.79	8.62	2.81	9.20	2.88	9.59	2.93
	35.0	7.42	2.80	7.81	2.84	8.20	2.89	**8.39**	**2.91**	8.97	2.98	9.36	3.03
	40.0	6.92	2.81	7.25	2.81	7.58	2.81	7.74	2.81	8.21	2.81	8.52	2.81
	43.0	6.16	2.31	6.48	2.31	6.70	2.31	6.83	2.31	7.21	2.31	7.46	2.31
	46.0	5.21	1.80	5.42	1.80	5.63	1.80	5.73	1.80	6.03	1.80	6.22	1.80
2.5+2.5+6.0	22.0	8.67	2.31	9.07	2.35	9.47	2.40	9.66	2.42	10.26	2.49	10.66	2.53
	25.0	8.43	2.39	8.83	2.44	9.22	2.48	9.42	2.50	10.02	2.57	10.42	2.62
	32.0	7.87	2.60	8.27	2.65	8.66	2.69	8.86	2.72	9.46	2.78	9.85	2.83
	35.0	7.63	2.70	8.02	2.75	8.42	2.79	**8.62**	**2.81**	9.22	2.88	9.61	2.93
	40.0	7.17	2.81	7.52	2.81	7.86	2.81	8.03	2.81	8.52	2.81	8.84	2.81
	43.0	6.33	2.31	6.62	2.31	6.90	2.31	7.03	2.31	7.43	2.31	7.69	2.31
	46.0	5.33	1.80	5.55	1.80	5.76	1.80	5.87	1.80	6.18	1.80	6.38	1.80
2.5+2.5+7.1	22.0	8.94	2.47	9.35	2.52	9.76	2.57	9.97	2.59	10.58	2.67	10.99	2.71
	25.0	8.69	2.56	9.10	2.61	9.51	2.66	9.72	2.68	10.33	2.76	10.74	2.80
	32.0	8.11	2.79	8.52	2.84	8.93	2.88	9.14	2.91	9.75	2.98	10.16	3.03
	35.0	7.87	2.89	8.28	2.94	8.69	2.99	**8.89**	**3.01**	9.50	3.09	9.91	3.13
	40.0	7.25	2.81	7.60	2.81	7.93	2.81	8.10	2.81	8.58	2.81	8.90	2.81
	43.0	6.43	2.31	6.71	2.31	6.98	2.31	7.12	2.31	7.51	2.31	7.77	2.31
	46.0	5.42	1.80	5.63	1.80	5.85	1.80	5.95	1.80	6.26	1.80	6.46	1.80
2.5+3.5+3.5	22.0	8.30	2.39	8.68	2.44	9.06	2.48	9.25	2.51	9.82	2.58	10.20	2.62
	25.0	8.07	2.48	8.45	2.52	8.83	2.57	9.02	2.59	9.59	2.66	9.97	2.71
	32.0	7.53	2.70	7.91	2.74	8.29	2.79	8.48	2.81	9.05	2.88	9.43	2.93
	35.0	7.30	2.80	7.68	2.84	8.06	2.89	**8.25**	**2.91**	8.82	2.98	9.20	3.03
	40.0	6.81	2.81	7.14	2.81	7.46	2.81	7.62	2.81	8.09	2.81	8.39	2.81
	43.0	6.07	2.31	6.34	2.31	6.60	2.31	6.73	2.31	7.12	2.31	7.36	2.31
	46.0	5.15	1.80	5.36	1.80	5.56	1.80	5.66	1.80	5.96	1.80	6.15	1.80
2.5+3.5+4.2	22.0	8.30	2.39	8.68	2.44	9.06	2.48	9.25	2.51	9.82	2.58	10.20	2.62
	25.0	8.07	2.48	8.45	2.52	8.83	2.57	9.02	2.59	9.59	2.66	9.97	2.71
	32.0	7.53	2.70	7.91	2.74	8.29	2.79	8.48	2.81	9.05	2.88	9.43	2.93
	35.0	7.30	2.80	7.68	2.84	8.06	2.89	**8.25**	**2.91**	8.82	2.98	9.20	3.03
	40.0	6.81	2.81	7.14	2.81	7.46	2.81	7.62	2.81	8.09	2.81	8.39	2.81
	43.0	6.07	2.31	6.34	2.31	6.60	2.31	6.73	2.31	7.12	2.31	7.36	2.31
	46.0	5.15	1.80	5.36	1.80	5.56	1.80	5.66	1.80	5.96	1.80	6.15	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059240A