4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.5+5.0+5.0	22.0	8.98	2.61	9.39	2.66	9.81	2.71	10.01	2.73	10.63	2.81	11.04	2.86
	25.0	8.73	2.70	9.14	2.75	9.56	2.80	9.76	2.83	10.38	2.90	10.79	2.95
	32.0	8.15	2.94	8.56	2.99	8.97	3.04	9.18	3.06	9.80	3.14	10.21	3.19
	35.0	7.90	3.05	8.31	3.10	8.72	3.15	**8.93**	**3.17**	9.55	3.25	9.96	3.30
	40.0	7.21	2.81	7.55	2.81	7.88	2.81	8.04	2.81	8.51	2.81	8.82	2.81
	43.0	6.42	2.31	6.70	2.31	6.96	2.31	7.10	2.31	7.48	2.31	7.73	2.31
	46.0	5.43	1.80	5.65	1.80	5.85	1.80	5.96	1.80	6.26	1.80	6.45	1.80
2.5+5.0+6.0	22.0	9.08	2.47	9.50	2.52	9.92	2.57	10.12	2.59	10.75	2.67	11.16	2.71
	25.0	8.83	2.56	9.25	2.61	9.66	2.66	9.87	2.68	10.49	2.76	10.91	2.80
	32.0	8.24	2.79	8.66	2.84	9.07	2.88	9.28	2.91	9.91	2.98	10.32	3.03
	35.0	7.99	2.89	8.41	2.94	8.82	2.99	**9.03**	**3.01**	9.65	3.09	10.07	3.13
	40.0	7.36	2.81	7.71	2.81	8.05	2.81	8.21	2.81	8.70	2.81	9.02	2.81
	43.0	6.51	2.31	6.79	2.31	7.07	2.31	7.21	2.31	7.61	2.31	7.87	2.31
	46.0	5.48	1.80	5.70	1.80	5.91	1.80	6.02	1.80	6.33	1.80	6.53	1.80
3.5+3.5+3.5	22.0	8.57	2.61	8.96	2.66	9.36	2.71	9.55	2.73	10.14	2.81	10.53	2.86
	25.0	8.33	2.70	8.72	2.75	9.12	2.80	9.31	2.83	9.90	2.90	10.29	2.95
	32.0	7.78	2.94	8.17	2.99	8.56	3.04	8.76	3.06	9.35	3.14	9.74	3.19
	35.0	7.54	3.05	7.93	3.10	8.32	3.15	**8.52**	**3.17**	9.11	3.25	9.50	3.30
	40.0	6.92	2.81	7.24	2.81	7.56	2.81	7.71	2.81	8.17	2.81	8.47	2.81
	43.0	6.19	2.31	6.46	2.31	6.72	2.31	6.84	2.31	7.22	2.31	7.48	2.31
	46.0	5.27	1.80	5.47	1.80	5.67	1.80	5.77	1.80	6.06	1.80	6.25	1.80
3.5+3.5+4.2	22.0	8.63	2.65	9.03	2.70	9.42	2.75	9.62	2.78	10.21	2.85	10.61	2.90
	25.0	8.39	2.74	8.79	2.79	9.18	2.84	9.38	2.87	9.97	2.95	10.37	3.00
	32.0	7.83	2.98	8.23	3.03	8.62	3.09	8.82	3.11	9.41	3.19	9.81	3.24
	35.0	7.59	3.09	7.99	3.15	8.38	3.20	**8.58**	**3.22**	9.17	3.30	9.57	3.35
	40.0	6.95	2.81	7.27	2.81	7.59	2.81	7.74	2.81	8.20	2.81	8.50	2.81
	43.0	6.23	2.31	6.49	2.31	6.75	2.31	6.88	2.31	7.25	2.31	7.49	2.31
	46.0	5.30	1.80	5.50	1.80	5.70	1.80	5.80	1.80	6.09	1.80	6.28	1.80
3.5+3.5+5.0	22.0	8.88	2.65	9.29	2.70	9.70	2.75	9.90	2.78	10.51	2.85	10.92	2.90
	25.0	8.64	2.74	9.04	2.79	9.45	2.84	9.65	2.87	10.26	2.95	10.67	3.00
	32.0	8.06	2.98	8.47	3.03	8.87	3.09	9.08	3.11	9.69	3.19	10.09	3.24
	35.0	7.81	3.09	8.22	3.15	8.63	3.20	**8.83**	**3.22**	9.44	3.30	9.85	3.35
	40.0	7.13	2.81	7.46	2.81	7.78	2.81	7.94	2.81	8.41	2.81	8.71	2.81
	43.0	6.36	2.31	6.63	2.31	6.90	2.31	7.03	2.31	7.41	2.31	7.66	2.31
	46.0	5.40	1.80	5.61	1.80	5.81	1.80	5.91	1.80	6.21	1.80	6.40	1.80
3.5+3.5+6.0	22.0	9.05	2.56	9.47	2.61	9.88	2.66	10.09	2.69	10.71	2.76	11.13	2.81
	25.0	8.80	2.66	9.22	2.71	9.63	2.76	9.84	2.78	10.46	2.86	10.87	2.91
	32.0	8.21	2.89	8.63	2.94	9.04	2.99	9.25	3.01	9.87	3.09	10.29	3.14
	35.0	7.96	3.00	8.38	3.05	8.79	3.10	**9.00**	**3.12**	9.62	3.20	10.04	3.25
	40.0	7.28	2.81	7.62	2.81	7.96	2.81	8.12	2.81	8.60	2.81	8.91	2.81
	43.0	6.47	2.31	6.74	2.31	7.02	2.31	7.15	2.31	7.54	2.31	7.80	2.31
	46.0	5.46	1.80	5.68	1.80	5.89	1.80	5.99	1.80	6.30	1.80	6.49	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059241A