## 4MKS75F (★ cooling 50Hz 230V)

| Combination (Capacity) | Outdoor air temp. °CWB | Indoor air temp.: °CWB | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | 14°C | | 16°C | | 18°C | | 19°C | | 22°C | | 24°C | |
| | | TC kW | PI kW | TC kW | PI kW | TC kW | PI kW | TC kW | PI kW | TC kW | PI kW | TC kW | PI kW |
| 2.0+2.0+2.0+2.5 | 22.0 | 8.11 | 1.87 | 8.48 | 1.90 | 8.85 | 1.94 | 9.04 | 1.96 | 9.59 | 2.01 | 9.96 | 2.05 |
| | 25.0 | 7.88 | 1.93 | 8.25 | 1.97 | 8.62 | 2.01 | 8.81 | 2.02 | 9.37 | 2.08 | 9.74 | 2.11 |
| | 32.0 | 7.36 | 2.10 | 7.73 | 2.14 | 8.10 | 2.18 | 8.29 | 2.19 | 8.84 | 2.25 | 9.21 | 2.28 |
| | 35.0 | 7.13 | 2.18 | 7.50 | 2.22 | 7.87 | 2.25 | **8.06** | **2.27** | 8.62 | 2.33 | 8.99 | 2.36 |
| | 40.0 | 6.76 | 2.32 | 7.13 | 2.36 | 7.50 | 2.39 | 7.68 | 2.41 | 8.24 | 2.47 | 8.61 | 2.50 |
| | 43.0 | 6.39 | 2.31 | 6.70 | 2.31 | 7.00 | 2.31 | 7.15 | 2.31 | 7.58 | 2.31 | 7.86 | 2.31 |
| | 46.0 | 5.30 | 1.80 | 5.54 | 1.80 | 5.77 | 1.80 | 5.89 | 1.80 | 6.22 | 1.80 | 6.44 | 1.80 |
| 2.0+2.0+2.0+3.5 | 22.0 | 8.34 | 2.01 | 8.72 | 2.04 | 9.10 | 2.08 | 9.29 | 2.10 | 9.87 | 2.16 | 10.25 | 2.20 |
| | 25.0 | 8.11 | 2.08 | 8.49 | 2.12 | 8.87 | 2.16 | 9.06 | 2.17 | 9.63 | 2.23 | 10.02 | 2.27 |
| | 32.0 | 7.57 | 2.26 | 7.95 | 2.30 | 8.33 | 2.34 | 8.52 | 2.36 | 9.09 | 2.42 | 9.48 | 2.46 |
| | 35.0 | 7.34 | 2.34 | 7.72 | 2.38 | 8.10 | 2.42 | **8.29** | **2.44** | 8.86 | 2.50 | 9.24 | 2.54 |
| | 40.0 | 6.95 | 2.49 | 7.33 | 2.53 | 7.71 | 2.57 | 7.90 | 2.59 | 8.48 | 2.65 | 8.86 | 2.69 |
| | 43.0 | 6.37 | 2.31 | 6.67 | 2.31 | 6.97 | 2.31 | 7.11 | 2.31 | 7.53 | 2.31 | 7.80 | 2.31 |
| | 46.0 | 5.31 | 1.80 | 5.54 | 1.80 | 5.77 | 1.80 | 5.88 | 1.80 | 6.21 | 1.80 | 6.42 | 1.80 |
| 2.0+2.0+2.0+4.2 | 22.0 | 8.42 | 2.05 | 8.80 | 2.09 | 9.19 | 2.13 | 9.38 | 2.15 | 9.96 | 2.21 | 10.35 | 2.25 |
| | 25.0 | 8.19 | 2.12 | 8.57 | 2.16 | 8.96 | 2.20 | 9.15 | 2.22 | 9.73 | 2.28 | 10.11 | 2.32 |
| | 32.0 | 7.64 | 2.31 | 8.03 | 2.35 | 8.41 | 2.39 | 8.60 | 2.41 | 9.18 | 2.47 | 9.57 | 2.51 |
| | 35.0 | 7.41 | 2.39 | 7.79 | 2.43 | 8.18 | 2.47 | **8.37** | **2.49** | 8.95 | 2.55 | 9.33 | 2.59 |
| | 40.0 | 7.02 | 2.55 | 7.40 | 2.59 | 7.79 | 2.63 | 7.98 | 2.65 | 8.56 | 2.71 | 8.94 | 2.75 |
| | 43.0 | 6.38 | 2.31 | 6.68 | 2.31 | 6.97 | 2.31 | 7.12 | 2.31 | 7.54 | 2.31 | 7.81 | 2.31 |
| | 46.0 | 5.32 | 1.80 | 5.55 | 1.80 | 5.78 | 1.80 | 5.89 | 1.80 | 6.22 | 1.80 | 6.43 | 1.80 |
| 2.0+2.0+2.0+5.0 | 22.0 | 8.84 | 2.23 | 9.25 | 2.27 | 9.65 | 2.31 | 9.85 | 2.34 | 10.46 | 2.40 | 10.87 | 2.44 |
| | 25.0 | 8.60 | 2.31 | 9.00 | 2.35 | 9.41 | 2.39 | 9.61 | 2.42 | 10.22 | 2.48 | 10.62 | 2.52 |
| | 32.0 | 8.02 | 2.51 | 8.43 | 2.55 | 8.83 | 2.60 | 9.04 | 2.62 | 9.64 | 2.68 | 10.05 | 2.73 |
| | 35.0 | 7.78 | 2.60 | 8.18 | 2.65 | 8.59 | 2.69 | **8.79** | **2.71** | 9.40 | 2.78 | 9.80 | 2.82 |
| | 40.0 | 7.37 | 2.77 | 7.77 | 2.81 | 8.12 | 2.81 | 8.29 | 2.81 | 8.80 | 2.81 | 9.13 | 2.81 |
| | 43.0 | 6.50 | 2.31 | 6.79 | 2.31 | 7.08 | 2.31 | 7.22 | 2.31 | 7.64 | 2.31 | 7.91 | 2.31 |
| | 46.0 | 5.43 | 1.80 | 5.66 | 1.80 | 5.88 | 1.80 | 5.99 | 1.80 | 6.32 | 1.80 | 6.53 | 1.80 |
| 2.0+2.0+2.0+6.0 | 22.0 | 9.18 | 2.18 | 9.60 | 2.22 | 10.02 | 2.26 | 10.24 | 2.28 | 10.87 | 2.35 | 11.29 | 2.39 |
| | 25.0 | 8.93 | 2.26 | 9.35 | 2.30 | 9.77 | 2.34 | 9.98 | 2.36 | 10.61 | 2.43 | 11.03 | 2.47 |
| | 32.0 | 8.33 | 2.45 | 8.75 | 2.50 | 9.17 | 2.54 | 9.39 | 2.56 | 10.02 | 2.62 | 10.44 | 2.67 |
| | 35.0 | 8.08 | 2.55 | 8.50 | 2.59 | 8.92 | 2.63 | **9.13** | **2.65** | 9.76 | 2.72 | 10.18 | 2.76 |
| | 40.0 | 7.65 | 2.71 | 8.07 | 2.75 | 8.49 | 2.79 | 8.69 | 2.81 | 9.22 | 2.81 | 9.57 | 2.81 |
| | 43.0 | 6.76 | 2.31 | 7.07 | 2.31 | 7.37 | 2.31 | 7.52 | 2.31 | 7.95 | 2.31 | 8.24 | 2.31 |
| | 46.0 | 5.62 | 1.80 | 5.86 | 1.80 | 6.09 | 1.80 | 6.21 | 1.80 | 6.54 | 1.80 | 6.76 | 1.80 |
| 2.0+2.0+2.0+7.1 | 22.0 | 9.34 | 2.26 | 9.77 | 2.30 | 10.20 | 2.35 | 10.41 | 2.37 | 11.06 | 2.44 | 11.48 | 2.48 |
| | 25.0 | 9.09 | 2.34 | 9.51 | 2.39 | 9.94 | 2.43 | 10.16 | 2.45 | 10.80 | 2.52 | 11.23 | 2.56 |
| | 32.0 | 8.48 | 2.55 | 8.91 | 2.59 | 9.34 | 2.64 | 9.55 | 2.66 | 10.19 | 2.72 | 10.62 | 2.77 |
| | 35.0 | 8.22 | 2.64 | 8.65 | 2.69 | 9.08 | 2.73 | **9.29** | **2.75** | 9.93 | 2.82 | 10.36 | 2.86 |
| | 40.0 | 7.78 | 2.81 | 8.16 | 2.81 | 8.52 | 2.81 | 8.70 | 2.81 | 9.23 | 2.81 | 9.57 | 2.81 |
| | 43.0 | 6.79 | 2.31 | 7.10 | 2.31 | 7.40 | 2.31 | 7.54 | 2.31 | 7.97 | 2.31 | 8.25 | 2.31 |
| | 46.0 | 5.65 | 1.80 | 5.89 | 1.80 | 6.12 | 1.80 | 6.23 | 1.80 | 6.57 | 1.80 | 6.78 | 1.80 |

### NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

### SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059242A