4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.0+3.5+4.2	22.0	8.85	2.27	9.26	2.31	9.66	2.36	9.87	2.38	10.47	2.44	10.88	2.49
	25.0	8.61	2.35	9.01	2.39	9.42	2.44	9.62	2.46	10.23	2.53	10.63	2.57
	32.0	8.03	2.56	8.44	2.60	8.84	2.64	9.05	2.67	9.65	2.73	10.06	2.78
	35.0	7.79	2.65	8.19	2.70	8.60	2.74	**8.80**	**2.76**	9.41	2.83	9.81	2.87
	40.0	7.36	2.81	7.72	2.81	8.07	2.81	8.24	2.81	8.75	2.81	9.07	2.81
	43.0	6.47	2.31	6.77	2.31	7.05	2.31	7.19	2.31	7.60	2.31	7.87	2.31
	46.0	5.42	1.80	5.65	1.80	5.87	1.80	5.98	1.80	6.30	1.80	6.50	1.80
2.0+2.0+3.5+5.0	22.0	9.25	2.43	9.68	2.48	10.10	2.53	10.31	2.55	10.95	2.62	11.37	2.67
	25.0	9.00	2.52	9.42	2.57	9.84	2.61	10.06	2.64	10.69	2.71	11.12	2.76
	32.0	8.40	2.74	8.82	2.79	9.25	2.84	9.46	2.86	10.09	2.93	10.52	2.98
	35.0	8.14	2.84	8.56	2.89	8.99	2.94	**9.20**	**2.96**	9.84	3.03	10.26	3.08
	40.0	7.52	2.81	7.88	2.81	8.23	2.81	8.40	2.81	8.90	2.81	9.22	2.81
	43.0	6.63	2.31	6.92	2.31	7.20	2.31	7.34	2.31	7.75	2.31	8.02	2.31
	46.0	5.56	1.80	5.78	1.80	6.00	1.80	6.11	1.80	6.43	1.80	6.64	1.80
2.0+2.0+3.5+6.0	22.0	9.34	2.30	9.77	2.35	10.20	2.39	10.41	2.41	11.06	2.48	11.48	2.53
	25.0	9.09	2.38	9.51	2.43	9.94	2.47	10.16	2.50	10.80	2.56	11.23	2.61
	32.0	8.48	2.59	8.91	2.64	9.34	2.68	9.55	2.71	10.19	2.77	10.62	2.82
	35.0	8.22	2.69	8.65	2.74	9.08	2.78	**9.29**	**2.80**	9.93	2.87	10.36	2.91
	40.0	7.73	2.81	8.10	2.81	8.46	2.81	8.64	2.81	9.16	2.81	9.50	2.81
	43.0	6.76	2.31	7.06	2.31	7.36	2.31	7.50	2.31	7.93	2.31	8.20	2.31
	46.0	5.63	1.80	5.87	1.80	6.10	1.80	6.21	1.80	6.54	1.80	6.75	1.80
2.0+2.0+4.2+4.2	22.0	8.98	2.35	9.39	2.40	9.81	2.44	10.01	2.46	10.63	2.53	11.04	2.58
	25.0	8.73	2.43	9.14	2.48	9.56	2.53	9.76	2.55	10.38	2.62	10.79	2.66
	32.0	8.15	2.65	8.56	2.70	8.97	2.74	9.18	2.76	9.80	2.83	10.21	2.88
	35.0	7.90	2.75	8.31	2.79	8.72	2.84	**8.93**	**2.86**	9.55	2.93	9.96	2.98
	40.0	7.38	2.81	7.74	2.81	8.08	2.81	8.25	2.81	8.75	2.81	9.08	2.81
	43.0	6.50	2.31	6.79	2.31	7.08	2.31	7.22	2.31	7.62	2.31	7.89	2.31
	46.0	5.46	1.80	5.68	1.80	5.90	1.80	6.01	1.80	6.32	1.80	6.53	1.80
2.0+2.0+4.2+5.0	22.0	9.26	2.43	9.69	2.48	10.11	2.53	10.32	2.55	10.96	2.62	11.39	2.67
	25.0	9.01	2.52	9.43	2.57	9.86	2.61	10.07	2.64	10.70	2.71	11.13	2.76
	32.0	8.41	2.74	8.83	2.79	9.26	2.84	9.47	2.86	10.10	2.93	10.53	2.98
	35.0	8.15	2.84	8.57	2.89	9.00	2.94	**9.21**	**2.96**	9.85	3.03	10.27	3.08
	40.0	7.53	2.81	7.89	2.81	8.23	2.81	8.41	2.81	8.91	2.81	9.23	2.81
	43.0	6.63	2.31	6.92	2.31	7.21	2.31	7.35	2.31	7.76	2.31	8.02	2.31
	46.0	5.56	1.80	5.79	1.80	6.01	1.80	6.11	1.80	6.43	1.80	6.64	1.80
2.0+2.5+2.5+2.5	22.0	8.34	2.01	8.72	2.04	9.10	2.08	9.29	2.10	9.87	2.16	10.25	2.20
	25.0	8.11	2.08	8.49	2.12	8.87	2.16	9.06	2.17	9.63	2.23	10.02	2.27
	32.0	7.57	2.26	7.95	2.30	8.33	2.34	8.52	2.36	9.09	2.42	9.48	2.46
	35.0	7.34	2.34	7.72	2.38	8.10	2.42	**8.29**	**2.44**	8.86	2.50	9.24	2.54
	40.0	6.95	2.49	7.33	2.53	7.71	2.57	7.90	2.59	8.48	2.65	8.86	2.69
	43.0	6.37	2.31	6.67	2.31	6.97	2.31	7.11	2.31	7.53	2.31	7.80	2.31
	46.0	5.31	1.80	5.54	1.80	5.77	1.80	5.88	1.80	6.21	1.80	6.42	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059243A