4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.5+3.5+5.0	22.0	9.38	2.51	9.81	2.56	10.24	2.61	10.46	2.64	11.10	2.71	11.53	2.76
	25.0	9.12	2.61	9.55	2.65	9.98	2.70	10.20	2.73	10.84	2.80	11.27	2.85
	32.0	8.52	2.83	8.95	2.88	9.38	2.93	9.59	2.96	10.24	3.03	10.67	3.08
	35.0	8.26	2.94	8.69	2.99	9.12	3.04	**9.33**	**3.06**	9.97	3.14	10.40	3.19
	40.0	7.56	2.81	7.91	2.81	8.26	2.81	8.43	2.81	8.93	2.81	9.25	2.81
	43.0	6.67	2.31	6.96	2.31	7.24	2.31	7.38	2.31	7.78	2.31	8.05	2.31
	46.0	5.60	1.80	5.82	1.80	6.04	1.80	6.15	1.80	6.47	1.80	6.67	1.80
2.0+2.5+4.2+4.2	22.0	8.99	2.35	9.40	2.40	9.82	2.44	10.02	2.46	10.64	2.53	11.05	2.58
	25.0	8.74	2.43	9.15	2.48	9.57	2.53	9.77	2.55	10.39	2.62	10.80	2.66
	32.0	8.16	2.65	8.57	2.70	8.98	2.74	9.19	2.76	9.81	2.83	10.22	2.88
	35.0	7.91	2.75	8.32	2.79	8.73	2.84	**8.94**	**2.86**	9.56	2.93	9.97	2.98
	40.0	7.39	2.81	7.75	2.81	8.09	2.81	8.26	2.81	8.76	2.81	9.09	2.81
	43.0	6.51	2.31	6.80	2.31	7.08	2.31	7.22	2.31	7.63	2.31	7.89	2.31
	46.0	5.46	1.80	5.68	1.80	5.90	1.80	6.01	1.80	6.33	1.80	6.53	1.80
2.0+3.5+3.5+3.5	22.0	9.29	2.56	9.72	2.61	10.15	2.66	10.36	2.68	11.00	2.75	11.42	2.80
	25.0	9.04	2.65	9.46	2.70	9.89	2.75	10.10	2.77	10.74	2.85	11.16	2.90
	32.0	8.43	2.88	8.86	2.93	9.29	2.98	9.50	3.01	10.14	3.08	10.56	3.13
	35.0	8.18	2.99	8.60	3.04	9.03	3.09	**9.24**	**3.11**	9.88	3.19	10.30	3.24
	40.0	7.46	2.81	7.81	2.81	8.15	2.81	8.32	2.81	8.81	2.81	9.13	2.81
	43.0	6.60	2.31	6.89	2.31	7.17	2.31	7.30	2.31	7.70	2.31	7.98	2.31
	46.0	5.56	1.80	5.78	1.80	5.99	1.80	6.10	1.80	6.41	1.80	6.61	1.80
2.0+3.5+3.5+4.2	22.0	9.30	2.56	9.73	2.61	10.16	2.66	10.37	2.68	11.01	2.75	11.44	2.80
	25.0	9.05	2.65	9.47	2.70	9.90	2.75	10.11	2.77	10.75	2.85	11.18	2.90
	32.0	8.44	2.88	8.87	2.93	9.30	2.98	9.51	3.01	10.15	3.08	10.57	3.13
	35.0	8.18	2.99	8.61	3.04	9.04	3.09	**9.25**	**3.11**	9.89	3.19	10.32	3.24
	40.0	7.47	2.81	7.82	2.81	8.16	2.81	8.33	2.81	8.82	2.81	9.14	2.81
	43.0	6.61	2.31	6.89	2.31	7.17	2.31	7.31	2.31	7.71	2.31	7.97	2.31
	46.0	5.56	1.80	5.78	1.80	6.00	1.80	6.11	1.80	6.42	1.80	6.62	1.80
2.5+2.5+2.5+2.5	22.0	8.49	2.06	8.88	2.10	9.27	2.14	9.46	2.16	10.05	2.22	10.43	2.26
	25.0	8.25	2.14	8.64	2.18	9.03	2.22	9.23	2.24	9.81	2.30	10.20	2.34
	32.0	7.70	2.33	8.09	2.37	8.48	2.41	8.68	2.43	9.26	2.49	9.65	2.53
	35.0	7.47	2.41	7.86	2.45	8.25	2.49	**8.44**	**2.51**	9.02	2.57	9.41	2.61
	40.0	7.07	2.57	7.46	2.61	7.85	2.65	8.05	2.67	8.63	2.73	9.02	2.77
	43.0	6.41	2.31	6.71	2.31	7.00	2.31	7.15	2.31	7.57	2.31	7.84	2.31
	46.0	5.35	1.80	5.58	1.80	5.80	1.80	5.92	1.80	6.24	1.80	6.45	1.80
2.5+2.5+2.5+3.5	22.0	8.84	2.27	9.25	2.31	9.65	2.36	9.85	2.38	10.46	2.44	10.87	2.49
	25.0	8.60	2.35	9.00	2.39	9.41	2.44	9.61	2.46	10.22	2.53	10.62	2.57
	32.0	8.02	2.56	8.43	2.60	8.83	2.64	9.04	2.67	9.64	2.73	10.05	2.78
	35.0	7.78	2.65	8.18	2.70	8.59	2.74	**8.79**	**2.76**	9.40	2.83	9.80	2.87
	40.0	7.35	2.81	7.71	2.81	8.06	2.81	8.23	2.81	8.74	2.81	9.06	2.81
	43.0	6.47	2.31	6.76	2.31	7.04	2.31	7.18	2.31	7.59	2.31	7.86	2.31
	46.0	5.42	1.80	5.64	1.80	5.86	1.80	5.97	1.80	6.29	1.80	6.50	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059244A