4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
7.1	22.0	5.94	1.62	7.29	2.20	7.88	2.41	8.05	2.43	8.55	2.50	8.88	2.54
	25.0	5.94	1.75	7.29	2.40	7.68	2.49	7.85	2.51	8.34	2.58	8.68	2.63
	32.0	5.94	2.14	6.88	2.66	7.22	2.70	7.38	2.72	7.88	2.79	8.21	2.84
	35.0	5.94	2.35	6.68	2.76	7.01	2.80	**7.18**	**2.82**	7.68	2.89	8.01	2.94
	40.0	5.94	2.80	6.29	2.81	6.59	2.81	6.73	2.81	7.16	2.81	7.44	2.81
	43.0	5.43	2.31	5.68	2.31	5.92	2.31	6.04	2.31	6.39	2.31	6.61	2.31
	46.0	4.67	1.80	4.86	1.80	5.05	1.80	5.14	1.80	5.41	1.80	5.59	1.80
2.0+2.0	22.0	5.24	1.20	5.48	1.22	5.72	1.25	5.84	1.26	6.20	1.29	6.44	1.32
	25.0	5.10	1.24	5.34	1.27	5.58	1.29	5.70	1.30	6.06	1.34	6.30	1.36
	32.0	4.76	1.35	5.00	1.38	5.24	1.40	5.36	1.41	5.72	1.45	5.96	1.47
	35.0	4.61	1.40	4.85	1.43	5.09	1.45	**5.21**	**1.46**	5.57	1.50	5.81	1.52
	40.0	4.37	1.49	4.61	1.52	4.85	1.54	4.97	1.55	5.33	1.59	5.57	1.61
	43.0	4.22	1.55	4.46	1.57	4.70	1.60	4.82	1.61	5.18	1.64	5.42	1.67
	46.0	4.08	1.61	4.32	1.63	4.56	1.66	4.68	1.67	5.04	1.70	5.28	1.73
2.0+2.5	22.0	5.69	1.38	5.95	1.41	6.21	1.43	6.35	1.45	6.74	1.49	7.00	1.52
	25.0	5.54	1.43	5.80	1.46	6.06	1.48	6.19	1.50	6.58	1.54	6.84	1.56
	32.0	5.17	1.56	5.43	1.58	5.69	1.61	5.82	1.62	6.21	1.66	6.47	1.69
	35.0	5.01	1.61	5.27	1.64	5.53	1.67	**5.66**	**1.68**	6.05	1.72	6.31	1.75
	40.0	4.74	1.72	5.01	1.74	5.27	1.77	5.40	1.78	5.79	1.83	6.05	1.85
	43.0	4.59	1.78	4.85	1.81	5.11	1.84	5.24	1.85	5.63	1.89	5.89	1.92
	46.0	4.37	1.80	4.58	1.80	4.80	1.80	4.90	1.80	5.21	1.80	5.40	1.80
2.0+3.5	22.0	6.26	1.73	6.54	1.76	6.83	1.79	6.97	1.81	7.40	1.86	7.69	1.89
	25.0	6.08	1.79	6.37	1.82	6.66	1.86	6.80	1.87	7.23	1.92	7.52	1.96
	32.0	5.68	1.95	5.96	1.98	6.25	2.01	6.39	2.03	6.82	2.08	7.11	2.11
	35.0	5.50	2.02	5.79	2.05	6.08	2.09	**6.22**	**2.10**	6.65	2.15	6.94	2.19
	40.0	5.21	2.15	5.50	2.18	5.79	2.21	5.93	2.23	6.36	2.28	6.65	2.32
	43.0	5.04	2.23	5.33	2.26	5.61	2.30	5.75	2.31	6.11	2.31	6.35	2.31
	46.0	4.34	1.80	4.55	1.80	4.74	1.80	4.84	1.80	5.13	1.80	5.31	1.80
2.0+4.2	22.0	6.43	1.92	6.75	1.98	7.05	2.02	7.20	2.03	7.64	2.09	7.94	2.13
	25.0	6.28	2.01	6.57	2.05	6.87	2.08	7.02	2.10	7.46	2.16	7.76	2.20
	32.0	5.86	2.19	6.16	2.22	6.45	2.26	6.60	2.28	7.04	2.34	7.34	2.37
	35.0	5.68	2.27	5.98	2.31	6.27	2.34	**6.42**	**2.36**	6.86	2.42	7.16	2.46
	40.0	5.38	2.41	5.68	2.45	5.97	2.49	6.12	2.51	6.56	2.56	6.86	2.60
	43.0	5.06	2.31	5.31	2.31	5.56	2.31	5.68	2.31	6.03	2.31	6.25	2.31
	46.0	4.34	1.80	4.54	1.80	4.73	1.80	4.82	1.80	5.09	1.80	5.27	1.80
2.0+5.0	22.0	7.20	2.04	7.53	2.08	7.86	2.12	8.03	2.14	8.52	2.20	8.85	2.24
	25.0	7.00	2.11	7.33	2.15	7.66	2.19	7.83	2.21	8.32	2.27	8.65	2.31
	32.0	6.54	2.30	6.87	2.34	7.20	2.38	7.36	2.40	7.85	2.46	8.18	2.50
	35.0	6.34	2.38	6.67	2.42	7.00	2.46	**7.16**	**2.48**	7.65	2.54	7.98	2.58
	40.0	6.00	2.54	6.33	2.58	6.66	2.62	6.83	2.63	7.32	2.69	7.65	2.73
	43.0	5.53	2.31	5.80	2.31	6.05	2.31	6.18	2.31	6.55	2.31	6.79	2.31
	46.0	4.70	1.80	4.91	1.80	5.11	1.80	5.20	1.80	5.49	1.80	5.68	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059235B