4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.5+6.0	22.0	7.71	2.15	8.06	2.20	8.41	2.24	8.59	2.26	9.12	2.32	9.47	2.36
	25.0	7.49	2.23	7.84	2.27	8.20	2.31	8.37	2.34	8.90	2.40	9.26	2.44
	32.0	6.99	2.43	7.34	2.47	7.70	2.51	7.87	2.53	8.40	2.59	8.76	2.64
	35.0	6.78	2.52	7.13	2.56	7.48	2.60	**7.66**	**2.62**	8.19	2.69	8.54	2.73
	40.0	6.42	2.68	6.77	2.72	7.13	2.76	7.30	2.78	7.79	2.81	8.09	2.81
	43.0	5.80	2.31	6.07	2.31	6.34	2.31	6.47	2.31	6.85	2.31	7.09	2.31
	46.0	4.91	1.80	5.12	1.80	5.33	1.80	5.43	1.80	5.72	1.80	5.92	1.80
2.5+7.1	22.0	8.07	2.39	8.44	2.44	8.81	2.48	8.99	2.51	9.55	2.58	9.91	2.62
	25.0	7.84	2.48	8.21	2.52	8.58	2.57	8.77	2.59	9.32	2.66	9.69	2.71
	32.0	7.32	2.70	7.69	2.74	8.06	2.79	8.24	2.81	8.80	2.88	9.17	2.93
	35.0	7.10	2.80	7.47	2.84	7.84	2.89	**8.02**	**2.91**	8.57	2.98	8.94	3.03
	40.0	6.63	2.81	6.95	2.81	7.27	2.81	7.42	2.81	7.88	2.81	8.17	2.81
	43.0	5.93	2.31	6.20	2.31	6.45	2.31	6.58	2.31	6.95	2.31	7.20	2.31
	46.0	5.05	1.80	5.25	1.80	5.45	1.80	5.55	1.80	5.84	1.80	6.03	1.80
3.5+3.5	22.0	6.76	2.05	7.56	2.39	7.89	2.43	8.06	2.46	8.56	2.52	8.89	2.57
	25.0	6.76	2.24	7.36	2.47	7.69	2.52	7.86	2.54	8.36	2.61	8.69	2.65
	32.0	6.56	2.64	6.89	2.69	7.23	2.73	7.39	2.75	7.89	2.82	8.22	2.87
	35.0	6.36	2.74	6.69	2.78	7.02	2.83	**7.19**	**2.85**	7.69	2.92	8.02	2.97
	40.0	5.99	2.81	6.29	2.81	6.58	2.81	6.73	2.81	7.15	2.81	7.43	2.81
	43.0	5.43	2.31	5.68	2.31	5.92	2.31	6.04	2.31	6.39	2.31	6.61	2.31
	46.0	4.68	1.80	4.87	1.80	5.05	1.80	5.14	1.80	5.41	1.80	5.59	1.80
3.5+4.2	22.0	6.76	2.05	8.01	2.74	8.36	2.79	8.53	2.82	9.06	2.90	9.41	2.95
	25.0	6.76	2.24	7.79	2.84	8.14	2.89	8.32	2.91	8.84	2.99	9.20	3.05
	32.0	6.76	2.85	7.30	3.08	7.65	3.13	7.82	3.16	8.35	3.24	8.70	3.29
	35.0	6.73	3.14	7.08	3.19	7.43	3.25	**7.61**	**3.27**	8.14	3.35	8.49	3.40
	40.0	6.26	2.81	6.55	2.81	6.84	2.81	6.98	2.81	7.40	2.81	7.67	2.81
	43.0	5.71	2.31	5.95	2.31	6.18	2.31	6.30	2.31	6.64	2.31	6.86	2.31
	46.0	4.92	1.80	5.11	1.80	5.29	1.80	5.39	1.80	5.65	1.80	5.82	1.80
3.5+5.0	22.0	7.71	2.40	8.06	2.45	8.41	2.49	8.59	2.52	9.12	2.59	9.47	2.63
	25.0	7.49	2.49	7.84	2.53	8.20	2.58	8.37	2.60	8.90	2.67	9.26	2.72
	32.0	6.99	2.70	7.34	2.75	7.70	2.80	7.87	2.82	8.40	2.89	8.76	2.94
	35.0	6.78	2.81	7.13	2.85	7.48	2.90	**7.66**	**2.92**	8.19	2.99	8.54	3.04
	40.0	6.34	2.81	6.65	2.81	6.95	2.81	7.10	2.81	7.54	2.81	7.83	2.81
	43.0	5.71	2.31	5.97	2.31	6.22	2.31	6.34	2.31	6.70	2.31	6.93	2.31
	46.0	4.89	1.80	5.08	1.80	5.28	1.80	5.37	1.80	5.65	1.80	5.83	1.80
3.5+6.0	22.0	8.01	2.35	8.37	2.40	8.74	2.44	8.92	2.46	9.47	2.53	9.84	2.58
	25.0	7.78	2.43	8.15	2.48	8.52	2.53	8.70	2.55	9.25	2.62	9.62	2.66
	32.0	7.27	2.65	7.63	2.70	8.00	2.74	8.18	2.76	8.73	2.83	9.10	2.88
	35.0	7.04	2.75	7.41	2.79	7.78	2.84	**7.96**	**2.86**	8.51	2.93	8.88	2.98
	40.0	6.60	2.81	6.93	2.81	7.24	2.81	7.40	2.81	7.86	2.81	8.15	2.81
	43.0	5.91	2.31	6.17	2.31	6.43	2.31	6.56	2.31	6.93	2.31	7.17	2.31
	46.0	5.02	1.80	5.23	1.80	5.43	1.80	5.53	1.80	5.82	1.80	6.01	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059236B