4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
5.0+6.0	22.0	8.38	2.52	8.76	2.57	9.15	2.62	9.34	2.65	9.91	2.72	10.30	2.77
	25.0	8.15	2.61	8.53	2.66	8.91	2.71	9.11	2.74	9.68	2.81	10.07	2.86
	32.0	7.60	2.84	7.99	2.89	8.37	2.94	8.56	2.97	9.14	3.04	9.52	3.09
	35.0	7.37	2.95	7.75	3.00	8.14	3.05	**8.33**	**3.07**	8.91	3.15	9.29	3.20
	40.0	6.80	2.81	7.13	2.81	7.44	2.81	7.60	2.81	8.06	2.81	8.35	2.81
	43.0	6.09	2.31	6.36	2.31	6.61	2.31	6.74	2.31	7.12	2.31	7.36	2.31
	46.0	5.18	1.80	5.39	1.80	5.59	1.80	5.69	1.80	5.98	1.80	6.17	1.80
5.0+7.1	22.0	8.56	2.65	8.95	2.70	9.34	2.75	9.54	2.78	10.13	2.85	10.52	2.90
	25.0	8.32	2.74	8.71	2.79	9.11	2.84	9.30	2.87	9.89	2.95	10.28	3.00
	32.0	7.77	2.98	8.16	3.03	8.55	3.09	8.75	3.11	9.34	3.19	9.73	3.24
	35.0	7.53	3.09	7.92	3.15	8.31	3.20	**8.51**	**3.22**	9.10	3.30	9.49	3.35
	40.0	6.90	2.81	7.22	2.81	7.54	2.81	7.69	2.81	8.14	2.81	8.44	2.81
	43.0	6.19	2.31	6.45	2.31	6.71	2.31	6.83	2.31	7.21	2.31	7.45	2.31
	46.0	5.27	1.80	5.47	1.80	5.67	1.80	5.77	1.80	6.06	1.80	6.25	1.80
6.0+6.0	22.0	8.57	2.39	8.96	2.44	9.36	2.48	9.55	2.51	10.14	2.58	10.53	2.62
	25.0	8.33	2.48	8.72	2.52	9.12	2.57	9.31	2.59	9.90	2.66	10.29	2.71
	32.0	7.78	2.70	8.17	2.74	8.56	2.79	8.76	2.81	9.35	2.88	9.74	2.93
	35.0	7.54	2.80	7.93	2.84	8.32	2.89	**8.52**	**2.91**	9.11	2.98	9.50	3.03
	40.0	7.02	2.81	7.36	2.81	7.69	2.81	7.85	2.81	8.33	2.81	8.64	2.81
	43.0	6.23	2.31	6.51	2.31	6.78	2.31	6.91	2.31	7.30	2.31	7.56	2.31
	46.0	5.27	1.80	5.48	1.80	5.69	1.80	5.79	1.80	6.10	1.80	6.29	1.80
6.0+7.1	22.0	8.65	2.43	9.05	2.48	9.44	2.53	9.64	2.55	10.24	2.62	10.63	2.67
	25.0	8.41	2.52	8.81	2.57	9.20	2.61	9.40	2.64	10.00	2.71	10.39	2.76
	32.0	7.85	2.74	8.25	2.79	8.64	2.84	8.84	2.86	9.43	2.93	9.83	2.98
	35.0	7.61	2.84	8.01	2.89	8.40	2.94	**8.60**	**2.96**	9.19	3.03	9.59	3.08
	40.0	7.06	2.81	7.39	2.81	7.72	2.81	7.89	2.81	8.36	2.81	8.67	2.81
	43.0	6.27	2.31	6.54	2.31	6.81	2.31	6.95	2.31	7.34	2.31	7.59	2.31
	46.0	5.30	1.80	5.51	1.80	5.72	1.80	5.82	1.80	6.13	1.80	6.32	1.80
2.0+2.0+2.0	22.0	6.82	1.55	7.13	1.58	7.44	1.61	7.60	1.63	8.07	1.67	8.38	1.70
	25.0	6.63	1.61	6.94	1.64	7.26	1.67	7.41	1.68	7.88	1.73	8.19	1.76
	32.0	6.19	1.75	6.50	1.78	6.81	1.81	6.97	1.83	7.44	1.87	7.75	1.90
	35.0	6.00	1.82	6.31	1.85	6.62	1.88	**6.78**	**1.89**	7.25	1.94	7.56	1.97
	40.0	5.68	1.93	6.00	1.96	6.31	1.99	6.46	2.01	6.93	2.05	7.25	2.08
	43.0	5.49	2.01	5.81	2.04	6.12	2.07	6.27	2.08	6.74	2.13	7.06	2.16
	46.0	4.90	1.80	5.13	1.80	5.36	1.80	5.47	1.80	5.80	1.80	6.01	1.80
2.0+2.0+2.5	22.0	7.11	1.70	7.44	1.73	7.76	1.77	7.93	1.78	8.41	1.83	8.74	1.87
	25.0	6.91	1.76	7.24	1.80	7.57	1.83	7.73	1.85	8.22	1.89	8.54	1.93
	32.0	6.45	1.92	6.78	1.95	7.10	1.98	7.27	2.00	7.76	2.05	8.08	2.08
	35.0	6.26	1.99	6.58	2.02	6.91	2.06	**7.07**	**2.07**	7.56	2.12	7.88	2.15
	40.0	5.93	2.12	6.25	2.15	6.58	2.18	6.74	2.20	7.23	2.25	7.56	2.28
	43.0	5.73	2.20	6.05	2.23	6.38	2.26	6.54	2.28	6.99	2.31	7.26	2.31
	46.0	4.89	1.80	5.12	1.80	5.34	1.80	5.45	1.80	5.77	1.80	5.97	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059237B