4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.5+3.5	22.0	7.74	2.03	8.09	2.07	8.44	2.11	8.62	2.13	9.15	2.19	9.51	2.23
	25.0	7.52	2.10	7.87	2.14	8.23	2.18	8.41	2.20	8.94	2.26	9.29	2.30
	32.0	7.02	2.29	7.37	2.33	7.73	2.37	7.90	2.39	8.44	2.45	8.79	2.49
	35.0	6.80	2.37	7.16	2.41	7.51	2.45	**7.69**	**2.47**	8.22	2.53	8.58	2.57
	40.0	6.45	2.53	6.80	2.57	7.15	2.60	7.33	2.62	7.86	2.68	8.22	2.72
	43.0	5.92	2.31	6.20	2.31	6.47	2.31	6.60	2.31	7.00	2.31	7.25	2.31
	46.0	4.98	1.80	5.20	1.80	5.41	1.80	5.51	1.80	5.82	1.80	6.02	1.80
2.0+2.5+4.2	22.0	7.88	2.11	8.24	2.15	8.60	2.19	8.78	2.21	9.32	2.28	9.68	2.32
	25.0	7.66	2.19	8.02	2.23	8.38	2.27	8.56	2.29	9.10	2.35	9.46	2.39
	32.0	7.15	2.38	7.51	2.42	7.87	2.46	8.05	2.48	8.59	2.55	8.95	2.59
	35.0	6.93	2.47	7.29	2.51	7.65	2.55	**7.83**	**2.57**	8.37	2.63	8.73	2.68
	40.0	6.56	2.63	6.92	2.67	7.29	2.71	7.47	2.73	8.01	2.79	8.33	2.81
	43.0	5.95	2.31	6.22	2.31	6.49	2.31	6.63	2.31	7.02	2.31	7.27	2.31
	46.0	5.01	1.80	5.23	1.80	5.44	1.80	5.54	1.80	5.85	1.80	6.04	1.80
2.0+2.5+5.0	22.0	8.26	2.29	8.64	2.34	9.01	2.38	9.20	2.40	9.77	2.47	10.15	2.52
	25.0	8.03	2.38	8.41	2.42	8.79	2.46	8.97	2.49	9.54	2.55	9.92	2.60
	32.0	7.49	2.58	7.87	2.63	8.25	2.67	8.44	2.70	9.01	2.76	9.38	2.81
	35.0	7.26	2.68	7.64	2.73	8.02	2.77	**8.21**	**2.79**	8.78	2.86	9.16	2.90
	40.0	6.85	2.81	7.19	2.81	7.52	2.81	7.68	2.81	8.15	2.81	8.46	2.81
	43.0	6.09	2.31	6.36	2.31	6.63	2.31	6.76	2.31	7.15	2.31	7.40	2.31
	46.0	5.14	1.80	5.35	1.80	5.56	1.80	5.67	1.80	5.97	1.80	6.16	1.80
2.0+2.5+6.0	22.0	8.61	2.27	9.00	2.31	9.40	2.36	9.60	2.38	10.19	2.44	10.58	2.49
	25.0	8.37	2.35	8.77	2.39	9.16	2.44	9.36	2.46	9.95	2.53	10.34	2.57
	32.0	7.81	2.56	8.21	2.60	8.60	2.64	8.80	2.67	9.39	2.73	9.79	2.78
	35.0	7.57	2.65	7.97	2.70	8.36	2.74	**8.56**	**2.76**	9.15	2.83	9.55	2.87
	40.0	7.16	2.81	7.51	2.81	7.86	2.81	8.02	2.81	8.52	2.81	8.84	2.81
	43.0	6.32	2.31	6.61	2.31	6.89	2.31	7.02	2.31	7.42	2.31	7.69	2.31
	46.0	5.31	1.80	5.53	1.80	5.75	1.80	5.85	1.80	6.17	1.80	6.37	1.80
2.0+2.5+7.1	22.0	8.81	2.39	9.22	2.44	9.62	2.48	9.82	2.51	10.43	2.58	10.83	2.62
	25.0	8.57	2.48	8.97	2.52	9.37	2.57	9.58	2.59	10.18	2.66	10.58	2.71
	32.0	8.00	2.70	8.40	2.74	8.80	2.79	9.00	2.81	9.61	2.88	10.01	2.93
	35.0	7.75	2.80	8.15	2.84	8.56	2.89	**8.76**	**2.91**	9.37	2.98	9.77	3.03
	40.0	7.21	2.81	7.56	2.81	7.90	2.81	8.06	2.81	8.55	2.81	8.87	2.81
	43.0	6.38	2.31	6.66	2.31	6.94	2.31	7.07	2.31	7.47	2.31	7.73	2.31
	46.0	5.37	1.80	5.59	1.80	5.80	1.80	5.91	1.80	6.22	1.80	6.42	1.80
2.0+3.5+3.5	22.0	8.12	2.27	8.49	2.31	8.86	2.36	9.05	2.38	9.60	2.44	9.98	2.49
	25.0	7.89	2.35	8.26	2.39	8.64	2.44	8.82	2.46	9.38	2.53	9.75	2.57
	32.0	7.37	2.56	7.74	2.60	8.11	2.64	8.30	2.67	8.85	2.73	9.22	2.78
	35.0	7.14	2.65	7.51	2.70	7.88	2.74	**8.07**	**2.76**	8.63	2.83	9.00	2.87
	40.0	6.75	2.81	7.09	2.81	7.42	2.81	7.58	2.81	8.05	2.81	8.35	2.81
	43.0	6.01	2.31	6.28	2.31	6.55	2.31	6.68	2.31	7.06	2.31	7.31	2.31
	46.0	5.08	1.80	5.29	1.80	5.50	1.80	5.60	1.80	5.90	1.80	6.09	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059238B