4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+4.2+6.0	22.0	8.81	2.39	9.22	2.44	9.62	2.48	9.82	2.51	10.43	2.58	10.83	2.62
	25.0	8.57	2.48	8.97	2.52	9.37	2.57	9.58	2.59	10.18	2.66	10.58	2.71
	32.0	8.00	2.70	8.40	2.74	8.80	2.79	9.00	2.81	9.61	2.88	10.01	2.93
	35.0	7.75	2.80	8.15	2.84	8.56	2.89	**8.76**	**2.91**	9.37	2.98	9.77	3.03
	40.0	7.21	2.81	7.56	2.81	7.90	2.81	8.06	2.81	8.55	2.81	8.87	2.81
	43.0	6.38	2.31	6.66	2.31	6.94	2.31	7.07	2.31	7.47	2.31	7.73	2.31
	46.0	5.37	1.80	5.59	1.80	5.80	1.80	5.91	1.80	6.22	1.80	6.42	1.80
2.0+4.2+7.1	22.0	9.01	2.51	9.43	2.56	9.84	2.61	10.04	2.64	10.66	2.71	11.08	2.76
	25.0	8.76	2.61	9.18	2.65	9.59	2.70	9.79	2.73	10.41	2.80	10.83	2.85
	32.0	8.18	2.83	8.59	2.88	9.00	2.93	9.21	2.96	9.83	3.03	10.24	3.08
	35.0	7.93	2.94	8.34	2.99	8.75	3.04	**8.96**	**3.06**	9.58	3.14	9.99	3.19
	40.0	7.28	2.81	7.62	2.81	7.96	2.81	8.12	2.81	8.61	2.81	8.92	2.81
	43.0	6.46	2.31	6.73	2.31	7.01	2.31	7.14	2.31	7.54	2.31	7.79	2.31
	46.0	5.44	1.80	5.66	1.80	5.87	1.80	5.98	1.80	6.28	1.80	6.48	1.80
2.0+5.0+5.0	22.0	8.89	2.61	9.30	2.66	9.71	2.71	9.91	2.73	10.52	2.81	10.93	2.86
	25.0	8.65	2.70	9.05	2.75	9.46	2.80	9.66	2.83	10.27	2.90	10.68	2.95
	32.0	8.07	2.94	8.48	2.99	8.88	3.04	9.09	3.06	9.70	3.14	10.11	3.19
	35.0	7.82	3.05	8.23	3.10	8.64	3.15	**8.84**	**3.17**	9.45	3.25	9.86	3.30
	40.0	7.15	2.81	7.48	2.81	7.81	2.81	7.97	2.81	8.44	2.81	8.74	2.81
	43.0	6.37	2.31	6.64	2.31	6.91	2.31	7.04	2.31	7.42	2.31	7.67	2.31
	46.0	5.40	1.80	5.61	1.80	5.81	1.80	5.92	1.80	6.21	1.80	6.41	1.80
2.0+5.0+6.0	22.0	9.02	2.43	9.44	2.48	9.85	2.53	10.06	2.55	10.68	2.62	11.09	2.67
	25.0	8.77	2.52	9.19	2.57	9.60	2.61	9.81	2.64	10.43	2.71	10.84	2.76
	32.0	8.19	2.74	8.60	2.79	9.01	2.84	9.22	2.86	9.84	2.93	10.25	2.98
	35.0	7.94	2.84	8.35	2.89	8.76	2.94	**8.97**	**2.96**	9.59	3.03	10.00	3.08
	40.0	7.34	2.81	7.69	2.81	8.03	2.81	8.20	2.81	8.69	2.81	9.01	2.81
	43.0	6.49	2.31	6.77	2.31	7.05	2.31	7.19	2.31	7.59	2.31	7.85	2.31
	46.0	5.46	1.80	5.68	1.80	5.89	1.80	6.00	1.80	6.31	1.80	6.51	1.80
2.5+2.5+2.5	22.0	7.53	1.91	7.88	1.95	8.22	1.99	8.40	2.01	8.91	2.06	9.26	2.10
	25.0	7.32	1.98	7.67	2.02	8.01	2.06	8.19	2.08	8.71	2.13	9.05	2.17
	32.0	6.84	2.16	7.18	2.20	7.53	2.23	7.70	2.25	8.22	2.31	8.56	2.34
	35.0	6.63	2.24	6.97	2.28	7.32	2.31	**7.49**	**2.33**	8.01	2.39	8.35	2.43
	40.0	6.28	2.38	6.62	2.42	6.97	2.46	7.14	2.48	7.66	2.53	8.00	2.57
	43.0	5.89	2.31	6.17	2.31	6.45	2.31	6.59	2.31	6.99	2.31	7.25	2.31
	46.0	4.94	1.80	5.16	1.80	5.38	1.80	5.48	1.80	5.79	1.80	6.00	1.80
2.5+2.5+3.5	22.0	7.93	2.15	8.29	2.20	8.65	2.24	8.83	2.26	9.38	2.32	9.74	2.36
	25.0	7.71	2.23	8.07	2.27	8.43	2.31	8.61	2.34	9.16	2.40	9.52	2.44
	32.0	7.19	2.43	7.56	2.47	7.92	2.51	8.10	2.53	8.64	2.59	9.01	2.64
	35.0	6.97	2.52	7.34	2.56	7.70	2.60	**7.88**	**2.62**	8.42	2.69	8.79	2.73
	40.0	6.61	2.68	6.97	2.72	7.33	2.76	7.51	2.78	8.01	2.81	8.32	2.81
	43.0	5.95	2.31	6.23	2.31	6.50	2.31	6.63	2.31	7.02	2.31	7.27	2.31
	46.0	5.02	1.80	5.24	1.80	5.45	1.80	5.55	1.80	5.85	1.80	6.05	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059239B