4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.5+3.5+5.0	22.0	8.67	2.56	9.07	2.61	9.47	2.66	9.66	2.69	10.26	2.76	10.66	2.81
	25.0	8.43	2.66	8.83	2.71	9.22	2.76	9.42	2.78	10.02	2.86	10.42	2.91
	32.0	7.87	2.89	8.27	2.94	8.66	2.99	8.86	3.01	9.46	3.09	9.85	3.14
	35.0	7.63	3.00	8.02	3.05	8.42	3.10	**8.62**	**3.12**	9.22	3.20	9.61	3.25
	40.0	7.00	2.81	7.33	2.81	7.65	2.81	7.81	2.81	8.28	2.81	8.58	2.81
	43.0	6.25	2.31	6.52	2.31	6.78	2.31	6.91	2.31	7.29	2.31	7.54	2.31
	46.0	5.30	1.80	5.51	1.80	5.72	1.80	5.82	1.80	6.11	1.80	6.31	1.80
2.5+3.5+6.0	22.0	8.92	2.47	9.33	2.52	9.74	2.57	9.94	2.59	10.56	2.67	10.97	2.71
	25.0	8.67	2.56	9.08	2.61	9.49	2.66	9.70	2.68	10.31	2.76	10.72	2.80
	32.0	8.10	2.79	8.50	2.84	8.91	2.88	9.12	2.91	9.73	2.98	10.14	3.03
	35.0	7.85	2.89	8.26	2.94	8.67	2.99	**8.87**	**3.01**	9.48	3.09	9.89	3.13
	40.0	7.24	2.81	7.58	2.81	7.92	2.81	8.08	2.81	8.56	2.81	8.88	2.81
	43.0	6.41	2.31	6.69	2.31	6.97	2.31	7.10	2.31	7.50	2.31	7.76	2.31
	46.0	5.41	1.80	5.63	1.80	5.84	1.80	5.94	1.80	6.25	1.80	6.45	1.80
2.5+3.5+7.1	22.0	9.06	2.56	9.48	2.61	9.89	2.66	10.10	2.69	10.72	2.76	11.14	2.81
	25.0	8.81	2.66	9.23	2.71	9.64	2.76	9.85	2.78	10.47	2.86	10.89	2.91
	32.0	8.22	2.89	8.64	2.94	9.05	2.99	9.26	3.01	9.88	3.09	10.30	3.14
	35.0	7.97	3.00	8.39	3.05	8.80	3.10	**9.01**	**3.12**	9.63	3.20	10.05	3.25
	40.0	7.29	2.81	7.63	2.81	7.96	2.81	8.13	2.81	8.61	2.81	8.92	2.81
	43.0	6.47	2.31	6.75	2.31	7.02	2.31	7.16	2.31	7.55	2.31	7.80	2.31
	46.0	5.46	1.80	5.68	1.80	5.89	1.80	5.99	1.80	6.30	1.80	6.50	1.80
2.5+4.2+4.2	22.0	8.31	2.39	8.69	2.44	9.07	2.48	9.26	2.51	9.83	2.58	10.21	2.62
	25.0	8.08	2.48	8.46	2.52	8.84	2.57	9.03	2.59	9.60	2.66	9.98	2.71
	32.0	7.54	2.70	7.92	2.74	8.30	2.79	8.49	2.81	9.06	2.88	9.44	2.93
	35.0	7.31	2.80	7.69	2.84	8.07	2.89	**8.26**	**2.91**	8.83	2.98	9.21	3.03
	40.0	6.82	2.81	7.15	2.81	7.47	2.81	7.63	2.81	8.10	2.81	8.40	2.81
	43.0	6.08	2.31	6.35	2.31	6.61	2.31	6.74	2.31	7.12	2.31	7.37	2.31
	46.0	5.15	1.80	5.36	1.80	5.57	1.80	5.67	1.80	5.96	1.80	6.15	1.80
2.5+4.2+5.0	22.0	8.68	2.56	9.08	2.61	9.48	2.66	9.67	2.69	10.27	2.76	10.67	2.81
	25.0	8.44	2.66	8.84	2.71	9.23	2.76	9.43	2.78	10.03	2.86	10.43	2.91
	32.0	7.88	2.89	8.27	2.94	8.67	2.99	8.87	3.01	9.47	3.09	9.87	3.14
	35.0	7.64	3.00	8.03	3.05	8.43	3.10	**8.63**	**3.12**	9.23	3.20	9.62	3.25
	40.0	7.01	2.81	7.34	2.81	7.66	2.81	7.82	2.81	8.29	2.81	8.59	2.81
	43.0	6.26	2.31	6.53	2.31	6.79	2.31	6.92	2.31	7.30	2.31	7.55	2.31
	46.0	5.31	1.80	5.52	1.80	5.72	1.80	5.82	1.80	6.12	1.80	6.31	1.80
2.5+4.2+6.0	22.0	8.93	2.47	9.34	2.52	9.75	2.57	9.96	2.59	10.57	2.67	10.98	2.71
	25.0	8.68	2.56	9.09	2.61	9.50	2.66	9.71	2.68	10.32	2.76	10.73	2.80
	32.0	8.11	2.79	8.51	2.84	8.92	2.88	9.13	2.91	9.74	2.98	10.15	3.03
	35.0	7.86	2.89	8.27	2.94	8.68	2.99	**8.88**	**3.01**	9.49	3.09	9.90	3.13
	40.0	7.24	2.81	7.59	2.81	7.92	2.81	8.09	2.81	8.57	2.81	8.89	2.81
	43.0	6.42	2.31	6.70	2.31	6.97	2.31	7.11	2.31	7.51	2.31	7.76	2.31
	46.0	5.41	1.80	5.63	1.80	5.84	1.80	5.95	1.80	6.25	1.80	6.45	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ▭ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059240B