4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
3.5+4.2+4.2	22.0	8.59	2.61	8.98	2.66	9.38	2.71	9.57	2.73	10.16	2.81	10.56	2.86
	25.0	8.35	2.70	8.75	2.75	9.14	2.80	9.34	2.83	9.93	2.90	10.32	2.95
	32.0	7.79	2.94	8.19	2.99	8.58	3.04	8.78	3.06	9.37	3.14	9.76	3.19
	35.0	7.56	3.05	7.95	3.10	8.34	3.15	**8.54**	**3.17**	9.13	3.25	9.52	3.30
	40.0	6.93	2.81	7.26	2.81	7.57	2.81	7.73	2.81	8.19	2.81	8.49	2.81
	43.0	6.20	2.31	6.47	2.31	6.73	2.31	6.86	2.31	7.23	2.31	7.48	2.31
	46.0	5.28	1.80	5.48	1.80	5.68	1.80	5.78	1.80	6.07	1.80	6.26	1.80
3.5+4.2+5.0	22.0	8.89	2.65	9.30	2.70	9.71	2.75	9.91	2.78	10.52	2.85	10.93	2.90
	25.0	8.65	2.74	9.05	2.79	9.46	2.84	9.66	2.87	10.27	2.95	10.68	3.00
	32.0	8.07	2.98	8.48	3.03	8.88	3.09	9.09	3.11	9.70	3.19	10.11	3.24
	35.0	7.82	3.09	8.23	3.15	8.64	3.20	**8.84**	**3.22**	9.45	3.30	9.86	3.35
	40.0	7.13	2.81	7.47	2.81	7.79	2.81	7.95	2.81	8.42	2.81	8.72	2.81
	43.0	6.37	2.31	6.64	2.31	6.90	2.31	7.03	2.31	7.41	2.31	7.66	2.31
	46.0	5.40	1.80	5.61	1.80	5.82	1.80	5.92	1.80	6.21	1.80	6.41	1.80
3.5+5.0+5.0	22.0	9.09	2.61	9.51	2.66	9.93	2.71	10.13	2.73	10.76	2.81	11.18	2.86
	25.0	8.84	2.70	9.26	2.75	9.67	2.80	9.88	2.83	10.51	2.90	10.92	2.95
	32.0	8.25	2.94	8.67	2.99	9.08	3.04	9.29	3.06	9.92	3.14	10.33	3.19
	35.0	8.00	3.05	8.42	3.10	8.83	3.15	**9.04**	**3.17**	9.66	3.25	10.08	3.30
	40.0	7.29	2.81	7.63	2.81	7.96	2.81	8.13	2.81	8.61	2.81	8.92	2.81
	43.0	6.48	2.31	6.76	2.31	7.03	2.31	7.16	2.31	7.55	2.31	7.81	2.31
	46.0	5.48	1.80	5.69	1.80	5.90	1.80	6.01	1.80	6.31	1.80	6.51	1.80
4.2+4.2+4.2	22.0	8.60	2.61	8.99	2.66	9.39	2.71	9.59	2.73	10.18	2.81	10.57	2.86
	25.0	8.36	2.70	8.76	2.75	9.15	2.80	9.35	2.83	9.94	2.90	10.33	2.95
	32.0	7.80	2.94	8.20	2.99	8.59	3.04	8.79	3.06	9.38	3.14	9.77	3.19
	35.0	7.57	3.05	7.96	3.10	8.35	3.15	**8.55**	**3.17**	9.14	3.25	9.53	3.30
	40.0	6.94	2.81	7.26	2.81	7.58	2.81	7.74	2.81	8.20	2.81	8.50	2.81
	43.0	6.21	2.31	6.48	2.31	6.74	2.31	6.86	2.31	7.24	2.31	7.48	2.31
	46.0	5.28	1.80	5.49	1.80	5.69	1.80	5.79	1.80	6.08	1.80	6.27	1.80
4.2+4.2+5.0	22.0	8.90	2.65	9.31	2.70	9.72	2.75	9.92	2.78	10.53	2.85	10.94	2.90
	25.0	8.65	2.74	9.06	2.79	9.47	2.84	9.67	2.87	10.29	2.95	10.69	3.00
	32.0	8.08	2.98	8.49	3.03	8.89	3.09	9.10	3.11	9.71	3.19	10.12	3.24
	35.0	7.83	3.09	8.24	3.15	8.65	3.20	**8.85**	**3.22**	9.46	3.30	9.87	3.35
	40.0	7.14	2.81	7.47	2.81	7.80	2.81	7.96	2.81	8.42	2.81	8.73	2.81
	43.0	6.37	2.31	6.64	2.31	6.91	2.31	7.04	2.31	7.42	2.31	7.67	2.31
	46.0	5.40	1.80	5.61	1.80	5.82	1.80	5.92	1.80	6.22	1.80	6.41	1.80
2.0+2.0+2.0+2.0	22.0	7.88	1.76	8.24	1.79	8.60	1.83	8.78	1.84	9.32	1.90	9.68	1.93
	25.0	7.66	1.82	8.02	1.86	8.38	1.89	8.56	1.91	9.10	1.96	9.46	1.99
	32.0	7.15	1.98	7.51	2.02	7.87	2.05	8.05	2.07	8.59	2.12	8.95	2.15
	35.0	6.93	2.06	7.29	2.09	7.65	2.13	**7.83**	**2.14**	8.37	2.19	8.73	2.23
	40.0	6.56	2.19	6.92	2.22	7.29	2.26	7.47	2.27	8.01	2.33	8.37	2.36
	43.0	6.34	2.27	6.71	2.31	7.01	2.31	7.16	2.31	7.60	2.31	7.88	2.31
	46.0	5.28	1.80	5.53	1.80	5.76	1.80	5.88	1.80	6.22	1.80	6.44	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059241B