4MKS75F (★ cooling 50Hz 230V)

Combination (Capacity)	Outdoor air temp. °CWB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.0+2.5+2.5	22.0	8.19	1.92	8.56	1.96	8.94	2.00	9.13	2.02	9.69	2.07	10.06	2.11
	25.0	7.96	1.99	8.34	2.03	8.71	2.07	8.90	2.09	9.46	2.14	9.84	2.18
	32.0	7.43	2.17	7.80	2.21	8.18	2.24	8.37	2.26	8.93	2.32	9.30	2.35
	35.0	7.20	2.25	7.58	2.29	7.95	2.32	**8.14**	**2.34**	8.70	2.40	9.08	2.44
	40.0	6.82	2.39	7.20	2.43	7.57	2.47	7.76	2.49	8.32	2.54	8.70	2.58
	43.0	6.37	2.31	6.67	2.31	6.97	2.31	7.11	2.31	7.54	2.31	7.82	2.31
	46.0	5.29	1.80	5.53	1.80	5.76	1.80	5.87	1.80	6.20	1.80	6.42	1.80
2.0+2.0+2.5+3.5	22.0	8.49	2.06	8.88	2.10	9.27	2.14	9.46	2.16	10.05	2.22	10.43	2.26
	25.0	8.25	2.14	8.64	2.18	9.03	2.22	9.23	2.24	9.81	2.30	10.20	2.34
	32.0	7.70	2.33	8.09	2.37	8.48	2.41	8.68	2.43	9.26	2.49	9.65	2.53
	35.0	7.47	2.41	7.86	2.45	8.25	2.49	**8.44**	**2.51**	9.02	2.57	9.41	2.61
	40.0	7.07	2.57	7.46	2.61	7.85	2.65	8.05	2.67	8.63	2.73	9.02	2.77
	43.0	6.41	2.31	6.71	2.31	7.00	2.31	7.15	2.31	7.57	2.31	7.84	2.31
	46.0	5.35	1.80	5.58	1.80	5.80	1.80	5.92	1.80	6.24	1.80	6.45	1.80
2.0+2.0+2.5+4.2	22.0	8.50	2.06	8.89	2.10	9.28	2.14	9.47	2.16	10.06	2.22	10.45	2.26
	25.0	8.26	2.14	8.65	2.18	9.04	2.22	9.24	2.24	9.82	2.30	10.21	2.34
	32.0	7.71	2.33	8.10	2.37	8.49	2.41	8.69	2.43	9.27	2.49	9.66	2.53
	35.0	7.48	2.41	7.87	2.45	8.26	2.49	**8.45**	**2.51**	9.03	2.57	9.42	2.61
	40.0	7.08	2.57	7.47	2.61	7.86	2.65	8.06	2.67	8.64	2.73	9.03	2.77
	43.0	6.42	2.31	6.72	2.31	7.01	2.31	7.16	2.31	7.58	2.31	7.85	2.31
	46.0	5.35	1.80	5.58	1.80	5.81	1.80	5.92	1.80	6.25	1.80	6.46	1.80
2.0+2.0+2.5+5.0	22.0	8.91	2.27	9.32	2.31	9.73	2.36	9.93	2.38	10.54	2.44	10.95	2.49
	25.0	8.66	2.35	9.07	2.39	9.48	2.44	9.69	2.46	10.30	2.53	10.71	2.57
	32.0	8.09	2.56	8.50	2.60	8.90	2.64	9.11	2.67	9.72	2.73	10.13	2.78
	35.0	7.84	2.65	8.25	2.70	8.66	2.74	**8.86**	**2.76**	9.47	2.83	9.88	2.87
	40.0	7.41	2.81	7.77	2.81	8.12	2.81	8.30	2.81	8.80	2.81	9.13	2.81
	43.0	6.51	2.31	6.81	2.31	7.09	2.31	7.23	2.31	7.65	2.31	7.91	2.31
	46.0	5.45	1.80	5.68	1.80	5.90	1.80	6.01	1.80	6.33	1.80	6.54	1.80
2.0+2.0+2.5+6.0	22.0	9.18	2.18	9.60	2.22	10.02	2.26	10.24	2.28	10.87	2.35	11.29	2.39
	25.0	8.93	2.26	9.35	2.30	9.77	2.34	9.98	2.36	10.61	2.43	11.03	2.47
	32.0	8.33	2.45	8.75	2.50	9.17	2.54	9.39	2.56	10.02	2.62	10.44	2.67
	35.0	8.08	2.55	8.50	2.59	8.92	2.63	**9.13**	**2.65**	9.76	2.72	10.18	2.76
	40.0	7.65	2.71	8.07	2.75	8.49	2.79	8.69	2.81	9.22	2.81	9.57	2.81
	43.0	6.76	2.31	7.07	2.31	7.37	2.31	7.52	2.31	7.95	2.31	8.24	2.31
	46.0	5.62	1.80	5.86	1.80	6.09	1.80	6.21	1.80	6.54	1.80	6.76	1.80
2.0+2.0+3.5+3.5	22.0	8.84	2.27	9.25	2.31	9.65	2.36	9.85	2.38	10.46	2.44	10.87	2.49
	25.0	8.60	2.35	9.00	2.39	9.41	2.44	9.61	2.46	10.22	2.53	10.62	2.57
	32.0	8.02	2.56	8.43	2.60	8.83	2.64	9.04	2.67	9.64	2.73	10.05	2.78
	35.0	7.78	2.65	8.18	2.70	8.59	2.74	**8.79**	**2.76**	9.40	2.83	9.80	2.87
	40.0	7.35	2.81	7.71	2.81	8.06	2.81	8.23	2.81	8.74	2.81	9.06	2.81
	43.0	6.47	2.31	6.76	2.31	7.04	2.31	7.18	2.31	7.59	2.31	7.86	2.31
	46.0	5.42	1.80	5.64	1.80	5.86	1.80	5.97	1.80	6.29	1.80	6.50	1.80

NOTES

1 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2 kW class; wall mounted G series

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

3D059242B