4MKS75F (★ cooling 50Hz 230V)

Outdoor unit	Combination of indoor unit	Capacity of each indoor unit										
		Each capacity (kW)				Total capacity (kW)		Total input (W)		Total current (A)		Power factor (%)
		A Room	B Room	C Room	D Room	Rating	(Min.~max.)	Rating	(Min.~max.)	Rating	(Min.~max.)	Rating
4MKS75F2V1B	2.0+2.0+3.5+4.2	1.28	1.28	2.24	2.69	7.50	2.47 ~ 8.80	1980	420 ~ 2760	8.7	1.8 ~ 12.1	99
	2.0+2.0+3.5+5.0	1.20	1.20	2.10	3.00	7.50	2.72 ~ 9.20	1930	480 ~ 2960	8.5	2.1 ~ 13.0	99
	2.0+2.0+3.5+6.0	1.11	1.11	1.95	3.33	7.50	2.88 ~ 9.29	1790	510 ~ 2800	7.9	2.2 ~ 12.3	99
	2.0+2.0+4.2+4.2	1.21	1.21	2.54	2.54	7.50	2.47 ~ 8.93	1980	420 ~ 2860	8.7	1.8 ~ 12.6	99
	2.0+2.0+4.2+5.0	1.14	1.14	2.39	2.84	7.50	2.72 ~ 9.21	1930	480 ~ 2960	8.5	2.1 ~ 13.0	99
	2.0+2.5+2.5+2.5	1.59	1.97	1.97	1.97	7.50	2.36 ~ 8.29	1980	390 ~ 2440	8.7	1.7 ~ 10.7	99
	2.0+2.5+2.5+3.5	1.43	1.79	1.79	2.49	7.50	2.47 ~ 8.58	1980	420 ~ 2610	8.7	1.8 ~ 11.5	99
	2.0+2.5+2.5+4.2	1.34	1.67	1.67	2.81	7.50	2.47 ~ 8.59	1980	420 ~ 2610	8.7	1.8 ~ 11.5	99
	2.0+2.5+2.5+5.0	1.25	1.56	1.56	3.13	7.50	2.60 ~ 9.00	1930	460 ~ 2800	8.5	2.0 ~ 12.3	99
	2.0+2.5+2.5+6.0	1.15	1.44	1.44	3.47	7.50	2.88 ~ 9.28	1790	510 ~ 2780	7.9	2.2 ~ 12.2	99
	2.0+2.5+3.5+3.5	1.30	1.64	2.28	2.28	7.50	2.47 ~ 8.92	1980	420 ~ 2860	8.7	1.8 ~ 12.6	99
	2.0+2.5+3.5+4.2	1.23	1.54	2.15	2.58	7.50	2.47 ~ 8.93	1980	420 ~ 2860	8.7	1.8 ~ 12.6	99
	2.0+2.5+3.5+5.0	1.15	1.44	2.03	2.88	7.50	2.83 ~ 9.33	1930	500 ~ 3060	8.5	2.2 ~ 13.4	99
	2.0+2.5+4.2+4.2	1.16	1.45	2.44	2.44	7.50	2.47 ~ 8.94	1980	420 ~ 2860	8.7	1.8 ~ 12.6	99
	2.0+3.5+3.5+3.5	1.20	2.10	2.10	2.10	7.50	2.70 ~ 9.24	1980	460 ~ 3110	8.7	2.0 ~ 13.7	99
	2.0+3.5+3.5+4.2	1.14	1.99	1.99	2.39	7.50	2.70 ~ 9.25	1980	460 ~ 3110	8.7	2.0 ~ 13.7	99
	2.5+2.5+2.5+2.5	1.87	1.87	1.87	1.87	7.48	2.36 ~ 8.44	1980	390 ~ 2510	8.7	1.7 ~ 11.0	99
	2.5+2.5+2.5+3.5	1.70	1.70	1.70	2.40	7.50	2.47 ~ 8.79	1980	420 ~ 2760	8.7	1.8 ~ 12.1	99
	2.5+2.5+2.5+4.2	1.60	1.60	1.60	2.69	7.50	2.47 ~ 8.79	1980	420 ~ 2760	8.7	1.8 ~ 12.1	99
	2.5+2.5+2.5+5.0	1.50	1.50	1.50	3.00	7.50	2.60 ~ 9.20	1930	460 ~ 2960	8.5	2.0 ~ 13.0	99
	2.5+2.5+2.5+6.0	1.39	1.39	1.39	3.33	7.50	2.88 ~ 9.28	1790	500 ~ 2750	7.9	2.2 ~ 12.1	99
	2.5+2.5+3.5+3.5	1.56	1.56	2.19	2.19	7.50	2.59 ~ 9.05	1980	430 ~ 2960	8.7	1.9 ~ 13.0	99
	2.5+2.5+3.5+4.2	1.48	1.48	2.07	2.48	7.50	2.59 ~ 9.06	1980	430 ~ 2960	8.7	1.9 ~ 13.0	99
	2.5+2.5+3.5+5.0	1.39	1.39	1.94	2.78	7.50	2.83 ~ 9.33	1930	500 ~ 3060	8.5	2.2 ~ 13.4	99
	2.5+2.5+4.2+4.2	1.40	1.40	2.35	2.35	7.50	2.59 ~ 9.07	1980	430 ~ 2960	8.7	1.9 ~ 13.0	99
	2.5+3.5+3.5+3.5	1.44	2.02	2.02	2.02	7.50	2.59 ~ 9.24	1980	450 ~ 3110	8.7	2.0 ~ 13.7	99

NOTES

3D059234

1 Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).

2 The total ability of connected a indoor unit is up to 13.5kW

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2, 5.0 kW class; wall mounted G series
6.0, 7.1 kW class; wall mounted F series

4 Capacities are based on the following conditions:
Corresponding refrigerant piping length: 5m
Level difference: 0m