5MKS90E7V3B

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.0+4.2+4.2	22.0	9.11	2.74	9.53	2.80	9.95	2.85	10.16	2.88	10.78	2.96	11.20	3.01
	25.0	8.86	2.84	9.28	2.90	9.70	2.95	9.90	2.98	10.53	3.06	10.95	3.11
	32.0	8.27	3.09	8.69	3.15	9.10	3.20	9.31	3.23	9.94	3.31	10.36	3.36
	35.0	8.02	3.21	8.43	3.26	8.85	3.32	**9.06**	**3.34**	9.69	3.42	10.10	3.48
	40.0	7.59	3.42	8.01	3.47	8.43	3.52	8.64	3.55	9.26	3.63	9.68	3.68
	43.0	7.34	3.55	7.76	3.60	8.17	3.60	8.37	3.60	8.97	3.60	9.36	3.60
	46.0	7.02	3.03	7.37	3.03	7.72	3.03	7.89	3.03	8.39	3.03	8.71	3.03
2.0+2.0+4.2+5.0	22.0	9.28	2.77	9.71	2.82	10.13	2.88	10.35	2.90	10.99	2.99	11.41	3.04
	25.0	9.03	2.87	9.45	2.92	9.88	2.98	10.09	3.00	10.73	3.08	11.15	3.14
	32.0	8.42	3.12	8.85	3.18	9.28	3.23	9.49	3.26	10.13	3.34	10.55	3.39
	35.0	8.17	3.24	8.59	3.29	9.02	3.35	**9.23**	**3.37**	9.87	3.45	10.29	3.51
	40.0	7.74	3.45	8.16	3.50	8.59	3.55	8.80	3.58	9.44	3.66	9.86	3.72
	43.0	7.48	3.58	7.90	3.60	8.32	3.60	8.53	3.60	9.13	3.60	9.52	3.60
	46.0	7.13	3.03	7.49	3.03	7.84	3.03	8.01	3.03	8.51	3.03	8.84	3.03
2.0+2.0+4.2+6.0	22.0	9.73	2.82	10.17	2.87	10.62	2.93	10.84	2.96	11.51	3.04	11.95	3.09
	25.0	9.46	2.92	9.90	2.97	10.35	3.03	10.57	3.06	11.24	3.14	11.68	3.19
	32.0	8.83	3.18	9.27	3.23	9.72	3.29	9.94	3.31	10.61	3.40	11.05	3.45
	35.0	8.56	3.30	9.00	3.35	9.45	3.41	**9.67**	**3.43**	10.34	3.52	10.78	3.57
	40.0	8.11	3.51	8.55	3.56	9.00	3.62	9.22	3.64	9.89	3.73	10.32	3.75
	43.0	7.84	3.60	8.27	3.60	8.70	3.60	8.91	3.60	9.53	3.60	9.93	3.60
	46.0	7.43	3.03	7.79	3.03	8.15	3.03	8.33	3.03	8.84	3.03	9.18	3.03
2.0+2.0+4.2+7.1	22.0	10.14	3.21	10.60	3.27	11.07	3.33	11.30	3.36	12.00	3.45	12.46	3.52
	25.0	9.86	3.32	10.32	3.38	10.79	3.45	11.02	3.48	11.72	3.57	12.18	3.63
	32.0	9.20	3.61	9.67	3.68	10.13	3.74	10.36	3.77	11.06	3.86	11.52	3.92
	35.0	8.92	3.75	9.38	3.81	9.85	3.87	**10.08**	**3.90**	10.78	4.00	11.23	4.02
	40.0	8.45	3.75	8.91	3.75	9.37	3.75	9.58	3.75	10.22	3.75	10.63	3.75
	43.0	8.17	3.60	8.63	3.60	9.10	3.60	9.32	3.60	9.92	3.60	10.32	3.60
	46.0	7.86	3.03	8.22	3.03	8.57	3.03	8.74	3.03	9.25	3.03	9.58	3.03
2.0+2.0+5.0+5.0	22.0	9.46	2.79	9.89	2.84	10.32	2.89	10.54	2.92	11.19	3.00	11.62	3.06
	25.0	9.19	2.89	9.63	2.94	10.06	2.99	10.28	3.02	10.92	3.10	11.36	3.16
	32.0	8.58	3.14	9.01	3.19	9.45	3.25	9.66	3.28	10.31	3.36	10.75	3.41
	35.0	8.32	3.26	8.75	3.31	9.18	3.37	**9.40**	**3.39**	10.05	3.47	10.48	3.53
	40.0	7.88	3.47	8.31	3.52	8.75	3.57	8.96	3.60	9.61	3.68	10.04	3.74
	43.0	7.62	3.60	8.05	3.60	8.47	3.60	8.68	3.60	9.28	3.60	9.68	3.60
	46.0	7.25	3.03	7.61	3.03	7.96	3.03	8.13	3.03	8.64	3.03	8.97	3.03
2.0+2.0+5.0+6.0	22.0	10.46	3.50	10.94	3.57	11.42	3.64	11.66	3.67	12.38	3.77	12.86	3.84
	25.0	10.17	3.63	10.65	3.69	11.13	3.76	11.37	3.80	12.09	3.90	12.57	3.97
	32.0	9.49	3.95	9.97	4.01	10.45	4.08	10.69	4.12	11.40	4.18	11.86	4.18
	35.0	9.20	4.02	9.68	4.02	10.16	4.02	**10.39**	**4.02**	11.07	4.02	11.51	4.02
	40.0	8.72	3.75	9.20	3.75	9.68	3.75	9.92	3.75	10.59	3.75	11.00	3.75
	43.0	8.43	3.60	8.91	3.60	9.39	3.60	9.63	3.60	10.34	3.60	10.73	3.60
	46.0	8.14	3.03	8.62	3.03	8.98	3.03	9.15	3.03	9.65	3.03	9.98	3.03

3D059282A

NOTES

1 Capacities are based on following conditions
Corresponding refrigerant piping length : 5.0m
Level difference : 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2, 5.0 kW class; wall mounted G series
6.0, 7.1 kW class; wall mounted F, G series

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)