5MKS90E7V3B

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.0+2.5+4.2+4.2	22.0	10.15	3.21	10.61	3.27	11.08	3.33	11.31	3.36	12.01	3.45	12.47	3.52
	25.0	9.87	3.32	10.33	3.38	10.80	3.45	11.03	3.48	11.73	3.57	12.19	3.63
	32.0	9.21	3.61	9.67	3.68	10.14	3.74	10.37	3.77	11.07	3.86	11.53	3.92
	35.0	8.93	3.75	9.39	3.81	9.86	3.87	**10.09**	**3.90**	10.79	4.00	11.24	4.02
	40.0	8.46	3.75	8.92	3.75	9.38	3.75	9.59	3.75	10.23	3.75	10.64	3.75
	43.0	8.18	3.60	8.64	3.60	9.11	3.60	9.32	3.60	9.93	3.60	10.33	3.60
	46.0	7.87	3.03	8.23	3.03	8.58	3.03	8.75	3.03	9.26	3.03	9.59	3.03
2.0+2.0+3.5+3.5+3.5	22.0	9.75	2.83	10.19	2.88	10.64	2.94	10.86	2.96	11.53	3.05	11.98	3.10
	25.0	9.48	2.93	9.92	2.98	10.37	3.04	10.59	3.07	11.26	3.15	11.71	3.20
	32.0	8.84	3.19	9.29	3.24	9.74	3.30	9.96	3.32	10.63	3.41	11.08	3.46
	35.0	8.57	3.31	9.02	3.36	9.47	3.42	**9.69**	**3.44**	10.36	3.53	10.81	3.58
	40.0	8.12	3.52	8.57	3.57	9.02	3.63	9.24	3.65	9.91	3.74	10.34	3.75
	43.0	7.85	3.60	8.29	3.60	8.72	3.60	8.93	3.60	9.55	3.60	9.95	3.60
	46.0	7.44	3.03	7.81	3.03	8.16	3.03	8.34	3.03	8.86	3.03	9.20	3.03
2.0+2.0+3.5+3.5+4.2	22.0	10.14	3.21	10.60	3.27	11.07	3.33	11.30	3.36	12.00	3.45	12.46	3.52
	25.0	9.86	3.32	10.32	3.38	10.79	3.45	11.02	3.48	11.72	3.57	12.18	3.63
	32.0	9.20	3.61	9.67	3.68	10.13	3.74	10.36	3.77	11.06	3.86	11.52	3.92
	35.0	8.92	3.75	9.38	3.81	9.85	3.87	**10.08**	**3.90**	10.78	4.00	11.23	4.02
	40.0	8.45	3.75	8.91	3.75	9.37	3.75	9.58	3.75	10.22	3.75	10.63	3.75
	43.0	8.17	3.60	8.63	3.60	9.10	3.60	9.32	3.60	9.92	3.60	10.32	3.60
	46.0	7.86	3.03	8.22	3.03	8.57	3.03	8.74	3.03	9.25	3.03	9.58	3.03
2.0+2.5+2.5+2.5+2.5	22.0	9.73	2.82	10.17	2.87	10.62	2.93	10.84	2.96	11.51	3.04	11.95	3.09
	25.0	9.46	2.92	9.90	2.97	10.35	3.03	10.57	3.06	11.24	3.14	11.68	3.19
	32.0	8.83	3.18	9.27	3.23	9.72	3.29	9.94	3.31	10.61	3.40	11.05	3.45
	35.0	8.56	3.30	9.00	3.35	9.45	3.41	**9.67**	**3.43**	10.34	3.52	10.78	3.57
	40.0	8.11	3.51	8.55	3.56	9.00	3.62	9.22	3.64	9.89	3.73	10.32	3.75
	43.0	7.84	3.60	8.27	3.60	8.70	3.60	8.91	3.60	9.53	3.60	9.93	3.60
	46.0	7.43	3.03	7.79	3.03	8.15	3.03	8.33	3.03	8.84	3.03	9.18	3.03
2.0+2.5+2.5+2.5+3.5	22.0	9.73	2.82	10.17	2.87	10.62	2.93	10.84	2.96	11.51	3.04	11.95	3.09
	25.0	9.46	2.92	9.90	2.97	10.35	3.03	10.57	3.06	11.24	3.14	11.68	3.19
	32.0	8.83	3.18	9.27	3.23	9.72	3.29	9.94	3.31	10.61	3.40	11.05	3.45
	35.0	8.56	3.30	9.00	3.35	9.45	3.41	**9.67**	**3.43**	10.34	3.52	10.78	3.57
	40.0	8.11	3.51	8.55	3.56	9.00	3.62	9.22	3.64	9.89	3.73	10.32	3.75
	43.0	7.84	3.60	8.27	3.60	8.70	3.60	8.91	3.60	9.53	3.60	9.93	3.60
	46.0	7.43	3.03	7.79	3.03	8.15	3.03	8.33	3.03	8.84	3.03	9.18	3.03
2.0+2.5+2.5+2.5+4.2	22.0	9.74	2.83	10.18	2.88	10.63	2.94	10.85	2.96	11.52	3.05	11.97	3.10
	25.0	9.47	2.93	9.91	2.98	10.36	3.04	10.58	3.07	11.25	3.15	11.70	3.20
	32.0	8.84	3.19	9.28	3.24	9.73	3.30	9.95	3.32	10.62	3.41	11.07	3.46
	35.0	8.57	3.31	9.01	3.36	9.46	3.42	**9.68**	**3.44**	10.35	3.53	10.79	3.58
	40.0	8.11	3.52	8.56	3.57	9.01	3.63	9.23	3.65	9.90	3.74	10.33	3.75
	43.0	7.84	3.60	8.28	3.60	8.71	3.60	8.92	3.60	9.54	3.60	9.94	3.60
	46.0	7.44	3.03	7.80	3.03	8.16	3.03	8.33	3.03	8.85	3.03	9.19	3.03

3D059289A

NOTES

1 Capacities are based on following conditions
Corresponding refrigerant piping length : 5.0m
Level difference : 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2, 5.0 kW class; wall mounted G series
6.0, 7.1 kW class; wall mounted F, G series

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)