5MKS90E7V3B

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.0+2.0+2.0+2.0	22.0	8.01	1.99	8.37	2.03	8.74	2.07	8.92	2.09	9.47	2.14	9.84	2.18
	25.0	7.78	2.06	8.15	2.10	8.52	2.14	8.70	2.16	9.25	2.22	9.62	2.25
	32.0	7.27	2.24	7.63	2.28	8.00	2.32	8.18	2.34	8.73	2.40	9.10	2.44
	35.0	7.04	2.33	7.41	2.36	7.78	2.40	**7.96**	**2.42**	8.51	2.48	8.88	2.52
	40.0	6.67	2.47	7.04	2.51	7.41	2.55	7.59	2.57	8.14	2.63	8.51	2.67
	43.0	6.45	2.57	6.82	2.61	7.18	2.65	7.37	2.67	7.92	2.72	8.28	2.76
	46.0	6.23	2.67	6.59	2.71	6.96	2.74	7.14	2.76	7.69	2.82	8.06	2.86
2.0+2.0+2.0+2.5	22.0	8.30	2.14	8.68	2.19	9.06	2.23	9.25	2.25	9.82	2.31	10.20	2.35
	25.0	8.07	2.22	8.45	2.26	8.83	2.31	9.02	2.33	9.59	2.39	9.97	2.43
	32.0	7.53	2.42	7.91	2.46	8.29	2.50	8.48	2.52	9.05	2.58	9.43	2.63
	35.0	7.30	2.51	7.68	2.55	8.06	2.59	**8.25**	**2.61**	8.82	2.68	9.20	2.72
	40.0	6.92	2.67	7.30	2.71	7.68	2.75	7.87	2.77	8.44	2.84	8.82	2.88
	43.0	6.69	2.77	7.07	2.81	7.45	2.85	7.64	2.87	8.21	2.94	8.59	2.98
	46.0	6.45	2.88	6.83	2.92	7.21	2.96	7.40	2.98	7.97	3.03	8.31	3.03
2.0+2.0+2.0+3.5	22.0	8.83	2.46	9.24	2.51	9.64	2.55	9.84	2.58	10.45	2.65	10.85	2.70
	25.0	8.59	2.55	8.99	2.59	9.40	2.64	9.60	2.67	10.20	2.74	10.61	2.78
	32.0	8.01	2.77	8.42	2.82	8.82	2.87	9.03	2.89	9.63	2.96	10.04	3.01
	35.0	7.77	2.87	8.17	2.92	8.58	2.97	**8.78**	**2.99**	9.39	3.06	9.79	3.11
	40.0	7.36	3.06	7.76	3.11	8.17	3.15	8.37	3.18	8.98	3.25	9.38	3.30
	43.0	7.11	3.17	7.52	3.22	7.92	3.27	8.13	3.29	8.73	3.36	9.14	3.41
	46.0	6.80	3.03	7.16	3.03	7.52	3.03	7.69	3.03	8.21	3.03	8.54	3.03
2.0+2.0+2.0+4.2	22.0	9.17	2.63	9.59	2.68	10.01	2.73	10.22	2.76	10.85	2.83	11.27	2.89
	25.0	8.92	2.72	9.34	2.78	9.76	2.83	9.97	2.85	10.60	2.93	11.02	2.98
	32.0	8.32	2.96	8.74	3.02	9.16	3.07	9.37	3.09	10.01	3.17	10.43	3.22
	35.0	8.07	3.08	8.49	3.13	8.91	3.18	**9.12**	**3.20**	9.75	3.28	10.17	3.33
	40.0	7.64	3.27	8.07	3.32	8.49	3.37	8.70	3.40	9.33	3.48	9.75	3.53
	43.0	7.39	3.40	7.81	3.45	8.23	3.50	8.44	3.52	9.07	3.60	9.47	3.60
	46.0	7.03	3.03	7.39	3.03	7.75	3.03	7.92	3.03	8.43	3.03	8.77	3.03
2.0+2.0+2.0+5.0	22.0	9.08	2.65	9.50	2.70	9.92	2.75	10.12	2.78	10.75	2.85	11.16	2.90
	25.0	8.83	2.74	9.25	2.79	9.66	2.84	9.87	2.87	10.49	2.95	10.91	3.00
	32.0	8.24	2.98	8.66	3.03	9.07	3.09	9.28	3.11	9.91	3.19	10.32	3.24
	35.0	7.99	3.09	8.41	3.15	8.82	3.20	**9.03**	**3.22**	9.65	3.30	10.07	3.35
	40.0	7.57	3.29	7.99	3.34	8.40	3.40	8.61	3.42	9.23	3.50	9.65	3.55
	43.0	7.32	3.42	7.73	3.47	8.15	3.52	8.36	3.55	8.97	3.60	9.37	3.60
	46.0	6.97	3.03	7.33	3.03	7.68	3.03	7.85	3.03	8.36	3.03	8.69	3.03
2.0+2.0+2.0+6.0	22.0	9.71	2.82	10.15	2.87	10.60	2.93	10.82	2.96	11.49	3.04	11.93	3.09
	25.0	9.44	2.92	9.88	2.97	10.33	3.03	10.55	3.06	11.22	3.14	11.66	3.19
	32.0	8.81	3.18	9.25	3.23	9.70	3.29	9.92	3.31	10.59	3.40	11.03	3.45
	35.0	8.54	3.30	8.98	3.35	9.43	3.41	**9.65**	**3.43**	10.32	3.52	10.76	3.57
	40.0	8.09	3.51	8.53	3.56	8.98	3.62	9.20	3.64	9.87	3.73	10.30	3.75
	43.0	7.82	3.60	8.26	3.60	8.68	3.60	8.89	3.60	9.51	3.60	9.91	3.60
	46.0	7.41	3.03	7.78	3.03	8.14	3.03	8.31	3.03	8.83	3.03	9.17	3.03

3D059280A

NOTES

1 Capacities are based on following conditions
Corresponding refrigerant piping length : 5.0m
Level difference : 0m

2 The bold line ☐ is indicated the standard condition.

3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5, 4.2, 5.0 kW class; wall mounted G series
6.0, 7.1 kW class; wall mounted F, G series

SYMBOLS

TC : Total cooling capacity (kW)
PI : Power input (kW)