5MKS90E

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.5+3.5+6.0	22.0	9.07	2.74	9.49	2.79	9.90	2.84	10.11	2.87	10.74	2.95	11.15	3.00
	25.0	8.82	2.83	9.24	2.89	9.65	2.94	9.86	2.97	10.48	3.05	10.90	3.10
	32.0	8.23	3.08	8.65	3.14	9.06	3.19	9.27	3.22	9.90	3.30	10.31	3.35
	35.0	7.98	3.20	8.40	3.25	8.81	3.31	9.02	3.33	9.64	3.41	10.06	3.47
	40.0	7.56	3.40	7.98	3.46	8.39	3.51	8.60	3.54	9.22	3.62	9.64	3.67
	43.0	7.31	3.53	7.72	3.59	8.14	3.60	8.34	3.60	8.93	3.60	9.32	3.60
	46.0	6.99	3.03	7.34	3.03	7.69	3.03	7.86	3.03	8.35	3.03	8.68	3.03
2.5+3.5+7.1	22.0	9.09	2.79	9.51	2.84	9.93	2.89	10.13	2.92	10.76	3.00	11.18	3.06
	25.0	8.84	2.89	9.26	2.94	9.67	2.99	9.88	3.02	10.51	3.10	10.92	3.16
	32.0	8.25	3.14	8.67	3.19	9.08	3.25	9.29	3.28	9.92	3.36	10.33	3.41
	35.0	8.00	3.26	8.42	3.31	8.83	3.37	9.04	3.39	9.66	3.47	10.08	3.53
	40.0	7.58	3.47	7.99	3.52	8.41	3.57	8.62	3.60	9.24	3.68	9.66	3.74
	43.0	7.33	3.60	7.74	3.60	8.15	3.60	8.35	3.60	8.95	3.60	9.33	3.60
	46.0	7.02	3.03	7.37	3.03	7.71	3.03	7.88	3.03	8.38	3.03	8.70	3.03
2.5+5.0+5.0	22.0	9.10	2.95	9.52	3.01	9.94	3.07	10.15	3.09	10.77	3.18	11.19	3.24
	25.0	8.85	3.06	9.27	3.11	9.68	3.17	9.89	3.20	10.52	3.29	10.94	3.34
	32.0	8.26	3.33	8.68	3.38	9.09	3.44	9.30	3.47	9.93	3.56	10.35	3.61
	35.0	8.01	3.45	8.42	3.51	8.84	3.57	9.05	3.59	9.68	3.68	10.09	3.74
	40.0	7.59	3.67	8.00	3.73	8.42	3.75	8.63	3.75	9.24	3.75	9.63	3.75
	43.0	7.33	3.60	7.75	3.60	8.17	3.60	8.38	3.60	8.97	3.60	9.35	3.60
	46.0	7.08	3.03	7.45	3.03	7.78	3.03	7.95	3.03	8.43	3.03	8.75	3.03
2.5+5.0+6.0	22.0	9.25	2.76	9.68	2.82	10.10	2.87	10.31	2.90	10.95	2.98	11.37	3.03
	25.0	9.00	2.86	9.42	2.91	9.84	2.97	10.06	2.99	10.69	3.08	11.12	3.13
	32.0	8.40	3.11	8.82	3.17	9.25	3.22	9.46	3.25	10.09	3.33	10.52	3.38
	35.0	8.14	3.23	8.56	3.28	8.99	3.34	9.20	3.36	9.84	3.44	10.26	3.50
	40.0	7.71	3.44	8.14	3.49	8.56	3.54	8.77	3.57	9.41	3.65	9.83	3.70
	43.0	7.45	3.57	7.88	3.60	8.29	3.60	8.50	3.60	9.10	3.60	9.49	3.60
	46.0	7.11	3.03	7.47	3.03	7.82	3.03	7.99	3.03	8.49	3.03	8.82	3.03
2.5+5.0+7.1	22.0	9.27	2.76	9.70	2.82	10.12	2.87	10.34	2.90	10.97	2.98	11.40	3.03
	25.0	9.02	2.86	9.44	2.91	9.87	2.97	10.08	2.99	10.72	3.08	11.14	3.13
	32.0	8.42	3.11	8.84	3.17	9.27	3.22	9.48	3.25	10.11	3.33	10.54	3.38
	35.0	8.16	3.23	8.58	3.28	9.01	3.34	9.22	3.36	9.86	3.44	10.28	3.50
	40.0	7.73	3.44	8.15	3.49	8.58	3.54	8.79	3.57	9.43	3.65	9.85	3.70
	43.0	7.47	3.57	7.90	3.60	8.31	3.60	8.52	3.60	9.12	3.60	9.51	3.60
	46.0	7.13	3.03	7.48	3.03	7.83	3.03	8.00	3.03	8.51	3.03	8.84	3.03
2.5+6.0+6.0	22.0	9.70	2.82	10.14	2.87	10.58	2.93	10.81	2.96	11.47	3.04	11.92	3.09
	25.0	9.43	2.92	9.87	2.97	10.32	3.03	10.54	3.06	11.20	3.14	11.65	3.19
	32.0	8.80	3.18	9.24	3.23	9.69	3.29	9.91	3.31	10.58	3.40	11.02	3.45
	35.0	8.53	3.30	8.97	3.35	9.42	3.41	9.64	3.43	10.31	3.52	10.75	3.57
	40.0	8.08	3.51	8.52	3.56	8.97	3.62	9.19	3.64	9.86	3.73	10.29	3.75
	43.0	7.81	3.60	8.25	3.60	8.67	3.60	8.88	3.60	9.50	3.60	9.90	3.60
	46.0	7.41	3.03	7.77	3.03	8.13	3.03	8.31	3.03	8.82	3.03	9.16	3.03

3D052453-5A

SYMBOLS

TC : Total capacity (kW)
PI : Power input (kW)

NOTES

Capacities are based on following conditions
Corresponding refrigerant piping length: 7.5 m
Level difference: 0 m

The above is the value for connecting with the following indoor units.
2.0 kW class; FTXS20D3VMW/L
2.5 kW class; FTXS25D3VMW/L
3.5 kW class; FTXS35D3VMW/L
5.0 kW class; FTXS50D2V1W/L
6.0 kW class; FTXS60EV1B
7.1 kW class; FTXS71EV1B