5MKS90E

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.5+2.5+3.5+5.0	22.0	9.27	2.76	9.70	2.82	10.12	2.87	10.34	2.90	10.97	2.98	11.40	3.03
	25.0	9.02	2.86	9.44	2.91	9.87	2.97	10.08	2.99	10.72	3.08	11.14	3.13
	32.0	8.42	3.11	8.84	3.17	9.27	3.22	9.48	3.25	10.11	3.33	10.54	3.38
	35.0	8.16	3.23	8.58	3.28	9.01	3.34	9.22	3.36	9.86	3.44	10.28	3.50
	40.0	7.73	3.44	8.15	3.49	8.58	3.54	8.79	3.57	9.43	3.65	9.85	3.70
	43.0	7.47	3.57	7.90	3.60	8.31	3.60	8.52	3.60	9.12	3.60	9.51	3.60
	46.0	7.13	3.03	7.48	3.03	7.83	3.03	8.00	3.03	8.51	3.03	8.84	3.03
2.5+2.5+3.5+6.0	22.0	9.72	2.82	10.16	2.87	10.61	2.93	10.83	2.96	11.50	3.04	11.94	3.09
	25.0	9.45	2.92	9.89	2.97	10.34	3.03	10.56	3.06	11.23	3.14	11.67	3.19
	32.0	8.82	3.18	9.26	3.23	9.71	3.29	9.93	3.31	10.60	3.40	11.04	3.45
	35.0	8.55	3.30	8.99	3.35	9.44	3.41	9.66	3.43	10.33	3.52	10.77	3.57
	40.0	8.10	3.51	8.54	3.56	8.99	3.62	9.21	3.64	9.88	3.73	10.31	3.75
	43.0	7.83	3.60	8.26	3.60	8.69	3.60	8.90	3.60	9.52	3.60	9.92	3.60
	46.0	7.42	3.03	7.79	3.03	8.14	3.03	8.32	3.03	8.84	3.03	9.17	3.03
2.5+2.5+3.5+7.1	22.0	10.18	3.27	10.65	3.33	11.11	3.40	11.35	3.43	12.04	3.53	12.51	3.59
	25.0	9.90	3.39	10.36	3.45	10.83	3.52	11.06	3.55	11.76	3.64	12.23	3.71
	32.0	9.24	3.69	9.70	3.75	10.17	3.81	10.40	3.85	11.10	3.94	11.57	4.01
	35.0	8.95	3.83	9.42	3.89	9.89	3.95	10.12	3.98	10.80	4.02	11.25	4.02
	40.0	8.48	3.75	8.95	3.75	9.42	3.75	9.63	3.75	10.27	3.75	10.68	3.75
	43.0	8.20	3.60	8.67	3.60	9.13	3.60	9.37	3.60	9.98	3.60	10.38	3.60
	46.0	7.92	3.03	8.29	3.03	8.64	3.03	8.81	3.03	9.31	3.03	9.64	3.03
2.5+2.5+5.0+5.0	22.0	10.01	3.41	10.47	3.48	10.93	3.54	11.15	3.58	11.84	3.68	12.30	3.74
	25.0	9.73	3.53	10.19	3.60	10.65	3.67	10.88	3.70	11.56	3.80	12.02	3.87
	32.0	9.08	3.84	9.54	3.91	10.00	3.98	10.23	4.01	10.92	4.11	11.37	4.18
	35.0	8.80	3.99	9.26	4.02	9.72	4.02	9.95	4.02	10.62	4.02	11.05	4.02
	40.0	8.34	3.75	8.80	3.75	9.26	3.75	9.49	3.75	10.17	3.75	10.57	3.75
	43.0	8.06	3.60	8.52	3.60	8.98	3.60	9.21	3.60	9.90	3.60	10.32	3.60
	46.0	7.78	3.03	8.24	3.03	8.65	3.03	8.81	3.03	9.31	3.03	9.63	3.03
2.5+3.5+3.5+3.5	22.0	9.12	2.79	9.54	2.84	9.96	2.89	10.17	2.92	10.79	3.00	11.21	3.06
	25.0	8.87	2.89	9.29	2.94	9.71	2.99	9.91	3.02	10.54	3.10	10.96	3.16
	32.0	8.28	3.14	8.70	3.19	9.11	3.25	9.32	3.28	9.95	3.36	10.37	3.41
	35.0	8.03	3.26	8.44	3.31	8.86	3.37	9.07	3.39	9.70	3.47	10.11	3.53
	40.0	7.60	3.47	8.02	3.52	8.44	3.57	8.65	3.60	9.27	3.68	9.69	3.74
	43.0	7.35	3.60	7.77	3.60	8.18	3.60	8.38	3.60	8.97	3.60	9.36	3.60
	46.0	7.04	3.03	7.39	3.03	7.73	3.03	7.90	3.03	8.40	3.03	8.72	3.03
2.5+3.5+3.5+5.0	22.0	9.27	2.77	9.70	2.82	10.12	2.88	10.34	2.90	10.97	2.99	11.40	3.04
	25.0	9.02	2.87	9.44	2.92	9.87	2.98	10.08	3.00	10.72	3.08	11.14	3.14
	32.0	8.42	3.12	8.84	3.18	9.27	3.23	9.48	3.26	10.11	3.34	10.54	3.39
	35.0	8.16	3.24	8.58	3.29	9.01	3.35	9.22	3.37	9.86	3.45	10.28	3.51
	40.0	7.73	3.45	8.15	3.50	8.58	3.55	8.79	3.58	9.43	3.66	9.85	3.72
	43.0	7.47	3.58	7.90	3.60	8.31	3.60	8.52	3.60	9.12	3.60	9.51	3.60
	46.0	7.13	3.03	7.48	3.03	7.83	3.03	8.00	3.03	8.51	3.03	8.84	3.03

3D052454-1A

SYMBOLS

TC : Total capacity (kW)
PI : Power input (kW)

NOTES

Capacities are based on following conditions
Corresponding refrigerant piping length: 7.5 m
Level difference: 0 m

The above is the value for connecting with the following indoor units.
2.0 kW class; FTXS20D3VMW/L 2.5 kW class; FTXS25D3VMW/L
3.5 kW class; FTXS35D3VMW/L 5.0 kW class; FTXS50D2V1W/L
6.0 kW class; FTXS60EV1B 7.1 kW class; FTXS71EV1B