5MKS90E

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+2.0+5.0	22.0	8.58	2.46	8.97	2.51	9.37	2.55	9.56	2.58	10.15	2.65	10.55	2.70
	25.0	8.34	2.55	8.73	2.59	9.13	2.64	9.32	2.67	9.91	2.74	10.31	2.78
	32.0	7.79	2.77	8.18	2.82	8.57	2.87	8.77	2.89	9.36	2.96	9.75	3.01
	35.0	7.55	2.87	7.94	2.92	8.33	2.97	8.53	2.99	9.12	3.06	9.51	3.11
	40.0	7.15	3.06	7.54	3.11	7.94	3.15	8.13	3.18	8.72	3.25	9.12	3.30
	43.0	6.91	3.17	7.31	3.22	7.70	3.27	7.89	3.29	8.48	3.36	8.88	3.41
	46.0	6.62	3.03	6.97	3.03	7.32	3.03	7.49	3.03	8.00	3.03	8.32	3.03
2.0+2.0+6.0	22.0	8.89	2.62	9.30	2.67	9.71	2.72	9.91	2.75	10.52	2.83	10.93	2.88
	25.0	8.65	2.72	9.05	2.77	9.46	2.82	9.66	2.84	10.27	2.92	10.68	2.97
	32.0	8.07	2.95	8.48	3.01	8.88	3.06	9.09	3.08	9.70	3.16	10.11	3.21
	35.0	7.82	3.07	8.23	3.12	8.64	3.17	8.84	3.19	9.45	3.27	9.86	3.32
	40.0	7.41	3.26	7.82	3.31	8.22	3.36	8.43	3.39	9.04	3.47	9.45	3.52
	43.0	7.16	3.39	7.57	3.44	7.98	3.49	8.18	3.51	8.79	3.59	9.18	3.60
	46.0	6.84	3.03	7.20	3.03	7.54	3.03	7.71	3.03	8.21	3.03	8.54	3.03
2.0+2.0+7.1	22.0	9.08	2.74	9.50	2.80	9.92	2.85	10.12	2.88	10.75	2.96	11.16	3.01
	25.0	8.83	2.84	9.25	2.90	9.66	2.95	9.87	2.98	10.49	3.06	10.91	3.11
	32.0	8.24	3.09	8.66	3.15	9.07	3.20	9.28	3.23	9.91	3.31	10.32	3.36
	35.0	7.99	3.21	8.41	3.26	8.82	3.32	9.03	3.34	9.65	3.42	10.07	3.48
	40.0	7.57	3.42	7.99	3.47	8.40	3.52	8.61	3.55	9.23	3.63	9.65	3.68
	43.0	7.32	3.55	7.73	3.60	8.14	3.60	8.35	3.60	8.94	3.60	9.33	3.60
	46.0	7.00	3.03	7.35	3.03	7.69	3.03	7.86	3.03	8.36	3.03	8.69	3.03
2.0+2.5+2.5	22.0	7.35	2.05	7.69	2.09	8.03	2.13	8.19	2.15	8.70	2.21	9.04	2.25
	25.0	7.15	2.12	7.49	2.16	7.82	2.20	7.99	2.22	8.50	2.28	8.83	2.32
	32.0	6.67	2.31	7.01	2.35	7.35	2.39	7.51	2.41	8.02	2.47	8.36	2.51
	35.0	6.47	2.39	6.80	2.43	7.14	2.47	7.31	2.49	7.82	2.55	8.15	2.59
	40.0	6.13	2.55	6.46	2.59	6.80	2.63	6.97	2.65	7.47	2.71	7.81	2.75
	43.0	5.92	2.64	6.26	2.68	6.60	2.72	6.77	2.74	7.27	2.80	7.61	2.84
	46.0	5.72	2.74	6.06	2.78	6.39	2.82	6.56	2.84	7.07	2.90	7.40	2.94
2.0+2.5+3.5	22.0	8.01	2.39	8.37	2.44	8.74	2.48	8.92	2.51	9.47	2.58	9.84	2.62
	25.0	7.78	2.48	8.15	2.52	8.52	2.57	8.70	2.59	9.25	2.66	9.62	2.71
	32.0	7.27	2.70	7.63	2.74	8.00	2.79	8.18	2.81	8.73	2.88	9.10	2.93
	35.0	7.04	2.80	7.41	2.84	7.78	2.89	7.96	2.91	8.51	2.98	8.88	3.03
	40.0	6.67	2.98	7.04	3.02	7.41	3.07	7.59	3.09	8.14	3.16	8.51	3.21
	43.0	6.45	3.09	6.82	3.14	7.18	3.18	7.37	3.21	7.92	3.27	8.28	3.32
	46.0	6.21	3.03	6.55	3.03	6.88	3.03	7.05	3.03	7.53	3.03	7.85	3.03
2.0+2.5+5.0	22.0	8.83	2.62	9.24	2.67	9.64	2.72	9.84	2.75	10.45	2.83	10.85	2.88
	25.0	8.59	2.72	8.99	2.77	9.40	2.82	9.60	2.84	10.20	2.92	10.61	2.97
	32.0	8.01	2.95	8.42	3.01	8.82	3.06	9.03	3.08	9.63	3.16	10.04	3.21
	35.0	7.77	3.07	8.17	3.12	8.58	3.17	8.78	3.19	9.39	3.27	9.79	3.32
	40.0	7.36	3.26	7.76	3.31	8.17	3.36	8.37	3.39	8.98	3.47	9.38	3.52
	43.0	7.11	3.39	7.52	3.44	7.92	3.49	8.13	3.51	8.73	3.59	9.12	3.60
	46.0	6.80	3.03	7.15	3.03	7.50	3.03	7.67	3.03	8.17	3.03	8.49	3.03

3D052449-3A

SYMBOLS

TC : Total capacity (kW)
PI : Power input (kW)

NOTES

Capacities are based on following conditions
Corresponding refrigerant piping length: 7.5 m
Level difference: 0 m

The above is the value for connecting with the following indoor units.
2.0 kW class; FTXS20D3VMW/L 2.5 kW class; FTXS25D3VMW/L
3.5 kW class; FTXS35D3VMW/L 5.0 kW class; FTXS50EV1B
6.0 kW class; FTXS60EV1B 7.1 kW class; FTXS71EV1B