5MKS90E

Cooling [50Hz 230V]

Combination (Capacity)	Outdoor air temp. °CDB	Indoor air temp.: °CWB											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
2.0+5.0+5.0	22.0	9.63	2.81	10.07	2.87	10.51	2.92	10.73	2.95	11.39	3.03	11.83	3.08
	25.0	9.36	2.91	9.80	2.97	10.24	3.02	10.46	3.05	11.12	3.13	11.56	3.19
	32.0	8.74	3.17	9.18	3.22	9.62	3.28	9.84	3.30	10.50	3.39	10.94	3.44
	35.0	8.47	3.29	8.91	3.34	9.35	3.40	9.57	3.42	10.23	3.51	10.67	3.56
	40.0	8.02	3.50	8.46	3.55	8.90	3.61	9.12	3.63	9.79	3.72	10.22	3.75
	43.0	7.75	3.60	8.19	3.60	8.61	3.60	8.82	3.60	9.44	3.60	9.84	3.60
	46.0	7.36	3.03	7.72	3.03	8.08	3.03	8.26	3.03	8.77	3.03	9.10	3.03
2.0+5.0+6.0	22.0	9.67	2.81	10.11	2.87	10.55	2.92	10.77	2.95	11.44	3.03	11.88	3.08
	25.0	9.40	2.91	9.84	2.97	10.28	3.02	10.50	3.05	11.17	3.13	11.61	3.19
	32.0	8.77	3.17	9.21	3.22	9.66	3.28	9.88	3.30	10.54	3.39	10.99	3.44
	35.0	8.50	3.29	8.95	3.34	9.39	3.40	9.61	3.42	10.27	3.51	10.72	3.56
	40.0	8.06	3.50	8.50	3.55	8.94	3.61	9.16	3.63	9.83	3.72	10.26	3.75
	43.0	7.79	3.60	8.22	3.60	8.65	3.60	8.86	3.60	9.47	3.60	9.88	3.60
	46.0	7.39	3.03	7.75	3.03	8.11	3.03	8.28	3.03	8.80	3.03	9.14	3.03
2.0+5.0+7.1	22.0	9.69	2.82	10.13	2.87	10.57	2.93	10.80	2.96	11.46	3.04	11.91	3.09
	25.0	9.42	2.92	9.86	2.97	10.30	3.03	10.53	3.06	11.19	3.14	11.64	3.19
	32.0	8.79	3.18	9.23	3.23	9.68	3.29	9.90	3.31	10.56	3.40	11.01	3.45
	35.0	8.52	3.30	8.96	3.35	9.41	3.41	9.63	3.43	10.30	3.52	10.74	3.57
	40.0	8.07	3.51	8.52	3.56	8.96	3.62	9.18	3.64	9.85	3.73	10.28	3.75
	43.0	7.80	3.60	8.24	3.60	8.67	3.60	8.88	3.60	9.49	3.60	9.89	3.60
	46.0	7.40	3.03	7.77	3.03	8.12	3.03	8.30	3.03	8.81	3.03	9.15	3.03
2.0+6.0+6.0	22.0	9.70	2.82	10.14	2.87	10.58	2.93	10.81	2.96	11.47	3.04	11.92	3.09
	25.0	9.43	2.92	9.87	2.97	10.32	3.03	10.54	3.06	11.20	3.14	11.65	3.19
	32.0	8.80	3.18	9.24	3.23	9.69	3.29	9.91	3.31	10.58	3.40	11.02	3.45
	35.0	8.53	3.30	8.97	3.35	9.42	3.41	9.64	3.43	10.31	3.52	10.75	3.57
	40.0	8.08	3.51	8.52	3.56	8.97	3.62	9.19	3.64	9.86	3.73	10.29	3.75
	43.0	7.81	3.60	8.25	3.60	8.67	3.60	8.88	3.60	9.50	3.60	9.90	3.60
	46.0	7.41	3.03	7.77	3.03	8.13	3.03	8.31	3.03	8.82	3.03	9.16	3.03
2.0+6.0+7.1	22.0	10.16	3.26	10.62	3.33	11.09	3.39	11.32	3.42	12.02	3.52	12.49	3.58
	25.0	9.88	3.38	10.34	3.44	10.81	3.51	11.04	3.54	11.74	3.63	12.20	3.70
	32.0	9.22	3.68	9.68	3.74	10.15	3.80	10.38	3.84	11.08	3.93	11.55	4.00
	35.0	8.94	3.82	9.40	3.88	9.87	3.94	10.10	3.97	10.79	4.02	11.23	4.02
	40.0	8.47	3.75	8.93	3.75	9.40	3.75	9.61	3.75	10.25	3.75	10.66	3.75
	43.0	8.18	3.60	8.65	3.60	9.11	3.60	9.35	3.60	9.96	3.60	10.36	3.60
	46.0	7.90	3.03	8.27	3.03	8.62	3.03	8.79	3.03	9.30	3.03	9.63	3.03
2.5+2.5+2.5	22.0	7.68	2.24	8.04	2.29	8.39	2.33	8.56	2.35	9.09	2.42	9.44	2.46
	25.0	7.47	2.32	7.82	2.37	8.18	2.41	8.35	2.43	8.88	2.50	9.23	2.54
	32.0	6.97	2.53	7.33	2.57	7.68	2.62	7.85	2.64	8.38	2.70	8.73	2.75
	35.0	6.76	2.62	7.11	2.67	7.46	2.71	7.64	2.73	8.17	2.80	8.52	2.84
	40.0	6.40	2.79	6.76	2.84	7.11	2.88	7.28	2.90	7.81	2.97	8.16	3.01
	43.0	6.19	2.90	6.54	2.94	6.89	2.98	7.07	3.01	7.60	3.07	7.95	3.12
	46.0	5.98	3.01	6.32	3.03	6.66	3.03	6.82	3.03	7.31	3.03	7.62	3.03

3D052449-4A

SYMBOLS

TC : Total capacity (kW)
PI : Power input (kW)

NOTES

Capacities are based on following conditions
Corresponding refrigerant piping length: 7.5 m
Level difference: 0 m

The above is the value for connecting with the following indoor units.
2.0 kW class; FTXS20D3VMW/L 2.5 kW class; FTXS25D3VMW/L
3.5 kW class; FTXS35D3VMW/L 5.0 kW class; FTXS50EV1B
6.0 kW class; FTXS60EV1B 7.1 kW class; FTXS71EV1B