

RXLG25-35K

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXG25JV1BW FTXG25JV1BA	RXLG25K2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	46	2.8	23	0.23	40	0.15
		50 - 230					2.6				
		50 - 240					2.5				
FTXG35JV1BW FTXG35JV1BA	RXLG35K2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	68	4.7	23	0.23	40	0.15
		50 - 230					4.4				
		50 - 240					4.2				

3D066215A

SYMBOLS

MCA : Min. Circuit Amps (A)
MFA : Max. Fuse Amps (A)
RHz : Rated operating frequency (Hz)
RLA : Rated Load Amps (A)
OFM : Outdoor Fan Motor
IFM : Indoor Fan Motor
FLA : Full Load Amps (A)
W : Fan Motor Rated Output (W)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19.0°CWB
Outdoor temp.: 35°CDB.
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use Circuit Breaker.