

RKS60F3

RXS60F3

Representative unit combination		Power supply				Comp		OFM		IFM	
Indoor unit	Outdoor unit	Hz-Volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FCQ60C8VEB	RKS60F3V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20.0	73	7.4	53	0.19	56	0.40
		50 - 230					7.1				
		50 - 240					6.8				
FCQ60C8VEB	RXS60F3V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20.0	73	7.4	53	0.19	56	0.40
		50 - 230					7.1				
		50 - 240					6.8				

SYMBOLS

MCA : Min. Circuit Amps. (A)
 MFA : Max. Fuse Amps. (A)
 RLA : Rated Load Amps. (A)
 OFM : Outdoor Fan Motor
 IFM : Indoor Fan Motor
 FLA : Full Load Amps. (A)
 W : Fan Motor Rated Output (W)
 RHz : Rated Operating frequency (Hz)

NOTES

- RLA is based on the following conditions.
 - Indoor temp. 27°C DB/19.0°C WB.
 - Outdoor temp. 35°C DB.
- Maximum allowable voltage variation between phases is 2%.
- Select wire size based on the larger value of MCA.
- Instead of fuse, use circuit breaker.