

RXL25J

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXS25J2V1B	RXL25J2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	10	45	2.6	23	0.23	23	0.15
		50 - 230					2.4				
		50 - 240					2.3				
FVXS25FV1B	RXL25J2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	10	46	3.0	23	0.23	48	0.05
		50 - 230					2.8				
		50 - 240					2.7				

3D070944

SYMBOLS

MCA	: Min. Circuit Amps (A)
MFA	: Max. Fuse Amps (A)
RHz	: Rated operating frequency (Hz)
RLA	: Rated Load Amps (A)
OFM	: Outdoor Fan Motor
IFM	: Indoor Fan Motor
FLA	: Full Load Amps (A)
W	: Rated motor output (W) (W)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19.0°CWB
Outdoor temp. : 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use Circuit Breaker.