

RXL35J

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXS35J2V1B	RXL35J2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	10	65	3.9	23	0.23	23	0.15
		50 - 230					3.7				
		50 - 240					3.5				
FVXS35FV1B	RXL35J2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	10	66	4.8	23	0.23	48	0.05
		50 - 230					4.6				
		50 - 240					4.4				

3D070943A

SYMBOLS

MCA	: Min. Circuit Amps. (A)
MFA	: Max. Fuse Amps (A)
RLA	: Rated Load Amps. (A)
OFM	: Outdoor Fan Motor.
IFM	: Indoor Fan Motor.
FLA	: Full Load Amps. (A)
W	: Fan Motor Rated Output (W)
RHz	: Rated operating frequency (Hz)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19°CWB
Outdoor temp.: 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.