


Field wiring



C5,C6,C19 : Capacitor
 DB1,DB2,DB3 : Diode bridge
 E1H : Heater
 FU1,FU2,FU3,FU4,FU5 : Fuse
 FU6 : Field fuse
 IPM1,IPM2 : Intelligent power module
 L : Live
 L1 : Coil
 L1R : Reactor
 M1C : Compressor motor
 M1F : Fan motor
 MRCW,MRC30 : Magnetic relay

N : Neutral
 Q1L : Overload protector
 PCB1,PCB2,PCB3 : Printed circuit board
 S10,S11,S20,S40 : Connector
 S50,S70,S80,S90 : Thermistor
 S100,S110,HL3 : Thermistor
 R1T,R2T,R3T : Thermostat
 SIT : Thermostat

SA1 : Surge arrester
 Q1D : Earth leak detector
 SW1 : Forced operation switch
 V1,V2,V3 : Varistor
 X1M : Terminal strip
 Y1E : Electronic expansion valve coil
 Y1R : Reversing solenoid valve coil
 Z1C,Z2C,Z3C : Ferrite core
 PE : Protective earth

Notes

1. Refer to purchasing specification AS303002, unless otherwise specified.
2. Size: Length 105 X Width 185.
3. Refer to the nameplate for the power requirements.