

RXL50J

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXS50J	RXL50J	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20	66	6.3	53	0.27	23	0.15
		50 - 230					6.0				
		50 - 240					5.7				
FVXS50F	RXL50J	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20	69	6.7	53	0.27	48	0.10
		50 - 230					6.3				
		50 - 240					6.1				

3D080813

SYMBOLS

MCA	: Min. Circuit Amps (A)
MFA	: Max. Fuse Amps (A)
RLA	: Rated Load Amps (A)
OFM	: Outdoor fan motor
IFM	: Indoor Fan Motor
FLA	: Full Load Amps (A)
W	: Fan Motor Rated Output (W)
RHz	: Rated operating frequency (Hz)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19°CWB
Outdoor temp.: 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.