

RXLG25-35K

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXG25/JW FTXG25/JA	RXLG25K	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	46	2.8	23	0.23	40	0.15
							2.6				
							2.5				
FTXG35/JW FTXG35/JA	RXLG35K	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	68	4.7	23	0.23	40	0.15
							4.4				
							4.2				

3D066215B

SYMBOLS

- MCA
- :
- Min. Circuit Amps (A)
- MFA
- :
- Max. Fuse Amps (A)
- RLA
- :
- Rated Load Amps (A)
- OFM
- :
- Outdoor fan motor
- IFM
- :
- Indoor Fan Motor
- FLA
- :
- Full Load Amps (A)
- W
- :
- Fan Motor Rated Output (W)
- RHz
- :
- Rated operating frequency (Hz)

NOTES

1.
- RLA is based on the following conditions:
- Indoor temp.: 27°CDB/19°CWB
- Outdoor temp.: 35°CDB
2.
- Maximum allowable voltage variation between phases is 2%.
3.
- Select wire size based on the larger value of MCA.
4.
- Instead of fuse, use circuit breaker.