

RXLG25-35K

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FVXG25K	RXLG25K	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	47	2.6	23	0.23	32	0.16
		50 - 230					2.5				
		50 - 240					2.4				
FVXG35K	RXLG35K	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	72	4.4	23	0.23	32	0.16
		50 - 230					4.2				
		50 - 240					4.0				

3D072090A

	SYMBOLS
MCA	: Min. Circuit Amps (A)
MFA	: Max. Fuse Amps (A)
RLA	: Rated Load Amps (A)
OFM	: Outdoor fan motor
IFM	: Indoor Fan Motor
FLA	: Full Load Amps (A)
W	: Fan Motor Rated Output (W)
RHz	: Rated operating frequency (Hz)

	NOTES
1.	RLA is based on the following conditions: Indoor temp.: 27°CDB/19°CWB Outdoor temp.: 35°CDB
2.	Maximum allowable voltage variation between phases is 2%.
3.	Select wire size based on the larger value of MCA.
4.	Instead of fuse, use circuit breaker.