

RXS-F

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXS71G	RXS71F	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20.0	57	10.3	66	0.40	43	0.19
		50 - 230					9.9				
		50 - 240					9.4				
FTXS60G	RXS60F	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20.0	84	8.7	53	0.32	43	0.16
		50 - 230					8.3				
		50 - 240					7.9				

3D056032D

SYMBOLS	
MCA	: Min. Circuit Amps (A)
MFA	: Max. Fuse Amps (A)
RLA	: Rated Load Amps (A)
OFM	: Outdoor fan motor
IFM	: Indoor Fan Motor
FLA	: Full Load Amps (A)
W	: Fan Motor Rated Output (W)
RHz	: Rated operating frequency (Hz)

- | NOTES | |
|-------|---|
| 1. | RLA is based on the following conditions:
Indoor temp.: 27°CDB/19.0°CWB
Outdoor temp.: 35°CDB |
| 2. | Maximum allowable voltage variation between phases is 2%. |
| 3. | Select wire size based on the larger value of MCA. |
| 4. | Instead of fuse, use circuit breaker. |

Minimum Ssc value: kVA
Equipment complying with EN61000-3-12