

RXS25K

Representative unit combination		Power supply				COMP		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FVXS25F	RXS25K	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	10	46	3.0	23	0.23	48	0.05
		50 - 230					2.8				
		50 - 240					2.7				
FLXS25B	RXS25K	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	9.75	10	46	2.7	23	0.23	34	0.34
		50 - 230					2.5				
		50 - 240					2.4				

3D070944B

SYMBOLS		NOTES	
MCA	: Min. Circuit Amps. (A)	1	RLA is based on the following conditions: Indoor temp.: 27°CDB/19.0°CWB Outdoor temp.: 35°CDB
MFA	: Max. Fuse Amps (A)	2	Maximum allowable voltage variation between phases is 2%.
RLA	: Rated Load Amps. (A)	3	Select wire size based on the larger value of MCA.
OFM	: Outdoor Fan Motor.	4	Instead of fuse, use circuit breaker.
IFM	: Indoor Fan Motor.		
FLA	: Full Load Amps. (A)		
W	: Fan Motor Rated Output (W)		
RHz	: Rated operating frequency (Hz)		