

Representative Unit Combination		Power Supply				Comp		OFM		IFM	
Indoor Unit	Outdoor Unit	Hz - Volts	Voltage Range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXS50J2V1B	RXS50J2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20	66	6.3	53	0.27	23	0.15
		50 - 230					6.0				
		50 - 240					5.7				
FVXS50FV1B	RXS50J2V1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20	69	6.7	53	0.27	48	0.10
		50 - 230					6.3				
		50 - 240					6.1				

NOTES

1. RLA is based on the following conditions,
Indoor temp. 27 C DB/19.0 C WB.
Outdoor temp. 35 C DB.
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.

SYMBOLS

- MCA : Min. Circuit Amps (A)
 MFA : Max. Fuse Amps (A)
 RLA : Rated Load Amps (A)
 OFM : Outdoor Fan Motor
 IFM : Indoor Fan Motor
 FLA : Full Load Amps (A)
 W : Fan Motor Rated Output (W)
 RHz : Rated Operating Frequency (Hz)