

RXS71FA
RKS71FA

Representative unit combination		Power supply				Comp		OFM		IFM	
Indoor unit	Outdoor unit	Hz-Volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXS71GV1B	RXS71FAV1B	50 - 220	Max. 50Hz 264V Min. 50Hz 198V	19.75	20.0	57	10.3	66	0.40	43	0.19
		50 - 230					9.9				
		50 - 240					9.4				

Minimum Ssc value	kVA	Equipment complying with EN61000-3-12
-------------------	-----	---------------------------------------

SYMBOLS

MCA : Min. Circuit Amps (A)
MFA : Max. Fuse Amps (A)
RLA : Rated Load Amps (A)
OFM : Outdoor Fan Motor
IFM : Indoor Fan Motor
FLA : Full Load Amps (A)
W : Fan Motor Rated Output (W)
RHz : Rated Operating frequency (Hz)

NOTES

- RLA is based on the following conditions.
 - Indoor temp. 27°C DB/19.0°C WB.
 - Outdoor temp. 35°C DB.
- Maximum allowable voltage variation between phases is 2%.
- Select wire size based on the larger value of MCA.
- Instead of fuse, use circuit breaker.