FTXJ-AB
FTXJ-AS
FTXJ-AW

Option kit	Product name	Remark New Perfera	Remark New floor stand	Remark Emura 3	Applicable models	FTXJ20A2V1BW	FTXJ20A2V1BS	FTXJ20A2V1BB	FTXJ25A2V1BW	FTXJ25A2V1BS	FTXJ25A2V1BB	FTXJ35A2V1BW	FTXJ35A2V1BS	FTXJ35A2V1BB	FTXJ42A2V1BW	FTXJ42A2V1BS	FTXJ42A2V1BB	FTXJ50A2V1BW	FTXJ50A2V1BS	FTXJ50A2V1BB
					Class	20	20	20	25	25	25	35	35	35	42	42	42	50	50	50
					Casing	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3	Emura 3
					Factory	DICz														
						Emura 3														
Wired remote control	BRC073A1	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Extension cord for wired remote control (·3·m)	BRCW901A03					✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Extension cord for wired remote control (·8·m)	BRCW901A08					✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Intelligent Tablet Controller	DCC601A51	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Wiring adaptor (normal open contact - normal open pulse contact)	KRP413AB1S		②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Interface adaptor for DIII-NET	KRP928BB2S		②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Central remote control	DCS302CA51	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Unified ON/OFF controller	DCS301BA51	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Schedule timer	DST301BA51	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Intelligent Touch Manager	DCM601A5A	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
·Modbus· interface	EKMBDXA7V1	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Modbus gateway	RTD-RA	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
·KNX· interface	KLIC-DD	②③	②③	②③		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Titanium apatite deodorising filter without frame	KAF970A46	①	①	①		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Silver particle filter (Ag-ion) with frame	KAF057A41	①		①		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Conversion wire harness	EKRS21					✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Notes

1. Standard accessory
2. This option features a(n) ·S21· connector. To connect this option to the indoor unit, therefore conversion wire harness ·EKRS21· is required.
3. This option cannot operate together with the wireless LAN functionality that is a standard feature of the indoor unit.
   When connecting this option to the indoor unit, turn off the indoor unit's wireless LAN functionality.