

RX20-35K

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	1	2	3	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
FTX20JV	RX20K	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	36	2,2	0,033	0,17	0,016	0,12
FTX25JV	RX25K	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	48	3,2	0,033	0,17	0,016	0,12
FTX35JV	RX35K	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	70	4,7	0,033	0,17	0,016	0,12

Notes

- ¹ The ·RLA· is based on the following conditions.
Indoor temperature :27°C DB / ·19°C WB
Outdoor temperature :35°C DB
- ² Select the wire size according to the MCA.
- ³ The maximum allowable voltage that is unbalanced between phases is ·2·%.
- ⁴ Use a circuit breaker instead of a fuse.

Symbols

- ¹ Hz
² Voltage
³ Voltage range
MCA Minimum Circuit Ampere (A)
MFA Maximum Fuse Ampere (A)
RLA Rated load amps [A]

- OFM Outdoor fan motor
IFM Indoor fan motor
FLA Full Load Ampere (A)
kW Fan motor rated output [kW]
RHz Rated operating frequency [Hz]

3D092100B