

**RX-KM**

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor unit	Outdoor unit	Hz	Voltage	Voltage range	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
FTX25KMV1B	RX25KMV1B	50	220 230 240	Max. 50Hz 264V Min. 50Hz 198V	12,1	16	50	3,2	0,01	0,13	0,022	0,20
FTX35KMV1B	RX35KMV1B	50	220 230 240	Max. 50Hz 264V Min. 50Hz 198V	12,2	16	74	4,9	0,02	0,15	0,028	0,23

Notes

- The RLA is based on the following conditions.  
Indoor temperature 27°C DB / 19°C WB  
Outdoor temperature 35°C DB
- Select the wire size according to the MCA.
- The maximum allowable voltage that is unbalanced between phases is 2%.
- Use a circuit breaker instead of a fuse.

Symbols

- MCA: Minimum Circuit Ampere (A)  
MFA: Maximum Fuse Ampere (A)  
RLA: Rated load amps [A]  
OFM: Outdoor fan motor  
IFM: Indoor fan motor  
FLA: Full Load Ampere (A)  
kW: Fan motor rated output [kW]  
RHz: Rated operating frequency [Hz]